
Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1. Product Identifier: CS-3600 Sealant / Top Coat (One Part)
 - Product Name: Sealing Compound / Top Coat (One Part)
 - Product reference: CS-3600 Sealant /Top Coat (One Part)

1.2. Product Use:
 - Sealant /Top Coat

1.3. Manufacturer's Name:
CAGE Code: 14439
Flamemaster Corp.
Chem Seal Division
13576 Desmond Street
Pacoima, CA 91333 – USA

1.3.1 Suppliers Name (if not manufacturer)

Technical Contact:
Flamemaster Corp.
Tel: 818-890-1401
Fax: 818-890-6001
www.flamemaster.com

1.4. Emergency Telephone:
 Chemtrec – Chemtrec International
 800-424-9300 (North America)
 703-527-3887 (Outside North America))

Specification: AMS 4383 ONE PART SEALANT/TOP COAT

NSN:	8030-00-664-4019 CS3600 PINT	8030-00-664-4954 CS3600 QUART	8030-000857-3604 CS3600 GALLON	8030-01-255-0439 CS3600 5-GALLON	
-------------	---------------------------------	----------------------------------	-----------------------------------	-------------------------------------	--

Section -2. HAZARD (S) IDENTIFICATION

OSHA/HCS STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

CLASSIFICATION OF THE MIXTURE:

FLAMMABLE LIQUIDS - Category 2
ACUTE TOXICITY (INHALATION) - CATEGORY 4
ACUTE TOXICITY, ORAL (CATEGORY 4)
ACUTE TOXICITY, DERMAL (CATEGORY 4)
SKIN SENSITIZATION - Category 1
SKIN IRRITATION (CATEGORY 2)
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 2
MUTAGEN, (CATEGORY 2)
ASPIRATION HAZARD - (CATEGORY 1)
TOXIC TO REPRODUCTION (UNBORN CHILD) - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3
SPECIFIC TARGET ORGAN TOXICITY-REPEAT EXPOSURE -CATEGORY 2
CHRONIC, AQUATIC - CATEGORY 4

GHS LABEL REQUIREMENTS

HAZARD PICTOGRAMS



SIGNAL WORD : DANGER

HAZARD STATEMENTS:

HIGHLY FLAMMABLE LIQUID AND VAPOR - (H225)
HARMFUL IF SWALLOWED, IN CONTACT WITH SKIN OR IF INHALED- (H302+H312+H332)
CAUSES SERIOUS EYE DAMAGE - (H318)
MAY CAUSE AN ALLERGIC SKIN REACTION - (H317)
CAUSES SKIN IRRITATION - (H315)
SUSPECTED OF DAMAGING THE UNBORN CHILD - (H361d)
MAY CAUSE DROWSINESS OR DIZZINESS - (H336)
SUSPECTED OF CAUSING GENETIC DEFECTS - (H341)
SUSPECTED OF CAUSING CANCER - (H351)
MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE - (H373)
MAY CAUSE RESPIRATORY IRRITATION - (H335)
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - (H304)
MAY CAUSE LONG LASTING HARMFUL EFFECTS TO AQUATIC LIFE - (H413)

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

PRECAUTIONARY STATEMENTS:

- P101+P102+P103: If medical advice is needed, have product container or label at hand. Keep out of reach of children.
- Read label before use
- P202: Do not handle until all safety precautions have been read and understood
- P210: Keep away from heat/sparks/open flames and hot surfaces-No Smoking
- P240:Ground/bond container and receiving equipment
- P261+P262+P263+P264:Avoid breathing dust/fumes/gas/mist/vapours/spray.Do not get in eyes , on skin, or on clothing. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling.
- P270+P271+P273: Do not eat drink or smoke when using this product. Use only outdoors or in a well ventilated area. Avoid release to the environment.
- P281+P280: Use personal protective equipment as required. Wear protective gloves/ protective clothing/ eye protection/face protection
- P301+P310+P331: If swallowed: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting.
- P305+P351+P338+P315: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,if present and easy to do. Continue rinsing. Get immediate medical advice attention.
- P304+P340+P314: If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell
- P342+P340+P315: If experiencing respiratory symptoms: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice/attention.
- P302+P352: If on skin (or in hair) : Wash with plenty of soap and water. If skin irritation occurs seek medical attention
- P306+P361: If on clothing: Remove/ take off immediately all contaminated clothing
- P402+P403+P404: Store in a dry place. Store in a well ventilated space. Store in a closed container.
- P233+P234+P235: Keep container tightly closed. Keep only in original container. Keep cool.

SUPPLEMENTAL LABEL ELEMENTS:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of concentrations above recommended limits causes headaches, drowsiness and nausea and could lead to unconsciousness or possibly death.

1-component mixtures: formaldehyde is released during the curing phase. Formaldehyde may cause irreversible effects, is irritating to the mucous membranes and may cause the skin to become sensitized.

Avoid any contact with skin or clothing and wash thoroughly after handling.

Emits toxic fumes when heated.

Sanding and grinding dust may be harmful if inhaled.

HAZARDS NOT OTHERWISE CLASSIFIED:

Prolonged or repeated exposure may dry skin and / or cause skin irritation.

Section -3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical family : Mixture of organic compounds

For the hazards of the composition, (SDS see Section 2).

2 BUTANONE

Cas# 78-93-3

<=80% by weight

OSHA HAZARDS: FLAMMABLE LIQUID,TARGET ORGAN EFFECT,IRRITANT

TARGET ORGANS: CENTRAL NERVOUS SYSTEM

GHS CLASSIFICATION: 2-BUTANONE

FLAMMABLE LIQUIDS (CATEGORY 2)

ACUTE TOXICITY,ORAL (CATEGORY 5)

ACUTE TOXICITY,INHALATION (CATEGORY 5)

EYE IRRITATION (CATEGORY 2A)

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE(CATEGORY3) CENTRAL NERVOUS SYSTEM.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage, use and disposal are beyond our control and may be beyond our knowledge.

Phenol, 3% <= conc <10%, aqueous solutions **Cas# 108-95-2** **<= 20% by weight**

ACUTE TOXICITY, ORAL (CATEGORY 3) - H301

ACUTE TOXICITY, DERMAL (CATEGORY 3) - H311

ACUTE TOXICITY (INHALATION) - CATEGORY 3 - H331

SKIN CORROSION (CATEGORY 1B) - H314

MUTAGEN, (CATEGORY 2) - H341

SPECIFIC TARGET ORGAN TOXICITY-REPEAT EXPOSURE -CATEGORY 2 - H373

Section -4. FIRST-AID MEASURES

General: When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

Eye contact: Check for and remove any contact lenses. Irrigate with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek immediate medical attention.

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

Section -5. FIRE-FIGHTING MEASURES

Extinguishing agents

Recommended: Universal resistant foam, CO₂, water, powder.

Agents to avoid: None known

Attention

Promptly remove all persons in the event of a fire from the fire area. If safe to do so, remove all containers from fire area as well.

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Do not allow run-off from fire fighting to enter drains or water courses.

HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE: CARBON DIOXIDE, CARBON MONOXIDE, HALOGENATED COMPOUNDS, AND METAL OXIDE / OXIDES, SMOKE, CORROSIVE VAPORS, SULFUR OXIDES, UNIDENTIFIED ORGANIC COMPOUNDS, FLAMMABLE GASES, OXIDES OF CARBON AND NITROGEN, AIRBORNE SOLIDS, AND OTHER HAZARDOUS MATERIALS.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

Section -6. ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

Section -7. HANDLING AND STORAGE

7.1 Handling:

No smoking, eating and drinking during handling.

Avoid exposure during pregnancy.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

7.2 Storage:

Observe label precautions. Store between 32/F and 95/F (0/C and 35/C) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Engineering measures:

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

8.2 Exposure limits

Work place exposure limits (8 hour)

Substance	OSHA	ACGIH TLV
2-BUTANONE (MEK) *	200 ppm	200 ppm
Phenol, 3% <= conc <10%, aqueous solutions *	5 ppm (TWA)	5 ppm (TWA)
* can be absorbed through skin		

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

9. PHYSICAL AND CHEMICAL PROPERTIES

- | | |
|--------------------------------------------------|-----------------------------------------------|
| • Physical state at: 68 ° F (20 ° C) Liquid | • Ph : 6.0 |
| • Flash point: 3 Deg. C--- 38 Deg. F Method: TCC | • Volatile % by volume: 84.0 % |
| • Specific gravity at: 68 ° F (20 ° C) .88 g/cm3 | • Vapor pressure at: 68 ° F (20 ° C) 46 mm Hg |
| • Vapor Density: 2.41 | • Color: RED |
| • Lower Explosive Limit-2.3 | • Appearance: SYRUP |
| • Upper Explosive Limit- 11.0 | • Odor: Ketone odor |
| • Miscibility in water at 20 ° C: Moderate | • Boiling Point: N/A |
| | • Material Supports Combustion : Yes |

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see SDS section 7). In case of combustion, may produce hazardous decomposition products such as :

- | | | |
|--------------------|---------------------------------|----------------------------------|
| • Carbon Monoxide | • Halogenated Compounds | • Unidentified Organic Compounds |
| • Carbon Dioxide | • Oxides of Carbon and Nitrogen | • Flammable Gases |
| • Smoke | • Metal Oxide / Oxides | • Other Hazardous Materials |
| • Corrosive vapors | • Sulfur Oxides | • Airborne Solids |

11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs of overexposure include headache, dizziness, fatigue, muscular weakness, drowsiness, reduced fetal weight, increase in fetal deaths, skeletal malformations, and in extreme cases loss of consciousness

Repeated or prolonged contact with the preparation may cause Defatting of the skin resulting in non-allergic dermatitis and absorption through the skin.

The liquid splashed in the eyes causes serious eye irritation and damage.

Irritating to mouth, throat and stomach. Ingestion causes reduced fetal weight, increased fetal deaths and skeletal malformations

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

ACUTE TOXICITY:

PRODUCT:	RESULT	SPECIES	DOSE	EXPOSURE
Butanone	LC50 Inhalation Vapor	Rat	11243 ppm	4 Hours
	LD50 Dermal	Rabbit	6480 mg/kg	-
	LD50 ORAL	Rat	2737 mg/kg	-
Phenol, 3%<= conc <10% aqueous solutions	ATE US (ORAL)		100 mg/kg Body Weight	
	ATE US (DERMAL)		300 mg/kg Body Weight	
	ATE US (GASES)		700 ppmV/4h	
	ATE US (VAPORS)		3 mg/l/4h	
	ATE US (DUST, MIST)		.5 mg/4h	

Harmful if Swallowed

Harmful if Inhaled

Harmful if in Contact with the Skin

Suspected of Causing Cancer. Risk depends on level and duration of exposure.

Causes Serious Eye Damage

May Cause Respiratory Irritation

May Cause Skin Irritation

May Cause an Allergic Skin Reaction

Suspected of Damaging the Unborn Child.

May Cause Drowsiness and Dizziness

Suspected of Causing Genetic Defects

May Cause Damage to Organs Through Prolonged or Repeated Exposure

May Be Fatal if Swallowed and Enters Airways

CARCINOGENICITY:

INGREDIENT	IARC	OSHA	NTP	CAS#
Formaldehyde *	1		2	50-00-0

* Not Present in Reportable Quantities

SPECIFIC TARGET ORGAN TOXICITY-STOT (SINGLE EXPOSURE)

BUTANONE - CATEGORY 3

ASPIRATION TOXICITY:

Aspiration into the lungs when swallowed or vomited can be fatal.

TARGET ORGANS: BRAIN, BLOOD, KIDNEYS, LUNGS, REPRODUCTIVE SYSTEM, LIVER, HEART, PERIPHERAL NERVOUS SYSTEM, GASTROINTESTINAL TRACT, UPPER RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, EYE, LENS AND/OR CORNEA. CARDIOVASCULAR SYSTEM, NERVOUS SYSTEM.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

TOXICITY:

BUTANONE Cas#78-93-3

Lepomis Macrochirus	LC50	1690 mg/l	(LETHAL)	96 HRS
Daphnia Magna	EC50	308 mg/l	(LOCOMOTOR EFFECT)	48 HRS
Pimephales Promelas	LC50	2990 mg/l		96 HRS

PERSISTENCE and DEGRADABILITY:

BUTANONE - Readily biodegradable in water. Biodegradable in soil.

Biochemical Oxygen Demand (BOD) - 1.92 g O₂/g substance

Chemical Oxygen Demand (COD) - 2.31 g O₂/g substance

THOD - 2.44 g O₂/g substance

BOD (% of THOD) - >% THOD (5 days) > 0.5

Phenol, 3% <= conc <10% aqueous solutions - Readily biodegradable in water. Biodegradable in soil.

Biochemical Oxygen Demand (BOD) - 1.68 g O₂/g substance

Chemical Oxygen Demand (COD) - 2.28 g O₂/g substance

THOD - 2.38 g O₂/g substance

BOD (% of THOD) - 0.71 % THOD

Bioaccumulative Potential :

Product / Ingredient	LogP(ow)	BCF	Potential
Butanone	.29	-	low
Phenol, 3% <= conc <10%, aqueous solutions :	1.46	1276-1496 (Pimephales Promelas)	

Mobility in Soil : Not Available

13. DISPOSAL CONSIDERATIONS

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.

Dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or landfill.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

14. TRANSPORT INFORMATION

DOT: § 172.101 HAZARDOUS MATERIALS TABLE
 UN Number: 1133
 Proper Shipping Name: Adhesives
 Labels: Flammable Liquid

IATA:
 UN Number: 1133
 Proper Shipping Name: Adhesives
 Labels: Flammable Liquid

 Hazard Class: 3 Subclass: NO
 Packaging Group: II
 Passenger Air Packing Instruction : 309
 Passenger aircraft: 60 Liter (16 gallon)
 Cargo Air Packing Instruction : 310
 Cargo aircraft only: 220 Liter (58 gallon)



Hazard Class: 3 Subclass: NO
 Packaging Group: II
 Limited Quantity: Passenger aircraft: 60 Liter (16 gallon)
 Cargo aircraft only: 220 Liter (58 gallon)
 Vessel stowage: A
 ERG: 128
 NMFC: 4620 SUB.6 – CL.60
 Schedule B # 3506.91.0000

IMDG:
 UN Number: 1133
 Proper Shipping Name: Adhesives
 Label: 3
 Hazard Class: 3 Subclass: NO
 Packaging Group: II
 EMS No: F, E – S, D

15. REGULATORY INFORMATION

US Regulations Federal

chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA)	Chemical Name	CAS No	Weight %	Threshold limit (Reporting Value)
	2-BUTANONE	78-93-3	<=80%	Unknown
	Phenol, 3% <=conc <10% aqueous solutions	108-95-2	<=20%	Unknown

SARA notifications must remain attached to this SDS. Any copies and /or distribution of this SDS must include all SARA notifications.

SARA SECTION 302

Phenol, 3% <= conc <10% aqueous solutions - CAS#108-95-2 - 500-10000 lbs (Threshold Planning Quantity)

SARA SECTION 304

Phenol, 3% <= conc <10% aqueous solutions - CAS#108-95-2 - 1000 lbs (Reportable Quantity)

SARA SECTION 311/312

Butanone: Fire Hazard, Immediate (acute) Health Hazard

SARA notifications must remain attached to this SDS. Any copies and /or distribution of this SDS must include all SARA notifications.

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

US Regulations State

California Proposition 65 (Developmental – Female)	2-BUTANONE	78-93-3	<15%	>=1.0%
Massachusetts	2-BUTANONE	78-93-3	<15%	>=1.0%
New Jersey	2-BUTANONE	78-93-3	<15%	>=1.0%
Pennsylvania	2-BUTANONE	78-93-3	<15%	>=1.0%
Rhode Island	2-BUTANONE	78-93-3	<15%	>=1.0%

California Prop. 65 : Warning

This product contains a chemical known by the State of California to cause cancer, birth defects and other reproductive harm.

Canada



Class B – Flammable
2-BUTANONE



Class D - Poisonous and Infectious
materials Division 2: Materials Causing
Other Toxic Effects D2A
2-BUTANONE Cas#78-93-3

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

Listed National Pollutant Release Inventory (NPRI):

2-BUTANONE CAS#78-93-3

Phenol, 3% <= conc <10% aqueous solutions - CAS#108-95-2

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

16. OTHER INFORMATION

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0

* Customer and / or end user is responsible for determining Personal Protection Equipment

NFPA

HMIS

Notice to reader:

This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.

This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.

Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.

Preparer:	Flamemaster / Compliance Rev-A 5/20/2015 Supersedes (conversion)	Revision Notes: A	Conversion to ANSI format
Containers:	plastic jars, metal cans cartridge kits		

Limited Quantity See SDS Section 14

Maximum container size 50 Gallons / 190 Liters

End of Safety Data Sheet