



FLAMEMASTER
Flamemaster Corp.
13576 Desmond Street
Pacoima, CA 91331 - USA

SAFETY DATA SHEET
APRIL 2016

File: CS5306B GSA 07-10
Polythioether Quick Repair
Fuel Tank Sealant/Catalyst

Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1. Product Identifier: CS-5306 Part B All Classes (all application times)
 - Product Name: Polythioether Quick Repair Fuel Tank Sealant / Catalyst Part B
 - Product reference: CS-5306-B

1.2. Product Use:
 - Polythioether Quick Repair Fuel Tank Sealant

1.3. Manufacturer's Name:
CAGE Code: 14439
Flamemaster Corp.
Chem Seal Division
13576 Desmond Street
Pacoima, CA 91333 – USA

1.3.1 Suppliers Name (if not manufacturer)

Technical Contact:
Flamemaster Corp.
Tel: 818-890-1401
Fax: 818-890-6001
www.flamemaster.com

1.4. Emergency Telephone:
 Chemtrec – Chemtrec International
 800-424-9300 (North America)
 703-527-3887 (Outside North America))

	Specification: AMS 3277 TYPE 1		Catalyst Part B	ALL CLASSES	
NSN:	8030-01-330-0726 CS5306A1/4 2.5OZ	8030-01-330-6568 CS5306A1/2 2.5 OZ	8030-01-330-0730 CS5306A1/2 6OZ.	8030-01-330-0728 CS5306 A1/2 1/2 PT	8030-01-330-0729 CS5306 A1/2 PINT
	8030-01-330-0732 CS5306A1/2 QUART	8030-01-330-0731 CS5306A1/2 GAL	8030-01-330-0733 CS5306A1/2 5-GAL	8030-01-330-0734 CS5306A1/2 50-GAL	8030-01-330-0745 CS5306A1 2.5 OZ
	8030-01-330-3437 CS5306A1 6OZ.	8030-01-329-9999 CS5306A1 1/2 PINT	8030-01-330-2578 CS5306A1 PINT	8030-01-330-0737 CS5306A1 QUART	8030-01-330-0736 CS5306A1 GAL
	8030-01-330-2579 CS5306A1 5-GAL	8030-01-329-9998 CS5306A1 50-GAL	8030-01-331-3233 CS5306B-1 50 GAL	8030-01-290-5138 CS5306B-2 2.5 OZ	8030-01-290-5139 CS5306B-2 6OZ
	8030-01-290-5134 CS5306B1/4 2.5 OZ	8030-01-290-5135 CS5306B1/4 6OZ	8030-01-290-5136 CS5306B1/2 2.5OZ	8030-01-290-5137 CS5306B1/2 6OZ	8030-01-330-6571 CS5306B1/2 1/2 PT
	8030-01-330-8631 CS5306B1/2 PINT	8030-01-330-8632 CS5306B1/2 QUART	8030-01-330-6569 CS5306B1/2 GAL	8030-01-330-6570 CS5306B1/2 5-GAL	8030-01-330-6572 CS5306B-1 50-GAL
	8030-01-331-0694 CS5306B-1 1/2 PT	8030-01-330-9114 CS5306B-1 PINT	8030-01-330-9500 CS5306B-1 QUART	8030-01-330-9501 CS5306B-1 GAL	8030-01-331-0693 CS5306B-1 5-GAL
	8030-01-438-4103 CS5306 B2 GAL				

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

Section -2. HAZARD (S) IDENTIFICATION

SKIN CORROSION / IRRITATION - CATEGORY 2

SERIOUS EYE DAMAGE / EYE IRRITATION - CATEGORY 2

SKIN SENSITIZATION 1,

CARCINOGENICITY 2,

ASPIRATION HAZARD - (CATEGORY 1)

ACUTE TOXICITY,ORAL - CATEGORY 4

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE - (RESPIRATORY EFFECT) - CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE - (NARCOTIC EFFECT) - CATEGORY 3

TOXIC TO REPRODUCTION - CATEGORY 2

REPRODUCTIVE TOXICITY, EFFECTS ON OR VIA LACTATION

AQUATIC (CHRONIC) - CATEGORY 4

OSHA / HCS STATUS : THIS MATERIAL IS CONSIDERED HAZARDOUS BY THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

Human and Environmental Hazards:

HAZARD STATEMENTS:

HARMFUL IF SWALLOWED - H302

CAUSES SKIN IRRITATION - H315

CAUSES SERIOUS EYE IRRITATION - H319

MAY CAUSE AN ALLERGIC SKIN REACTION - H317

SUSPECTED OF CAUSING CANCER - H351

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - H304

MAY CAUSE DROWSINESS OR DIZZINESS - H336

MAY CAUSE HARM TO BREAST FED CHILDREN - H362

SUSPECTED OF DAMAGING FERTILITY. SUSPECTED OF DAMAGING THE UNBORN CHILD - H361fd

MAY CAUSE RESPIRATORY IRRITATION - H335

MAY CAUSE LONG LASTING HARMFUL EFFECTS TO AQUATIC LIFE - H413

HAZARD PICTOGRAMS:



SIGNAL WORD:

DANGER

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage,use and disposal are beyond our control and may be beyond our knowledge.

Full text of P statements associated to this compound:

- P101+P102+P103: If medical advice is needed, have product container or label at hand. Keep out of reach of children.
- Read label before use
- P202: Do not handle until all safety precautions have been read and understood
- P210: Keep away from heat/sparks/open flames and hot surfaces-No Smoking
- P240:Ground/bond container and receiving equipment
- P261+P262+P263+P264:Avoid breathing dust/fumes/gas/mist/vapours/spray.Do not get in eyes , on skin, or on clothing. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling.
- P270+P271+P273: Do not eat drink or smoke when using this product. Use only outdoors or in a well ventilated area. Avoid release to the environment.
- P281+P280: Use personal protective equipment as required. Wear protective gloves/ protective clothing/ eye protection/face protection
- P301+P310+P331: If swallowed: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting.
- P305+P351+P338+P315: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,if present and easy to do. Continue rinsing. Get immediate medical advice attention.
- P304+P340+P314: If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell
- P342+P340+P315: If experiencing respiratory symptoms: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice/attention.
- P302+P352: If on skin: Wash with plenty of soap and water
- P306+P361: If on clothing: Remove/ take off immediately all contaminated clothing
- P402+P403+P404: Store in a dry place. Store in a well ventilated space. Store in a closed container.
- P233+P234+P235: Keep container tightly closed. Keep only in original container. Keep cool.

ADDITIONAL LABEL ELEMENTS: Dust from grinding or abrading may be harmful if inhaled.

Trimethoxysilanes may form methanol if hydrolyzed or ingested. If ingested, methanol may be harmful or cause blindness. It may also be fatal. This product emits toxic (poisonous) fumes when heated and (or) burned.

HAZARDS NOT OTHERWISE CLASSIFIED: None Known

In the event of sanding, grinding, or abrading:

H372 Causes damage to organs through prolonged or repeated exposure.

Section -3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical family : Mixture of organic compounds

For the hazards of the composition, (SDS see Section 2).

BISPHENOL-A-EPOXY RESIN	CAS# 25068-38-6	EC# 500-033-5	<65% By Weight
OSHA HAZARDS: Skin Sensitiser,Irritant			
GHS CLASSIFICATION: EPOXY RESIN			
SKIN IRRITATION (CATEGORY 2)			
EYE IRRITATION (CATEGORY 2A)			
SKIN SENSITIZATION (CATEGORY 1)			
ACUTE AQUATIC TOXICITY (CATEGORY 2)			
CHRONIC AQUATIC TOXICITY (CATEGORY 2)			

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage,use and disposal are beyond our control and may be beyond our knowledge.

HYDANTOIN EPOXY RESIN CAS# 15336-82-0 EC# 239-366-3 < 10% By Weight
THIS MATERIAL IS CONSIDERED HAZARDOUS BY THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)
MAY BE CORROSIVE
CAUSES EYE BURNS (RISK OF SERIOUS DAMAGE TO EYES)
TOXIC BY INGESTION
CAUSES SKIN IRRITATION
CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA
CONTAINS MATERIAL WHICH MAY CAUSE HERITABLE GENETIC EFFECTS
VERY TOXIC BY INHALATION
MAY CAUSE DAMAGE TO THE FOLLOWING ORGANS: LIVER

CHEMICAL NAME: CARBON BLACK CAS# 1333-86-4 EC# 215-609-9 <10% By Weight
NOT CLASSIFIED

CHEMICAL NAME:
Poly[(phenyl glycidyl ether)-co-formaldehyde] CAS# 28064-14-4 EC# N/A <40% By Weight
SKIN SENSITIZATION - Sub Category 1B

CHEMICAL NAME: CALCIUM CARBONATE CAS# 471-34-1 EC# N/A <35% By Weight

CHEMICAL NAME: IRON OXIDE (SYNTHETIC) CAS# 12227-89-3 EC# 235-442-5 <20% By Weight
Hazards Identification: This product may auto-oxidize if exposed to heat. Inhalation can cause lung irritation or fibrosis.
THIS MATERIAL IS CONSIDERED HAZARDOUS BY THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)
Due to its potential to auto-oxidize (self heat).

CHEMICAL NAME:
(3-Glycidyloxypropyl)trimethoxysilane CAS#2530-83-8 EC#219-784-2 <10% By Weight
GHS CLASSIFICATION in accordance with 29 CFR 1910 (OSHA HCS)
SERIOUS EYE DAMAGE (CATEGORY 1), H318
ACUTE AQUATIC TOXICITY (CATEGORY 3), H402

Section -4. FIRST-AID MEASURES

General: When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

Eye contact: Check for and remove any contact lenses. Irrigate with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek immediate medical attention.

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

Section -5. FIRE-FIGHTING MEASURES

Extinguishing agents

Recommended: Universal resistant foam, CO₂, water, powder.

Agents to avoid: None known

Attention

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Do not allow run-off from fire fighting to enter drains or water courses.

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

Hazardous decomposition products include: Carbon Dioxide, Carbon Monoxide, Nitrogen Oxides, Smoke
Metal Oxide / Oxides, Halogenated Compounds, Toxic Fumes, Soot, Phenolics

Section -6. ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

Section -7. HANDLING AND STORAGE

7.1 Handling:

No smoking, eating and drinking during handling.

Avoid exposure during pregnancy/while nursing.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

7.2 Storage:

Observe label precautions. Store between 32/F and 95/F (0/C and 35/C) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Engineering measures:

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

8.2 Exposure limits

Work place exposure limits (8 hour)

Substance	ACGIH TLV
CALCIUM CARBONATE	TWA: 3 mg/m ³ 8 hours Form : Respirable
	TWA: 10 mg/m ³ 8 hours Form Total Dust
	OSHA PEL
	TWA: 5 mg/m ³ 8 hours Form: Respirable
	TWA: 15 mg/m ³ 8 hours Form: Total Dust
CARBON BLACK	ACGIH TLV
	TWA: 3 mg/m ³ 8 hours (Inhalable Fraction)
	OSHA PEL
	TWA: 3.5 mg/m ³ 8 hours
	ACGIH TLV
Synthetic Iron Oxide	15 mg/m ³

8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state at: 68 ° F (20 ° C) Liquid
- Flash point: 200 ° F (93 ° C) Method: TCC
- Relative Density : N/A
- Vapor Density: N/A
- Lower Explosive Limit (% vol.): N/A
- Upper Explosive Limit (% vol.): N/A
- Miscibility in water at 20 ° C: NEGLIGIBLE
- Material Supports Combustion. : Yes
- VOC : N/A
- % Solid (w/w) : N/A
- Vapor pressure at: 68 ° F (20 ° C) N/A
- Color: BLACK
- Appearance: PASTE
- Odor: NEGLIGIBLE OILY ODOR
- Boiling Point: Unknown

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see SDS section 7). In case of combustion, may produce hazardous decomposition products such as :

- Carbon monoxide
- Smoke
- Carbon Dioxide
- Oxides of nitrogen
- Metal Oxide / Oxides
- Halogenated Compounds
- Toxic Fumes
- Phenolics
- Soot

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health

ACUTE TOXICITY:

PRODUCT:	RESULT	SPECIES	DOSE	EXPOSURE
Bisphenol-A-Epoxy Resin	LD50 DERMAL	Rabbit	>2 g/kg	-
	LD50 ORAL	Rat	11.4 g/kg	-
Calcium Carbonate	LD50 ORAL	Rat	6450 mg/kg	-
Carbon Black	LD50 Dermal	Rabbit	>3 g/kg	-
	LD50 Oral	Rat	>15400mg/kg	-
Trimethoxysilane	LC50 Inhalation Dust & Mist	Rat	>5300 mg/m ³	4 hours
	LD50 Dermal	Rabbit	4.3 g/kg	-
	LD50 Oral	Rat	7.01 g/kg	-
Hydantoin Epoxy Resin	LD50 Oral	Rat	300 mg/kg	-
	LD50 Dermal	Rabbit	>3000 mg/kg	-
	LC50 Inhalation	Rat	>4.1 mg/cu.m	4 hours
Phenol-Formaldehyde	LD50 Oral	Rat	>4000 mg/kg	-
Novolac+Epichlorohydrin	LD50 Dermal	Rabbit	>2000 mg/kg	-

CARCINOGENICITY:

INGREDIENT	IARC	OSHA	NTP
Carbon Black, Respirable Powder	2B	-	-

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

Potential chronic health effects include the following:

May cause allergic reactions.

Suspected of causing cancer.

This Product is Harmful if Swallowed or Inhaled.

This Product also Causes Serious Eye Irritation.

This Product Causes Skin Irritation, Defatting of the Skin, and May Cause an Allergic Reaction or Skin Sensitization

MAY CAUSE DROWSINESS OR DIZZINESS

SUSPECTED OF DAMAGING FERTILITY. SUSPECTED OF DAMAGING THE UNBORN CHILD

MAY CAUSE HARM TO BREAST FED CHILDREN

Target Organs: lungs, skin, central nervous system, blood, kidneys, nervous system, liver, spleen, lymphatic system, cardiovascular system, upper respiratory tract, bone marrow, eye, lens, cornea

ASPIRATION HAZARD:

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Bioaccumulative Potential:

Not Available

Mobility in Soil:

Not Available

13. DISPOSAL CONSIDERATIONS

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.

React with base and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

14. TRANSPORT INFORMATION

DOT:	Not regulated
UN Number:	Not regulated
UN Proper Shipping Name :	N/A
Transport Hazard Class :	N/A
Packing Group :	N/A
Environmental Hazards :	No
Marine Pollutant Substances :	N/A

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage,use and disposal are beyond our control and may be beyond our knowledge.

IMDG**UN Number:**

3082

UN Proper Shipping Name :

Environmentally Hazardous Substance, Liquid, N.O.S.
(reaction product: bisphenol-A-(epichlorhydrin); epoxy resin,Phenol, polymer with formaldehyde, glycidyl ether (MW<=700))

Transport Hazard Class :

9

Packing Group :

III

Environmental Hazards :

Yes

Marine Pollutant Substances:

(reaction product: bisphenol-A-(epichlorhydrin); epoxy resin,Phenol, polymer with formaldehyde, glycidyl ether (MW<=700))

IATA

UN Number:

3082

UN Proper Shipping Name :

Environmentally Hazardous Substance, Liquid, N.O.S.
(reaction product: bisphenol-A-(epichlorhydrin); epoxy resin,Phenol, polymer with formaldehyde, glycidyl ether (MW<=700))

Transport Hazard Class :

9

Packing Group :

III

Environmental Hazards :

Yes

Marine Pollutant Substances:

(reaction product: bisphenol-A-(epichlorhydrin); epoxy resin,Phenol, polymer with formaldehyde, glycidyl ether (MW<=700))

NMFC: 4620 SUB.5 – CL.60**Schedule B #** 3506.91.0000**15. REGULATORY INFORMATION**

SARA 304 RQ : NOT REQUIRED (NO MATERIALS FOUND)**SARA 311/312**

Classification: Immediate (acute) health hazard

Delayed (chronic) health hazard

Composition of Ingredients :

REACTION PRODUCT: bisphenol-A-(epichlorhydrin) epoxy resin : Immediate (Acute) Health Hazard

Phenol, polymer with formaldehyde, glycidyl ether (MW<=700) : Immediate (Acute) Health Hazard

Carbon Black, Respirable Powder : Fire Hazard

: Delayed (Chronic) Health Hazard

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane : Immediate (Acute) Health Hazard

Synthetic Iron Oxide : Delayed (Chronic) Health Hazard

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage,use and disposal are beyond our control and may be beyond our knowledge.

15. REGULATORY INFORMATION

US Regulations Federal

chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA)	Chemical Name	CAS No	Weight %	Threshold limit (Reporting Value)
Bisphenol A Epoxy Resin		25068-38-6	<65%	unknown
Phenol Polymer with Formaldehyde		28064-14-4	<40%	unknown
Calcium Carbonate		471-34-1	<35%	unknown
Carbon Black		1333-86-4	<10%	unknown
Trimethoxysilane		2530-83-8	<10%	unknown
Hydantoin Epoxy Resin		15336-82-0	<10%	unknown
Synthetic Iron Oxide		12227-89-3	<20%	unknown

US Regulations State

California Proposition 65 (Developmental – Female)	Bisphenol A Epoxy Resin	25068-38-6	<65%	>=1.0%
Massachusetts	Bisphenol A Epoxy Resin	25068-38-6	<65%	>=1.0%
New Jersey	Bisphenol A Epoxy Resin	25068-38-6	<65%	>=1.0%
Pennsylvania	Bisphenol A Epoxy Resin	25068-38-6	<65%	>=1.0%
Rhode Island	Bisphenol A Epoxy Resin	25068-38-6	<65%	>=1.0%
California Proposition 65 (Developmental – Female)	Phenol polymer with Formaldehyde	28064-14-4	<40%	>=1.0%
Massachusetts	Phenol polymer with Formaldehyde	28064-14-4	<40%	>=1.0%
New Jersey	Phenol polymer with Formaldehyde	28064-14-4	<40%	>=1.0%
Pennsylvania	Phenol polymer with Formaldehyde	28064-14-4	<40%	>=1.0%
Rhode Island	Phenol polymer with Formaldehyde	28064-14-4	<40%	>=1.0%
California Proposition 65 (Developmental – Female)	Calcium Carbonate	471-34-1	<35%	>=1.0%
Massachusetts	Calcium Carbonate	471-34-1	<35%	>=1.0%
New Jersey	Calcium Carbonate	471-34-1	<35%	>=1.0%
Pennsylvania	Calcium Carbonate	471-34-1	<35%	>=1.0%
Rhode Island	Calcium Carbonate	471-34-1	<35%	>=1.0%
California Proposition 65 (Developmental – Female)	Carbon Black	1333-86-4	<10%	>=1.0%
Massachusetts	Carbon Black	1333-86-4	<10%	>=1.0%
New Jersey	Carbon Black	1333-86-4	<10%	>=1.0%
Pennsylvania	Carbon Black	1333-86-4	<10%	>=1.0%
Rhode Island	Carbon Black	1333-86-4	<10%	>=1.0%
California Proposition 65 (Developmental – Female)	Trimethoxysilane	2530-83-8	<10%	>=1.0%
Massachusetts	Trimethoxysilane	2530-83-8	<10%	>=1.0%
New Jersey	Trimethoxysilane	2530-83-8	<10%	>=1.0%
Pennsylvania	Trimethoxysilane	2530-83-8	<10%	>=1.0%
Rhode Island	Trimethoxysilane	2530-83-8	<10%	>=1.0%

Continued on next page

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

California Proposition 65 (Developmental – Female)	Hydantoin Epoxy Resin	15336-82-0	<10%	>=1.0%
Massachusetts	Hydantoin Epoxy Resin	15336-82-0	<10%	>=1.0%
New Jersey	Hydantoin Epoxy Resin	15336-82-0	<10%	>=1.0%
Pennsylvania	Hydantoin Epoxy Resin	15336-82-0	<10%	>=1.0%
Rhode Island	Hydantoin Epoxy Resin	15336-82-0	<10%	>=1.0%
California Proposition 65 (Developmental – Female)	Synthetic Iron Oxide	12227-89-3	<20%	>=1.0%
Massachusetts	Synthetic Iron Oxide	12227-89-3	<20%	>=1.0%
New Jersey	Synthetic Iron Oxide	12227-89-3	<20%	>=1.0%
Pennsylvania	Synthetic Iron Oxide	12227-89-3	<20%	>=1.0%
Rhode Island	Synthetic Iron Oxide	12227-89-3	<20%	>=1.0%

California Prop 65 Warning :

This Product contains one or more ingredients known by the state of California to cause cancer, birth defects, or other reproductive harm.



**materials Division 2: Materials Causing
Other Toxic Effects:**

Bisphenol-A-epoxy resin
Phenol polymer with formaldehyde
carbon black
calcium carbonate
trimethoxysilane
hydantoin epoxy resin
synthetic iron oxide

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR. Listed National Pollutant Release Inventory (NPRI) :

Bisphenol-A-epoxy resin Cas#25068-38-6

calcium carbonate Cas#471-34-1

Phenol polymer with formaldehyde Cas#28064-14-4

trimethoxysilane Cas#2530-83-8

carbon black Cas# 1333-896-4

hydantoin epoxy resin Cas#15336-82-0

synthetic iron oxide Cas# 12227-89-3

HEALTH 2
 FLAMMABILITY 0
 REACTIVITY 0

HEALTH 2
 FLAMMABILITY 0
 REACTIVITY 0

Customer and / or end user is responsible
 for determining PPE

NFPA

HMIS

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

Section 16 Other Information

Preparer-Flamemaster/Compliance
Rev A April 2015
Supercedes(Conversion)

Revision Notes: A

Conversion to ANSI format

Containers: Plastic Jars, Metal Cans, Cartridge Kits

Maximum Container Size: 50 Gallons/190 Liters

Notice to reader:

This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.

This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.

Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.

END OF SAFETY DATA SHEET