

**Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

1.1. Product Identifier: CS-3213 Part B Class B  
- Product Name: Corrosion Inhibiting Sealant / Catalyst Part B  
- Product reference: CS-3213-B

1.2. Product Use:  
- Corrosion Inhibiting Sealant

1.3. Manufacturer's Name:  
CAGE Code: 14439  
Flamemaster Corp.  
Chem Seal Division  
13576 Desmond Street  
Pacoima, CA 91333 – USA

1.3.1 Suppliers Name ( if not manufacturer )

Technical Contact:  
Flamemaster Corp.  
Tel: 818-890-1401  
Fax: 818-890-6001  
[www.flamemaster.com](http://www.flamemaster.com)

1.4. Emergency Telephone:  
Chemtrec – Chemtrec International  
800-424-9300 ( North America)  
703-527-3887 (Outside North America))

Specification	STM 40-111/MIL-PRF-81733			CATALYST PART B		CLASS B
<b>NSN:</b>	8030-01-184-0330 CS3213CLB-2 6OZ	8030-01-196-1958 CS3213CLB-2 2.5OZ	8030-01-124-7622 CS3213CLB-2 1/2 PT	8030-00-009-5023 CS3213CLB-2 PT	8030-00-008-7200 CS3213CLB-2 QT	
	8030-00-518-3439 CS3213CLB-2 GALLON	8030-01-333-3953 CS3213CLB-2 50 GAL	8030-01-184-0328 CS3213 CLB1/2 2.5 OZ	8030-01-184-0329 CS3213CLB1/2 6OZ	8030-01-124-7622 CS3213CLB1/2 1/2 PT	
	8030-00-008-7198 CS3213CLB1/2 PT	8030-00-470-9154 CS3213CLB1/2 QT	8030-01-097-4519 CS3213CLB1/2 GALLON	8030-01-480-4270 CS3213CLB PT		

---

---

**Section -2. HAZARD ( S ) IDENTIFICATION**

ASPIRATION HAZARD - (CATEGORY 1)

ACUTE TOXICITY (ORAL) - CATEGORY 4

ACUTE TOXICITY (INHALATION) - CATEGORY 4

SKIN CORROSION / IRRITATION - CATEGORY 1

SERIOUS EYE DAMAGE / EYE IRRITATION - CATEGORY 1

SKIN SENSITIZATION - CATEGORY 1

GERM CELL MUTAGENICITY - CATEGORY 1B

CARCINOGENICITY - CATEGORY 1A

TOXIC TO REPRODUCTION (FERTILITY) - CATEGORY 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - STOT SE - (RESPIRATORY TRACT IRRITATION) - CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - STOT RE - CATEGORY 2

AQUATIC (ACUTE) - CATEGORY 1

AQUATIC (CHRONIC) - CATEGORY 1

**OSHA / HCS STATUS :** THIS MATERIAL IS CONSIDERED HAZARDOUS BY THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

Human and Environmental Hazards:

**HAZARD STATEMENTS:**

May Be Fatal if Swallowed and Enters Airways

Harmful by Inhalation and / or Swallowing

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE

Causes Skin Irritation

May Cause An Allergic Skin Reaction

May Cause Genetic Defects

Suspected of Causing Cancer

Suspected of Damaging Fertility

May Cause Respiratory Irritation

May Cause Damage to Organs Through Prolonged or Repeated Exposure

VERY TOXIC TO AQUATIC LIFE

VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

**HAZARD PICTOGRAMS:**

**SIGNAL WORD:**

**DANGER**

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

Full text of P statements associated to this compound:

- P101+P102+P103: If medical advice is needed, have product container or label at hand. Keep out of reach of children.
- Read label before use
- P202: Do not handle until all safety precautions have been read and understood
- P210: Keep away from heat/sparks/open flames and hot surfaces-No Smoking
- P240:Ground/bond container and receiving equipment
- P261+P262+P263+P264:Avoid breathing dust/fumes/gas/mist/vapours/spray.Do not get in eyes , on skin, or on clothing. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling.
- P270+P271+P273: Do not eat drink or smoke when using this product. Use only outdoors or in a well ventilated area. Avoid release to the environment.
- P281+P280: Use personal protective equipment as required. Wear protective gloves/ protective clothing/ eye protection/face protection
- P301+P310+P331: If swallowed: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting.
- P305+P351+P338+P315: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,if present and easy to do. Continue rinsing. Get immediate medical advice attention.
- P304+P340+P314: If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell
- P342+P340+P315: If experiencing respiratory symptoms: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice/attention.
- P302+P352: If on skin: Wash with plenty of soap and water
- P306+P361: If on clothing: Remove/ take off immediately all contaminated clothing
- P402+P403+P404: Store in a dry place. Store in a well ventilated space. Store in a closed container.
- P233+P234+P235: Keep container tightly closed. Keep only in original container. Keep cool.

**HAZARDS NOT OTHERWISE CLASSIFIED:** OXIDISING POTENTIAL: Contact with combustible material may result in fire. Keep away from combustible materials. This material increases the risk of fire and may aid in combustion. Sanding and grinding dust may be harmful if inhaled. Sanding and grinding dust may form combustible concentrations in air.

**Other Hazards that do not result in classification:**

Prolonged or repeated exposure may dry skin and / or cause irritation

**In the event of sanding, grinding, or abrading:**

**H372 Causes damage to organs through prolonged or repeated exposure.**

**Section -3. COMPOSITION / INFORMATION ON INGREDIENTS**

**Chemical family :** Mixture of organic compounds

For the hazards of the composition, ( SDS see Section 2).

<b>CHEMICAL NAME: MANGANESE DIOXIDE</b>	CAS# 1313-13-9	EC# 215-202-6	<65% by weight
OSHA HAZARDS: TARGET ORGAN EFFECT,TOXIC BY INHALATION			
TARGET ORGANS: NERVES, LUNGS			
GHS CLASSIFICATION:			
ACUTE TOXICITY,ORAL (CATEGORY 4) - H302			
ACUTE TOXICITY,INHALATION (CATEGORY 4) - H332			
<b>CHEMICAL NAME: TERPHENYL, HYDROGENATED</b>	CAS# 61788-32-7	EC# 262-967-7	<50% by weight
AQUATIC CHRONIC (CATEGORY 4) - H413			
<b>CHEMICAL NAME: ZEOLITES</b>	CAS#1318-02-1	EC# 215-283-8	<15% by weight
NOT CLASSIFIED			

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage,use and disposal are beyond our control and may be beyond our knowledge.

**CHEMICAL NAME: MAGNESIUM CHROMATE** Cas# 13423-61-5 EC# 236-540-0 <40% by weight  
ACUTE TOXICITY, ORAL (CATEGORY 3), H301  
CARCINOGEN, (CATEGORY 1A) H350I  
CARCINOGEN, (CATEGORY 1A) H350  
SKIN CORROSIVE, (CATEGORY 1A) H314  
EYE DAMAGE, (CATEGORY 1) H314  
AQUATIC ACUTE, (CATEGORY 1) H400  
AQUATIC CHRONIC, (CATEGORY 1) H410

**CHEMICAL NAME: TERPHENYL** CAS# 26140-60-3 EC# 247-477-3 <10% by weight  
AQUATIC ACUTE (CATEGORY 1) - H400  
AQUATIC CHRONIC (CATEGORY 1) - H410

**CHEMICAL NAME: 1,3-DIPHENYLGUANIDINE** CAS# 102-06-7 EC# 203-002-1 <3% by weight  
ACUTE TOXICITY (CATEGORY 4) - H302  
SKIN IRRITATION (CATEGORY 2) - H315  
EYE IRRITATION (CATEGORY 2) - H319  
REPRODUCTIVE (CATEGORY 2) - H361f (FERTILITY)  
STOT-SINGLE EXPOSURE (CATEGORY 3) - H335  
AQUATIC CHRONIC (CATEGORY 2) - H411

**CHEMICAL NAME: BIS(PIPERIDINOTHIOCARBONYL) TETRASULFIDE** CAS# 120-54-7 EC# 204-406-0 <3% by weight  
SKIN SENSITIVITY (CATEGORY 1) - H317

**CHEMICAL NAME: POLYPHENYL, QUATER AND HIGHER** CAS# 68956-74-1 <10% by weight

#### **Section -4. FIRST-AID MEASURES**

**General:** When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

**Inhalation:** Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

**Eye contact:** Irrigate with clean, fresh water for at least 15 minutes, holding the eyelids apart, and seek medical attention.

**Skin contact:** Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

**Ingestion:** If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

---

---

**Section -5. FIRE-FIGHTING MEASURES**

---

**Extinguishing agents**

**Recommended:** Universal resistant foam, CO<sub>2</sub>, water, powder.

**Agents to avoid:** None known

**Attention**

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Do not allow run-off from fire fighting to enter drains or water courses.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

**Hazardous decomposition products include:** Carbon Dioxide, Carbon Monoxide, Nitrogen Oxides, Sulfur Oxides  
Metal Oxide / Oxides, Toxic Fumes

If exposed to hazardous decomposition products, symptoms may be delayed. Patient may require medical surveillance for up to 48 hours.

---

---

**Section -6. ACCIDENTAL RELEASE MEASURES**

---

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

---

---

**Section -7. HANDLING AND STORAGE**

---

**7.1 Handling:**

No smoking, eating and drinking during handling.

Avoid exposure during pregnancy/while nursing.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

**7.2 Storage:**

Observe label precautions. Store between 32/F and 95/F ( 0/C and 35/C ) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

---

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

---

**8.1 Engineering measures:**

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

---

---

**8.2 Exposure limits**

---

**Work place exposure limits ( 8 hour )**

---

<b>Substance</b>	<b>ACGIH TLV / OSHA PEL</b>
Manganese Dioxide	TWA: 0.1mg/m <sup>3</sup> (as Mn) 8 hours (Inhalable Fraction) ACGIH TWA: 0.02mg/m <sup>3</sup> (as Mn) 8 hours (Respirable Fraction) ACGIH CEIL: 5mg/m <sup>3</sup> OSHA PEL
Terphenyl, Hydrogenated	TWA: 4.9 mg/m <sup>3</sup> 8 hours - ACGIH TWA: 0.5 ppm 8 hours - ACGIH
Zeolites	TWA: 1mg/m <sup>3</sup> 8 hours (Respirable Fraction) - ACGIH
Terphenyl	C: 5mg/m <sup>3</sup> - ACGIH C: 0.53 ppm - ACGIH CEIL: 9 mg/m <sup>3</sup> - OSHA PEL CEIL : 1 ppm - OSHA PEL
Magnesium Chromate	TWA: 0.05 mg/m <sup>3</sup> (measured as Cr) 8 hours (Soluble) - ACGIH CEIL : 1 mg/10 m <sup>3</sup> OSHA PEL Z2 TWA : 0.005mg/m <sup>3</sup> (asCr) 8 hours - OSHA PEL

**8.3 Personal protection**

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

**Respiratory protection :**

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

**Hand protection :**

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

**Eye protection :**

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

**Skin protection :**

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• Physical state at: 68 ° F (20 ° C) Liquid</li> <li>• Flash point: 200 ° F (93 ° C) Method: TCC</li> <li>• Specific gravity at: 68 ° F (20 ° C) N/A</li> <li>• Vapor Density: N/A</li> <li>• Lower Explosive Limit (% vol.): N/A</li> <li>• Upper Explosive Limit (% vol.): N/A</li> <li>• Miscibility in water at 20 ° C: NEGLIGIBLE</li> <li>• Material Supports Combustion. : Yes</li> </ul> | <ul style="list-style-type: none"> <li>• Ph : N/A</li> <li>•% VOLATILE BY VOLUME - N/A</li> <li>• Vapor pressure at: 68 ° F (20 ° C) N/A</li> <li>• Color: BLACK</li> <li>• Appearance: PASTE</li> <li>• Odor: NEGLIGIBLE OILY ODOR</li> <li>• Boiling Point: N/A</li> </ul> |
|---|--|

**10. STABILITY AND REACTIVITY**

Stable under recommended storage and handling conditions (see SDS section 7). In case of combustion, may produce hazardous decomposition products such as :

- |                   |                        |         |
|-------------------|------------------------|---------|
| • Carbon monoxide | • Oxides of nitrogen   | • Smoke |
| • Sulfur oxides   | • Metal Oxide / Oxides |         |
| • Carbon Dioxide  | • Manganese Compounds  |         |

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

**11. TOXICOLOGICAL INFORMATION**

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health

**ACUTE TOXICITY:**

PRODUCT:	RESULT	SPECIES	DOSE	EXPOSURE
Manganese Dioxide	LD50 ORAL	Rat	3478 mg/kg	-
Terphenyl,Hydrogenated	LD50 ORAL	Rat	17500 mg/kg	-
Zeolites	LD50 ORAL	Rat	>5 g/kg	-
Terphenyl	LD50 Oral	Rat	>1400 mg/kg	-
1, 3-Diphenylguanidine	LD50 Oral	Rat	323mg/kg	-

**CARCINOGENICITY:**

INGREDIENT	IARC	OSHA	NTP
Magnesium Chromate	1	+	Known to be a human carcinogen
Zeolites	3	-	-

**Specific Target Organ Toxicity (STOT)- Single Exposure**

Magnesium Chromate - (Category 3)

1,3-Diphenylguanidine - (Category 3)

Zeolites - (Category 3)

**Specific Target Organ Toxicity (STOT) - Repeated Exposure:**

Manganese Dioxide - (Category 2)

**Potential chronic health effects include the following:**

May be Fatal if Swallowed and Enters Airways

Harmful by Inhalation and / or Swallowing

Causes Serious Eye Irritation

Causes Skin Irritation

May Cause An Allergic Skin Reaction

May Cause Genetic Defects

Suspected of Causing Cancer

Suspected of Damaging Fertility

May Cause Respiratory Irritation

May Cause Damage to Organs Through Prolonged or Repeated Exposure

This Product Causes Skin Irritation, Defatting of the Skin, and May Cause an Allergic Reaction.

**Target Organs:** lungs, skin, central nervous system, blood, kidneys, nervous system, liver, spleen, lymphatic system, cardiovascular system, upper respiratory tract, bone marrow, eye, lens, cornea, nose / sinuses

**ASPIRATION HAZARD:**

May Be Fatal if Swallowed and Enters Airways

**12. ECOLOGICAL INFORMATION**

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

**Bioaccumulative Potential:**

Product	LogPow	BCF	Potential
1,3 Diphenylguanidine	1.69	19.95	Low
Bis(piperidinothiocarbonyl) tetrasulfide	2.8	16.98	Low

**Mobility in Soil:**

Not Available

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.



---

---

**13. DISPOSAL CONSIDERATIONS**

---

---

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.

React with base and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

---

---

**14. TRANSPORT INFORMATION**

---

---

**DOT: Not regulated**

**UN Number: Not regulated**

**IATA: Not regulated**

**IMDG/IMO: Not regulated**

**NMFC: 4620 SUB.6 – CL.60**

**Schedule B # 3506.91.0000**

**IMDG**

UN NUMBER - 3082

**UN PROPER SHIPPING NAME** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (MAGNESIUM CHROMATE)

**TRANSPORT CLASS - 9**

**PACKING GROUP - III**

**ENVIRONMENTAL HAZARDS - YES**

**MARINE POLLUTANT - MAGNESIUM CHROMATE**

**IATA**

UN NUMBER - 3082

**UN PROPER SHIPPING NAME** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (MAGNESIUM CHROMATE)

**TRANSPORT CLASS - 9**

**PACKING GROUP - III**

**ENVIRONMENTAL HAZARDS - YES**

**MARINE POLLUTANT - MAGNESIUM CHROMATE**

---

---

**15. REGULATORY INFORMATION**

---

---

**Other EU Regulations:**

1,3-Diphenylguanidine - Reproductive (Category 2) H361f (Fertility)

**SARA 311/312**

Classification: Immediate (acute) health hazard

Delayed (chronic) health hazard

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

**Composition of Ingredients :**

- Manganese Dioxide : Immediate (acute) health hazard  
Delayed (chronic) health hazard
- Magnesium Chromate : Fire Hazard  
Immediate (acute) health hazard  
Delayed (chronic) health hazard
- Zeolites : Immediate (acute) health hazard
- Polyphenyls, quater and higher : Immediate (acute) health hazard
- Terphenyl : Immediate (acute) health hazard
- 1,3-Diphenylguanidine : Fire Hazard  
Immediate (acute) health hazard  
Delayed (chronic) health hazard
- Bis(piperidinothiocarbonyl) tetrasulfide : Fire Hazard  
Immediate (acute) health hazard

**US Regulations Federal**

chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA)	Chemical Name	CAS No	Weight %	Threshold limit (Reporting Value)
	Manganese Dioxide	1313-13-9	<65%	Unknown
	Magnesium chromate	13423-61-5	<40%	Unknown

SARA notifications must remain attached to this SDS. Any copies and /or distribution of this SDS must include all SARA notifications.

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST


**US Regulations State**

California Proposition 65 (Developmental – Female)	<b>MANGANESE DIOXIDE</b>	1313-13-9	< 65%	>= 1.0%
Massachusetts	<b>MANGANESE DIOXIDE</b>	1313-13-9	< 65%	>= 1.0%
New Jersey	<b>MANGANESE DIOXIDE</b>	1313-13-9	< 65%	>= 1.0%
Pennsylvania	<b>MANGANESE DIOXIDE</b>	1313-13-9	<65%	>= 1.0%
Rhode Island	<b>MANGANESE DIOXIDE</b>	1313-13-9	<65%	>= 1.0%
California Proposition 65 (Developmental – Female)	<b>MAGNESIUM CHROMATE</b>	13423-61-5	<40%	>= 1.0%
Massachusetts	<b>MAGNESIUM CHROMATE</b>	13423-61-5	<40%	>= 1.0%
New Jersey	<b>MAGNESIUM CHROMATE</b>	13423-61-5	<40%	>= 1.0%
Pennsylvania	<b>MAGNESIUM CHROMATE</b>	13423-61-5	<40%	>= 1.0%
Rhode Island	<b>MAGNESIUM CHROMATE</b>	13423-61-5	<40%	>= 1.0%

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

**California Prop 65 Warning :**

This Product contains one or more ingredients known by the state of California to cause cancer, birth defects, or other reproductive harm.



**materials Division 2: Materials Causing  
Other Toxic Effects:  
Manganese Dioxide CAS#1313-13-9  
Magnesium Chromate Cas#13423-61-5**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR. Listed National Pollutant Release Inventory (NPRI):Manganese Dioxide cas#1313-13-9 Magnesium Chromate Cas# 13423-61-5

---

**Section 16 Other Information**

---

HEALTH	3	HEALTH	3
FLAMMABILITY	1	FLAMMABILITY	1
REACTIVITY	1	REACTIVITY	1

Customers and/or end users are responsible for determining PPE codes.

**NFPA**

**HMIS**

Preparer-Flamemaster/Compliance  
Rev A JUNE 2015  
Supercedes(Conversion)

Revision Notes: A

Conversion to ANSI format

Containers: Plastic Jars, Metal Cans, Cartridge Kits

Maximum Container Size: 50 Gallons/190 Liters

Notice to reader:

This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.

This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.

Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.

END OF SAFETY DATA SHEET