



13576 Desmond Street  
Pacoima, CA 91331 - USA

**SAFETY DATA SHEET**  
**APRIL 2016**

**File: CS5306AA GSA 07-10**  
**Polythioether Quick Repair**  
**Fuel Sealant/Base**

**Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

- 1.1. Product Identifier: CS-5306-A Polythioether Quick Repair Fuel Tank Sealant  
 - Product Name: Quick Repair Fuel Tank Sealant / Base compound Part-A / Class A  
 - Product reference: CS-5306 Part A Base / Class A

**1.2. Product Use:**

- Polythioether Quick Repair Fuel Tank Sealant

**1.3. Manufacturer's Name:**

**CAGE Code: 14439**  
**Flamemaster Corp.**  
**Chem Seal Division**  
**13576 Desmond Street**  
**Pacoima, CA 91333 – USA**

**1.3.1 Suppliers Name ( if not manufacturer )**

**Technical Contact:**

**Flamemaster Corp.**  
**Tel: 818-890-1401**  
**Fax: 818-890-6001**  
[www.flamemaster.com](http://www.flamemaster.com)

**1.4. Emergency Telephone:**

Chemtrec – Chemtrec International  
 800-424-9300 ( North America)  
 703-527-3887 (Outside North America))

**Specification:**

**AMS 3277 TYPE 1**

**BASE PART A**

**CLASS A**

<b>NSN:</b>	8030-01-330-0726 CS5306A1/4 2.5OZ	8030-01-330-6568 CS5306A1/2 2.5 OZ	8030-01-330-0730 CS5306A1/2 6OZ.	8030-01-330-0728 CS5306 A1/2 1/2 PT	8030-01-330-0729 CS5306 A1/2 PINT
	8030-01-330-0732 CS5306A1/2 QUART	8030-01-330-0731 CS5306A1/2 GAL	8030-01-330-0733 CS5306A1/2 5-GAL	8030-01-330-0734 CS5306A1/2 50-GAL	8030-01-330-0745 CS5306A1 2.5 OZ
	8030-01-330-3437 CS5306A1 6OZ.	8030-01-329-9999 CS5306A1 1/2 PINT	8030-01-330-2578 CS5306A1 PINT	8030-01-330-0737 CS5306A1 QUART	8030-01-330-0736 CS5306A1 GAL
	8030-01-330-2579 CS5306A1 5-GAL	8030-01-329-9998 CS5306A1 50-GAL			

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

## Section -2. HAZARD ( S ) IDENTIFICATION

---

OSHA/HCS STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

### CLASSIFICATION OF THE MIXTURE:

FLAMMABLE LIQUIDS - CATEGORY 2

ASPIRATION HAZARD - (CATEGORY 1)

SKIN CORROSION / IRRITATION - CATEGORY 2

SERIOUS EYE DAMAGE / EYE IRRITATION - CATEGORY 2

CARCINOGENICITY - Category 2

SPECIFIC TARGET ORGAN TOXICITY (STOT SE) (SINGLE EXPOSURE) (RESPIRATORY TRACT IRRITATION) - Category 3

REPRODUCTIVE TOXICITY, EFFECTS ON OR VIA LACTATION

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE - (NARCOTIC EFFECT) - CATEGORY 3

ACUTE TOXICITY,ORAL - CATEGORY 4

TOXIC TO REPRODUCTION - CATEGORY 2

AQUATIC CHRONIC - CATEGORY 4

### GHS LABEL REQUIREMENTS

#### HAZARD PICTOGRAMS



**SIGNAL WORD : DANGER**

#### HAZARD STATEMENTS:

HIGHLY FLAMMABLE LIQUID AND VAPOR - H225

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - (H304)

CAUSES SERIOUS EYE IRRITATION - H319

CAUSES SKIN IRRITATION - H315

SUSPECTED OF CAUSING CANCER - H351

MAY CAUSE RESPIRATORY IRRITATION - H335

SUSPECTED OF DAMAGING FERTILITY. SUSPECTED OF DAMAGING THE UNBORN CHILD - H361fd

MAY CAUSE HARM TO BREAST FED CHILDREN - H362

MAY CAUSE DROWSINESS OR DIZZINESS - H336

HARMFUL IF SWALLOWED - H302

MAY CAUSE LONG LASTING HARMFUL EFFECTS TO AQUATIC LIFE - H413

#### PRECAUTIONARY STATEMENTS:

- P101+P102+P103: If medical advice is needed, have product container or label at hand. Keep out of reach of children.
- Read label before use
- P202: Do not handle until all safety precautions have been read and understood
- P210: Keep away from heat/sparks/open flames and hot surfaces-No Smoking
- P240:Ground/bond container and receiving equipment
- P261+P262+P263+P264:Avoid breathing dust/fumes/gas/mist/vapours/spray.Do not get in eyes , on skin, or on clothing. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling.
- P270+P271+P273: Do not eat drink or smoke when using this product. Use only outdoors or in a well ventilated area. Avoid release to the environment.
- P281+P280: Use personal protective equipment as required. Wear protective gloves/ protective clothing/ eye protection/face protection
- P301+P310+P331: If swallowed: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting.
- P305+P351+P338+P315: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,if present and easy to do. Continue rinsing. Get immediate medical advice attention.
- P304+P340+P314: If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell
- P342+P340+P315: If experiencing respiratory symptoms: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice/attention.
- P302+P352: If on skin (or in hair) : Wash with plenty of soap and water. If skin irritation occurs seek medical attention
- P306+P361: If on clothing: Remove/ take off immediately all contaminated clothing
- P402+P403+P404: Store in a dry place. Store in a well ventilated space. Store in a closed container.
- P233+P234+P235: Keep container tightly closed. Keep only in original container. Keep cool.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage, use and disposal are beyond our control and may be beyond our knowledge.

## SUPPLEMENTAL LABEL ELEMENTS:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of concentrations above recommended limits causes headaches, drowsiness and nausea and could lead to unconsciousness or possibly death.

Irritating to the mucous membranes and may cause the skin to become sensitized.

Avoid any contact with skin or clothing and wash thoroughly after handling.

Emits toxic fumes when heated.

### HAZARDS NOT OTHERWISE CLASSIFIED:

Prolonged or repeated exposure may dry skin and / or cause skin irritation.

Sanding and grinding dust may be harmful if inhaled. Sanding and grinding dust may form combustible concentrations in air.

### In the event of sanding, grinding, or abrading:

H372 Causes damage to organs through prolonged or repeated exposure.

---

---

## Section -3. COMPOSITION / INFORMATION ON INGREDIENTS

---

---

**Chemical family** : Mixture of organic compounds

For the hazards of the composition, (SDS see Section 2).

---

### PROPRIETARY POLYTHIOETHER

SKIN CORROSION / IRRITATION - CATEGORY 2

SERIOUS EYE DAMAGE / EYE IRRITATION - CATEGORY 2A

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE - (STOT SE) - (RESPIRATORY TRACT IRRITATION) - CATEGORY 3

### 2-BUTANONE

OSHA HAZARDS: FLAMMABLE LIQUID, TARGET ORGAN EFFECT, IRRITANT

TARGET ORGANS: CENTRAL NERVOUS SYSTEM

GHS CLASSIFICATION: 2-BUTANONE

FLAMMABLE LIQUIDS (CATEGORY 2)

ACUTE TOXICITY, ORAL (CATEGORY 5)

EYE IRRITATION (CATEGORY 2A)

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE (CATEGORY 3), CENTRAL NERVOUS SYSTEM

OTHER HAZARDS: REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS AND CRACKING

### CALCIUM CARBONATE:

GHS CLASSIFICATION: CALCIUM CARBONATE

EYE DAMAGE (CATEGORY 1)

SKIN IRRITATION (CATEGORY 2)

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE-(CATEGORY 3)

### TITANIUM DIOXIDE

OSHA HAZARDS: CARCINOGEN

GHS CLASSIFICATION: TITANIUM DIOXIDE

SKIN IRRITATION: (CATEGORY 3)

CARCINOGENICITY (CATEGORY 2)

### ALUMINUM HYDROXIDE

NOT CONSIDERED A HAZARDOUS SUBSTANCE

### 2,2'- THIODIETHANETHIOL

FLAMMABLE LIQUID: CATEGORY 4

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

SUBSTANCE % by weight in the product	H&P STATEMENTS	CAS	EINECS/ELINCS
PROPRIETARY POLYTHIOETHER <70%	H319,H335,H315,	NOT AVAILABLE	NOT AVAILABLE
2-BUTANONE (MEK) <15%	H225,H303+H333,H319,H336,P210, P261,P305+P351+P338	78-93-3	201-159-0
Titanium Dioxide <10%	H319,H335,H315,H332,H312,H302 H373,P305+P351+P313,P280+ P281,P262,P102,P280	13463-67-7	236-675-5
Calcium Carbonate <35%	H319 P305+P351+P313,P280	72608-12-9	207-439-9
ALUMINUM HYDROXIDE <15%	NOT CONSIDERED HAZARDOUS	21645-51-2	244-492-7
2,2'-THIODIETHANETHIOL <5%	H227	3570-55-6	226-671-0

#### Section -4. FIRST-AID MEASURES

**General:** When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

**Inhalation:** Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

**Eye contact:** Check for and remove any contact lenses. Irrigate with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek immediate medical attention.

**Skin contact:** Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

**Ingestion:** If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

#### Section -5. FIRE-FIGHTING MEASURES

##### Extinguishing agents

**Recommended:** Universal resistant foam, CO<sub>2</sub>, water, powder.

**Agents to avoid:** None known

##### Attention

Promptly remove all persons in the event of a fire from the fire area. If safe to do so, remove all containers from fire area as well.

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Do not allow run-off from fire fighting to enter drains or water courses.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Emits toxic fumes when heated.

**HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE:** CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN, METAL OXIDE / OXIDES, SMOKE, SULPHUR OXIDES, ORGANIC COMPOUNDS, TOXIC FUMES AND SOOT.

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

---

---

**Section -6. ACCIDENTAL RELEASE MEASURES**

---

---

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

---

---

**Section -7. HANDLING AND STORAGE**

---

---

**7.1 Handling:**

No smoking, eating and drinking during handling.

Avoid exposure during pregnancy/while nursing.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

---

**7.2 Storage:**

Observe label precautions. Store between 32/F and 95/F ( 0/C and 35/C ) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

---

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

---

**8.1 Engineering measures:**

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

---

**8.2 Exposure limits**

---

Work place exposure limits ( 8 hour )

Substance	OSHA	ACGIH TWA
2-BUTANONE (MEK) *	200 ppm	200 ppm
CALCIUM CARBONATE *	5 mg/m <sup>3</sup> ( RESPIRABLE FRACTION)	3 mg/m <sup>3</sup> (RESPIRABLE FRACTION)
CALCIUM CARBONATE *	15mg/m <sup>3</sup> (TOTAL DUST)	10 mg/m <sup>3</sup> (TOTAL DUST)
TITANIUM DIOXIDE *	15mg/m <sup>3</sup> (TOTAL DUST)	10 mg/m <sup>3</sup>
ALUMINUM HYDROXIDE *		1 mg/m <sup>3</sup> (RESPIRABLE FRACTION)
* can be absorbed through skin		

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

### 8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

#### Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

#### Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

#### Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

#### Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

---

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

---

- |  |  |
|--|--|
| <ul style="list-style-type: none"><li>• Physical state at: 68 ° F (20 ° C) Liquid</li><li>• Flash point: 40 ° F (&gt;4 ° C) Method: TCC</li><li>• Specific gravity at: 68 ° F (20 ° C) N/A</li><li>• Vapor Density: N/A</li><li>• Lower Explosive Limit (% vol.): N/A</li><li>• Density ( lbs / Gal ) : N/A</li><li>• Miscibility in water at 20 ° C: Negligible</li><li>• VOC : N/A</li></ul> | <ul style="list-style-type: none"><li>• Ph : Not Available</li><li>• % Solids (w/w) N/A</li><li>• Vapor pressure : Not Available</li><li>• Color: White</li><li>• Appearance: Paste</li><li>• Odor: Mercapton odor</li><li>• Boiling Point: Not Available</li><li>• Material Supports Combustion : Yes</li></ul> |
|--|--|

---

---

## 10. STABILITY AND REACTIVITY

---

---

Stable under recommended storage and handling conditions (see SDS section 7). In case of combustion, may produce hazardous decomposition products such as :

- |   |   |   |
|---|---|---|
| <ul style="list-style-type: none"><li>• Carbon Monoxide</li><li>• Metal Oxide / Oxides</li><li>• Carbon Dioxide</li></ul> | <ul style="list-style-type: none"><li>• Toxic Fumes</li><li>• Oxides of Carbon and Nitrogen</li><li>• Smoke</li></ul> | <ul style="list-style-type: none"><li>• Soot</li><li>• Sulphur Oxides</li><li>• Organic Compounds</li></ul> |
|---|---|---|

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

---

---

## 11. TOXICOLOGICAL INFORMATION

---

---

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs of overexposure include headache, dizziness, fatigue, muscular weakness, drowsiness, reduced fetal weight, increase in fetal deaths, skeletal malformations, and in extreme cases loss of consciousness

Repeated or prolonged contact with the preparation may cause Defatting of the skin resulting in non-allergic dermatitis and absorption through the skin.

The liquid splashed in the eyes causes serious eye irritation and damage.

Irritating to mouth, throat and stomach. Ingestion causes reduced fetal weight, increased fetal deaths and skeletal malformations

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

**ACUTE TOXICITY:**

PRODUCT:	RESULT	SPECIES	DOSE	EXPOSURE
Calcium Carbonate	LD50 ORAL	Rat	6450 mg/kg	-
Butanone	LC50 Inhalation Vapor	Rat	11243 ppm	4 Hours
	LD50 Dermal	Rabbit	6480 mg/kg	-
	LD50 ORAL	Rat	2737 mg/kg	-
2,2'-thiodiethanethiol	LC50 Inhalation Dust & Vapor	Rat	160 mg/m <sup>3</sup>	4 Hours
	LD50 ORAL	Rat	0.164 g/kg	-
Titanium Dioxide	LD50 ORAL	Rat	>10g/kg	-

**CARCINOGENICITY:**

INGREDIENT	IARC	OSHA	NTP	CAS#
TITANIUM DIOXIDE :	2B	-	-	13463-67-7

**SPECIFIC TARGET ORGAN TOXICITY-STOT (SINGLE EXPOSURE)**

PROPRIETARY POLYTHIOETHER - Category 3

BUTANONE - Category 3

2,2'-thiodiethanethiol - Category 3

**TARGET ORGANS:** BRAIN, BLOOD, KIDNEYS, LUNGS, REPRODUCTIVE SYSTEM, LIVER, HEART, PERIPHERAL NERVOUS SYSTEM, GASTROINTESTINAL TRACT, UPPER RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, NERVOUS SYSTEM, EYE, LENS AND/OR CORNEA

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - (H304)

CAUSES SERIOUS EYE IRRITATION - H319

CAUSES SKIN IRRITATION - H315

SUSPECTED OF CAUSING CANCER - H351

MAY CAUSE RESPIRATORY IRRITATION - H335

**SUSPECTED OF DAMAGING FERTILITY. SUSPECTED OF DAMAGING THE UNBORN CHILD - H361fd**

**MAY CAUSE HARM TO BREAST FED CHILDREN - H362**

MAY CAUSE DROWSINESS OR DIZZINESS - H336

HARMFUL IF SWALLOWED - H302

**ASPIRATION HAZARD:**

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS

**12. ECOLOGICAL INFORMATION**

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Toxicity :

Product / Ingredient	Result	Species	Exposure
Titanium Dioxide	Acute LC50>100mg/l Fresh Water	Daphnia	48 Hours

Bioaccumulative Potential :

Product / Ingredient	LogP(ow)	BCF	Potential
Butanone	.29	-	low

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

Mobility in Soil : Not Available

### 13. DISPOSAL CONSIDERATIONS

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.  
React with curing agent and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.  
Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.  
Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

### 14. TRANSPORT INFORMATION

DOT: § 172.101 HAZARDOUS MATERIALS TABLE

UN Number: 1133

Proper Shipping Name: Adhesives

Labels: Flammable Liquid

IATA:

UN Number: 1133

Proper Shipping Name: Adhesives

Labels: Flammable Liquid

Hazard Class: 3 Subclass: NO

Packaging Group: III

Passenger Air Packing Instruction : 355

Passenger aircraft: 60 Liter (16 gallon)

Cargo Air Packing Instruction : 366

Cargo aircraft only: 220 Liter (58 gallon)

Hazard Class: 3 Subclass: NO

Packaging Group: III

Limited Quantity: Passenger aircraft: 10 Liter (2.64 Gallons)

Cargo aircraft only: 220 Liter (58 gallon)

Vessel stowage: A

ERG: 128

NMFC 4620 sub.6-CL.60

Schedule B # 3506.91.0000

IMDG:

UN Number: 1133

Proper Shipping Name: Adhesives

Label: 3

Hazard Class: 3 Subclass: NO

Packaging Group: III

EMS No: F, E – S, D

### 15. REGULATORY INFORMATION

#### US Regulations Federal

chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA)	Chemical Name	CAS No	Weight %	Threshold limit (Reporting Value)
	Proprietary Polythioether	Not Available	<70 %	unknown
	2-BUTANONE	78-93-3	<15%	unknown
	Calcium Carbonate	72608-12-9	<35%	unknown
	Aluminum Hydroxide	21645-51-2	<15%	unknown
	Titanium Dioxide	*13463-67-7	< 3%	unknown
	2,2'thiodiethanethiol	3570-55-6	<5%	unknown
	*(DELETED CAS# 98084-96-9)			

SARA notifications must remain attached to this SDS. Any copies and /or distribution of this SDS must include all SARA notifications.

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.



**US Regulations State**

California Proposition 65 (Developmental – Female)	proprietary polythioether	NOT AVAILABLE	<70%	>=1.0%
Massachusetts	proprietary polythioether	NOT AVAILABLE	<70%	>=1.0%
New Jersey	proprietary polythioether	NOT AVAILABLE	<70%	>=1.0%
Pennsylvania	proprietary polythioether	NOT AVAILABLE	<70%	>=1.0%
Rhode Island	proprietary polythioether	NOT AVAILABLE	<70%	>=1.0%
California Proposition 65 (Developmental – Female)	2-BUTANONE	78-93-3	<15%	>=1.0%
Massachusetts	2-BUTANONE	78-93-3	<15%	>=1.0%
New Jersey	2-BUTANONE	78-93-3	<15%	>=1.0%
Pennsylvania	2-BUTANONE	78-93-3	<15%	>=1.0%
Rhode Island	2-BUTANONE	78-93-3	<15%	>=1.0%
California Proposition 65 (Developmental – Female)	Calcium Carbonate	72608-12-9	<35%	>=1.0%
Massachusetts	Calcium Carbonate	72608-12-9	<35%	>=1.0%
New Jersey	Calcium Carbonate	72608-12-9	<35%	>=1.0%
Pennsylvania	Calcium Carbonate	72608-12-9	<35%	>=1.0%
Rhode Island	Calcium Carbonate	72608-12-9	<35%	>=1.0%
California Proposition 65 (Developmental – Female)	Titanium Dioxide	13463-67-7	<10%	>=1.0%
Massachusetts	Titanium Dioxide	13463-67-7	<10%	>=1.0%
New Jersey	Titanium Dioxide	13463-67-7	<10%	>=1.0%
Pennsylvania	Titanium Dioxide	13463-67-7	<10%	>=1.0%
Rhode Island	Titanium Dioxide	13463-67-7	<10%	>=1.0%
California Proposition 65 (Developmental – Female)	ALUMINUM HYDROXIDE	21645-51-2	<15%	>=1.0%
Massachusetts	ALUMINUM HYDROXIDE	21645-51-2	<15%	>=1.0%
New Jersey	ALUMINUM HYDROXIDE	21645-51-2	<15%	>=1.0%
Pennsylvania	ALUMINUM HYDROXIDE	21645-51-2	<15%	>=1.0%
Rhode Island	ALUMINUM HYDROXIDE	21645-51-2	<15%	>=1.0%
California Proposition 65 (Developmental – Female)	2,2'-THIODIETHANETHIOL	3570-55-6	<5%	>=1.0%
Massachusetts	2,2'-THIODIETHANETHIOL	3570-55-6	<5%	>=1.0%
New Jersey	2,2'-THIODIETHANETHIOL	3570-55-6	<5%	>=1.0%
Pennsylvania	2,2'-THIODIETHANETHIOL	3570-55-6	<5%	>=1.0%
Rhode Island	2,2'-THIODIETHANETHIOL	3570-55-6	<5%	>=1.0%

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

**United States:** Sara 302/304 (Sara 304 RQ): Not Applicable

Information On Ingredients: None Were Found

Sara 311/312

Classification: Immediate (acute) Health Hazard, Delayed (chronic) Health Hazard, Fire Hazard

**Information On Ingredients:**

**Butanone:** Fire Hazard, Immediate (acute) Health Hazard

**Proprietary Polythioether:** Immediate (acute) Health Hazard

**Titanium Dioxide:** Delayed (chronic) Health Hazard

**2,2'-thiodiethanethiol:** Immediate (acute) Health Hazard

**Sudden Release Of Pressure:** No Products

**Reactivity:** No Products

**California Prop. 65 : Warning**

This product contains a chemical or chemicals known by the state of California to cause cancer.

Canada



**Class B – Flammable**

2-BUTANONE  
2,2'-thiodiethanethiol



**Class D - Poisonous and Infectious  
materials Division 2: Materials Causing  
Other Toxic Effects D2A D2B**

Proprietary Polythioether  
2-BUTANONE CAS#78-93-3  
Titanium Dioxide CAS# 13463-67-7  
Calcium Carbonate CAS# 72608-12-9  
2,2'-thiodiethanethiol CAS# 3570-55-6  
Aluminum Hydroxide CAS# 21645-51-2

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

Listed National Pollutant Release Inventory (NPRI):

2-BUTANONE CAS#78-93-3

Calcium Carbonate CAS#72608-12-9

Aluminum Hydroxide CAS# 21645-51-2

Proprietary Polythioether CAS# Not Available

Titanium Dioxide CAS#13463-67-7

2,2'-thiodiethanethiol CAS# 3570-55-6

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

---

---

**16. OTHER INFORMATION**

---

---

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0

Customer and / or end user is responsible for determining PPE

**NFPA****HMIS**

Preparer:	Flamemaster / Compliance Rev-A 4/20/2015 Supersedes (conversion)	Revision Notes: A	Conversion to ANSI format
Containers:	plastic jars, metal cans cartridge kits		

Limited Quantity      See SDS Section 14

Maximum container size 50 Gallons / 190 Liters

**Notice to reader:**

This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.

This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.

Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.

**End of Safety Data Sheet**