



FLAMEMASTER
 Flamemaster Corp.
 13576 Desmond Street
 Pacoima, CA 91331 - USA

SAFETY DATA SHEET
AUGUST 22, 2019

File: CS3205AB GSA 7-10
INTEGRAL FUEL TANK SEALANT
BASE COMPOUND
(Dichromate Cure)

Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1. Product Identifier: CS-3205 PART A CLASS B (TYPE 1) ALL
 - Product Name: Integral Fuel Tank Sealant / Base compound Part-A / (Dichromate Cure)
 - Product reference: CS-3205 PT A CLASS B BASE COMPOUND ALL

1.2. Product Use:
 -Integral Fuel Tank Sealant / (Dichromate Cure)

1.3. Manufacturer's Name:
CAGE Code: 14439
Flamemaster Corp.
Chem Seal Division
13576 Desmond Street
Pacoima, CA 91333 – USA

1.3.1 Suppliers Name (if not manufacturer)

Technical Contact:
Flamemaster Corp.
Tel: 818-890-1401
Fax: 818-890-6001
www.flamemaster.com

Emergency Contact Information :
 See Below

| Specification: | AMS-S-8802 | Base PT A | CLASS B | ALL |
|----------------|--------------------------------------|---------------------------------------|-------------------------------------|--|
| NSN: | 8030-01-154-9253 CS3205 B1/2 PINT | 8030-01-154-9254 CS3205 B1/2 QUART | 8030-01-154-9252 CS3205 B1/2 6OZ | 8030-01-156-6229 CS3205 B1/2 GALLON |
| | 8030-01-154-9256 CS3205 B2 PINT | 8030-01-154-9245 CS3205 B2 QUART | 8030-01-154-9255 CS3205 B2 6OZ | 8030-01-154-9246 CS3205 B2 GALLON |

Emergency Contact:
 CHEMTEL: WWW.CHEMTELINC.COM
 Flamemaster Corporation Contract Number MIS2644301
 Shipments of hazardous materials within United States, Canada, Puerto Rico, and U.S. Virgin Island should reference Chemtel's toll free phone number: 1-800-255-3924 - Reference Number MIS2644301
 Shipments and safety applications outside of United States, Canada, Puerto Rico, and the U.S. Virgin Islands must reference Chemtel phone number +1-813-248-0585 - Reference Number MIS2644301
 Collect Calls will be accepted. To ensure a bilingual operator please call collect.
 Shipments originating in U.S.A. and going overseas must use both numbers.
 Shipments originating overseas and destined for US, Canada, Puerto Rico or the Virgin Islands must also use both numbers.
 Calls originating on board vessels should follow normal ship to shore protocols. Use international access number and alert the ship to shore operator you are involved in an emergency incident.
 Shipments of hazardous materials within the listed countries should reference Chemtel's in-country phone numbers:
 Australia : 1-300-954-583 : Reference Number MIS2644301
 Brazil : 0-800-591-6042 : Reference Number MIS2644301
 China : 400-120-0751 : Reference Number MIS2644301
 India : 000-800-100-4086 : Reference Number MIS2644301
 Mexico : 01-800-099-0731 : Reference Number MIS2644301

Section -2. HAZARD (S) IDENTIFICATION

OSHA/HCS STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

CLASSIFICATION OF THE MIXTURE:

ASPIRATION HAZARD - CATEGORY 1
SKIN SENSITIZATION - Category 1
TOXIC TO REPRODUCTION (UNBORN CHILD) - Category 2
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (STOT RE) - CATEGORY 2
CARCINOGENICITY (CATEGORY 2)
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
SKIN CORROSION/IRRITATION - Category 2
REPRODUCTIVE TOXICITY, EFFECTS ON OR VIA LACTATION
AQUATIC (CHRONIC) - CATEGORY 3

GHS LABEL REQUIREMENTS**HAZARD PICTOGRAMS**

SIGNAL WORD : DANGER

HAZARD STATEMENTS:

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS
MAY CAUSE AN ALLERGIC SKIN REACTION
SUSPECTED OF DAMAGING THE UNBORN CHILD
MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED AND / OR REPEATED EXPOSURE
SUSPECTED OF CAUSING CANCER
CAUSES SERIOUS EYE IRRITATION - H319
CAUSES SKIN IRRITATION - H315
MAY CAUSE HARM TO BREAST-FED CHILDREN - H362
HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS - H412

GENERAL PRECAUTIONARY STATEMENTS:

P101: If medical advise is needed, have product container or label at hand.
P102: keep out of reach of children.
P103: Read label before use.

PRECAUTIONARY STATEMENTS:

- P101+P102+P103: If medical advice is needed, have product container or label at hand. Keep out of reach of children.
- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P260: Do not breathe dust / fumes / gas / mist / vapors / spray.
- P261: Avoid breathing dust / fumes / gas / mist / vapors / spray.
- P263: Avoid contact during pregnancy / while nursing.
- P264: Wash thoroughly after handling.
- P270: Do not eat, drink, or smoke when using this product.
- P272: Contaminated work clothing should not be allowed out of the workplace.
- P273: Avoid release to the environment.
- P280: Wear protective gloves / protective clothing / eye protection / face protection.
- P281: Use personal protection equipment as required.
- P301+310: IF SWALLOWED: Immediately call a POISON CENTER / doctor / ...
- P302+352: IF ON SKIN: Wash with plenty of water / ...
- P305+351+338: IF IN EYES: Rinse cautiously for several minutes. Remove contact lenses if present and easy to do-continue rinsing.
- P308+313: If exposed: Call a POISON CENTER or doctor / physician.
- P314: Get medical advice / attention if you feel unwell.
- P321: Specific treatment...See Label Information
- P331: Do NOT induce vomiting.
- P332+313: If skin irritation occurs: Get medical advice / attention.
- P333+313: If skin irritation or a rash occurs: Get medical advice / attention.
- P337+313: If eye irritation persists: Get medical advice / attention.
- P362: Take off all contaminated clothing.
- P363: Wash contaminated clothing before reuse.
- P391: Collect spillage.
- P405: Store locked up.
- P501: Dispose of contents / containers in accordance with local / regional / national / international regulations

SUPPLEMENTAL LABEL ELEMENTS:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of concentrations above recommended limits causes headaches, drowsiness and nausea and could lead to unconsciousness or possibly death.

1-component mixtures: formaldehyde is released during the curing phase. Formaldehyde may cause irreversible effects, is irritating to the mucous membranes and may cause the skin to become sensitized.

Avoid any contact with skin or clothing and wash thoroughly after handling.

Emits toxic fumes when heated. Dust from grinding and sanding may be harmful if inhaled.

HAZARDS NOT OTHERWISE CLASSIFIED:

Prolonged or repeated exposure may dry skin and / or cause skin irritation.

Section -3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical family : Mixture of organic compounds

For the hazards of the composition, (SDS see Section 2).

GHS CLASSIFICATION:LIQUID POLYSULFIDE POLYMER

EYE IRRITATION (CATEGORY 2)

SKIN IRRITATION (CATEGORY 2)

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE-(CATEGORY 3)

AQUATIC, CHRONIC (CATEGORY 3)

GHS CLASSIFICATION:LIQUID PHENOL POLYMER

EYE IRRITATION (CATEGORY 2)

SKIN IRRITATION (CATEGORY 2)

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE-(CATEGORY 3)

AQUATIC, CHRONIC (CATEGORY 3)

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS): TOLUENE

FLAMMABLE LIQUIDS (CATEGORY 2),H225

SKIN IRRITATION (CATEGORY 2),H315

REPRODUCTIVE TOXICITY (CATEGORY 2),H361

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE-(CATEGORY 3),CENTRAL NERVOUS SYSTEM,H336

SPECIFIC TARGET ORGAN TOXICITY-REPEATED EXPOSURE (CATEGORY 2),H373

ASPIRATION HAZARD (CATEGORY 1),H304

ACUTE AQUATIC TOXICITY (CATEGORY 2),H401

CALCIUM CARBONATE:

GHS CLASSIFICATION: CALCIUM CARBONATE

EYE DAMAGE (CATEGORY 1)

SKIN IRRITATION (CATEGORY 2)

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE-(CATEGORY 3)

METHYLATED SILICA

GHS CLASSIFICATION CATEGORIES NOT AVAILABLE

| SUBSTANCE % by weight in the product | H&P STATEMENTS | CAS | EINECS/ELINCS |
|---|---|------------|----------------------|
| LIQUID POLYSULFIDE-POLYMER < 71% | H319,H335,H315,H412,H223, P210,P270,P305+P351+P338 +P313,P306+P361,P370+P260 | N/A | POLYMER |
| LIQUID PHENOL-POLYMER < 71% | H319,H335,H315,H412,H223, P210,P270,P305+P351+P338 +P313,P306+P361,P370+P260 | N/A | POLYMER |
| TOLUENE (Methylbenzene) < 10% | H225,H304,H315,H319,H332,H336, H361,H371,H401, P210P260,P281,P301+P310,P305+ P351+ P338,P331 | 108-88-3 | 203-625-9 |
| METHYLATED SILICA < 10% | NOT AVAILABLE | 67762-90-7 | N/A |
| Calcium Carbonate <45% | H319 P305+P351+P313,P280 | 471-34-1 | 207-439-9 |

Section -4. FIRST-AID MEASURES

General: When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

Eye contact: Remove any contact lenses if present and easy to do. Irrigate with clean, fresh water for at least 15 minutes, holding the eye lids apart, and seek immediate medical attention.

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

Section -5. FIRE-FIGHTING MEASURES

Extinguishing agents

Recommended: Universal resistant foam, CO₂, water, powder.

Agents to avoid: None known

Attention

Promptly remove all persons in the event of a fire from the fire area. If safe to do so, remove all containers from fire area as well.

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE: CARBON DIOXIDE, CARBON MONOXIDE, HALOGENATED COMPOUNDS, METAL OXIDE / OXIDES, FORMALDEHYDE AND OTHER TOXIC FUMES

Section -6. ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

Section -7. HANDLING AND STORAGE

7.1 Handling:

No smoking, eating and drinking during handling. Wash hands and face before eating, drinking, or smoking.
Avoid exposure during pregnancy/while nursing.
Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.
Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.
Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.
Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.
Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.
Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

7.2 Storage:

Observe label precautions. Store between 32/F and 95/F (0/C and 35/C) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Engineering measures:

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).
If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

8.2 Exposure limits

Work place exposure limits (8 hour)

| Substance | OSHA | ACGIH TWA |
|---------------------------------|--|--|
| ALIPHATIC POLYSULFIDE-POLYMER * | Not known | Not known |
| PHENOLIC POLYMER * | Not known | Not known |
| TOLUENE (Methylbenzene)* | 200 ppm | 20 ppm |
| CALCIUM CARBONATE * | 5 mg/m ³ (RESPIRABLE FRACTION) | 3 mg/m ³ (RESPIRABLE FRACTION) |
| CALCIUM CARBONATE * | 15mg/m ³ (TOTAL DUST) | 10 mg/m ³ (TOTAL DUST) |
| METHYLATED SILICA * | N/A | 3 mg/m ³ (RESPIRABLE PARTICLES) |
| * can be absorbed through skin | | |

8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state at: 68 ° F (20 ° C) Liquid

Flash point: 200 ° F (93 ° C) Method: TCC

Odor: Polysulfide Odor

Appearance: PASTE

Color: BEIGE

Odor Threshold : Data Not Available for Mixture

pH : Data Not Available for Mixture

Melting Point / Freezing Point : Data Not Available for Mixture

Initial Boiling Point and Boiling Range : Data Not Available for Mixture

Evaporation Rate : Data Not Available for Mixture

Flammability (solid, gas) : Data Not Available for Mixture

Upper / Lower Flammability or Explosive Limits : Data Not Available for Mixture

Vapor Pressure : Data Not available for Mixture

Vapor Density : Data Not Available for Mixture

Relative Density : Data Not Availabe For Mixture

Solubility (ies) : Data Not Available for Mixture

Partition Coefficient : n-octanol / water : Data Not Available for Mixture

Auto-ignition Temperature : Data Not Available for Mixture

Decomposition Temperature : Data Not Available for Mixture

Viscosity : Data Not Available for Mixture

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see SDS section 7).

Reactivity : Data Not Available for Mixture

Chemical Stability : Data Not Available for Mixture

Possibility of Hazardous Reactions : Data Not Available for Mixture

Conditions to Avoid : Data Not Available for Mixture

Incompatible Materials : Data Not Available for Mixture

HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE BUT MAY NOT BE LIMITED TO THE FOLLOWING:

- Carbon Monoxide
- Smoke
- Carbon Dioxide
- Formaldehyde
- Halogenated Compounds
- Oxides of Nitrogen
- Metal Oxide / Oxides
- Other Toxic fumes

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs of overexposure include headache, dizziness, fatigue, muscular weakness, drowsiness, reduced fetal weight, increase in fetal deaths, skeletal malformations, and in extreme cases loss of consciousness

Repeated or prolonged contact with the preparation may cause Defatting of the skin resulting in non-allergic dermatitis and absorption through the skin.

The liquid splashed in the eyes causes serious eye irritation and damage.

Irritating to mouth, throat and stomach. Ingestion causes reduced fetal weight, increased fetal deaths and skeletal malformations

Formaldehyde is released during curing.

ACUTE TOXICITY:

| PRODUCT: | RESULT | SPECIES | DOSE | EXPOSURE |
|-------------------|-----------------------|---------|---------------------|----------|
| Calcium Carbonate | LD50 ORAL | Rat | 6450 mg/kg | - |
| Toluene | LC50 Inhalation Vapor | Rat | 49 g/m ³ | 4 Hours |
| | LC50 Inhalation Vapor | Rat | 8000 ppm | 4 Hours |
| | LD50 Dermal | Rabbit | 8.39 g/kg | - |
| Methylated Silica | LD50 ORAL | Rat | 636 mg/kg | - |
| | LD50 ORAL (Acute) | Rat | > 6350 mg/kg | - |
| | LD50 Dermal (Acute) | Rat | > 2000 mg/kg | - |

CARCINOGENICITY:

| INGREDIENT | IARC | OSHA | NTP | CAS# |
|------------|------|------|-----|----------|
| TOLUENE : | 3 | - | - | 108-88-3 |

SPECIFIC TARGET ORGAN TOXICITY-STOT (SINGLE EXPOSURE)

LIQUID POLYMER - CATEGORY 3

TOLUENE - CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY-STOT (REPEATED EXPOSURE)

TOLUENE - CATEGORY 2

TARGET ORGANS: BRAIN, BLOOD, KIDNEYS, LUNGS, REPRODUCTIVE SYSTEM, LIVER, HEART, PERIPHERAL NERVOUS SYSTEM, GASTROINTESTINAL TRACT, UPPER RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, EYE, LENS AND/OR CORNEA.

ASPIRATION HAZARD:

TOLUENE - CATEGORY 1

| ACUTE TOXICITY ESTIMATES : | ROUTE | ATE VALUE |
|----------------------------|-------|-------------|
| | ORAL | 41832 mg/kg |

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

Toxicity : N/A

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Persistence and Degradability :

| Product / Ingredient | Aquatic Half Life | Photolysis | Biodegradability |
|----------------------|-------------------|------------|------------------|
| Toluene | - | - | Readily |

Bioaccumulative Potential :

| Product / Ingredient | LogP(ow) | BCF | Potential |
|----------------------|----------|------|-----------|
| Toluene | 2.73 | 8.32 | low |

Toxicity to Fish :

| PRODUCT: | RESULT | SPECIES | DOSE | EXPOSURE |
|-------------------|--------|-------------------|--------------|----------|
| Methylated Silica | LC 50 | Brachydanio Rerio | >10000 mg/l | 96 hours |
| | EC 50 | Daphnia Magna | > 10000 mg/l | 24 hours |

Mobility in Soil : Not Available

13. DISPOSAL CONSIDERATIONS

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.

React with curing agent and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

14. TRANSPORT INFORMATION

DOT: Not regulated

UN Number: Not regulated

IATA: Not regulated

IMDG/IMO: Not regulated

NMFC: 4620 SUB.5 – CL.60

Schedule B # 3506.91.0000

15. REGULATORY INFORMATION

US Regulations Federal

| chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA) | Chemical Name | CAS No | Weight % | Threshold limit (Reporting Value) |
|---|-------------------------|----------|----------|-----------------------------------|
| | TOLUENE (Methylbenzene) | 108-88-3 | <10% | Unknown |
| | LIQUID POLYMER | N/A | <70% | Unknown |
| | LIQUID PHENOLIC POLYMER | N/A | <70% | Unknown |
| | Calcium Carbonate | 471-34-1 | <45% | Unknown |

SARA notifications must remain attached to this SDS. Any copies and /or distribution of this SDS must include all SARA notifications.

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

US Regulations State

| | | | | |
|--|----------------|----------|------|---------|
| California Proposition 65 (Developmental – Female) | TOLUENE | 108-88-3 | <10% | >= 1.0% |
| Massachusetts | TOLUENE | 108-88-3 | <10% | >= 1.0% |
| New Jersey | TOLUENE | 108-88-3 | <10% | >= 1.0% |
| Pennsylvania | TOLUENE | 108-88-3 | <10% | >= 1.0% |
| Rhode Island | TOLUENE | 108-88-3 | <10% | >= 1.0% |
| California Proposition 65 (Developmental – Female) | LIQUID POLYMER | N/A | <70% | >= 1.0% |
| Massachusetts | LIQUID POLYMER | N/A | <70% | >= 1.0% |
| New Jersey | LIQUID POLYMER | N/A | <70% | >= 1.0% |
| Pennsylvania | LIQUID POLYMER | N/A | <70% | >= 1.0% |
| Rhode Island | LIQUID POLYMER | N/A | <70% | >= 1.0% |

Continued on Next Page

Continued From Previous Page

| | | | | |
|---|-------------------------|------------|------|---------|
| California Proposition 65 (Developmental – Female) | LIQUID PHENOLIC POLYMER | N/A | <70% | >= 1.0% |
| Massachusetts | LIQUID PHENOLIC POLYMER | N/A | <70% | >= 1.0% |
| New Jersey | LIQUID PHENOLIC POLYMER | N/A | <70% | >= 1.0% |
| Pennsylvania | LIQUID PHENOLIC POLYMER | N/A | <70% | >= 1.0% |
| Rhode Island | LIQUID PHENOLIC POLYMER | N/A | <70% | >= 1.0% |
| California Proposition 65 (Developmental – Female) | Calcium Carbonate | 471-34-1 | <45% | >= 1.0% |
| Massachusetts | Calcium Carbonate | 471-34-1 | <45% | >= 1.0% |
| New Jersey | Calcium Carbonate | 471-34-1 | <45% | >= 1.0% |
| Pennsylvania | Calcium Carbonate | 471-34-1 | <45% | >= 1.0% |
| Rhode Island | Calcium Carbonate | 471-34-1 | <45% | >= 1.0% |
| California Proposition 65 (Developmental – Female) | Methylated Silica | 67762-90-7 | <10% | >= 1.0% |
| Massachusetts | Methylated Silica | 67762-90-7 | <10% | >= 1.0% |
| New Jersey | Methylated Silica | 67762-90-7 | <10% | >= 1.0% |
| Pennsylvania | Methylated Silica | 67762-90-7 | <10% | >= 1.0% |
| Rhode Island | Methylated Silica | 67762-90-7 | <10% | >= 1.0% |

United States: Sara 302/304 (Sara 304 RQ): Not Applicable

Information On Ingredients: None Were Found

Sara 311/312

Classification: Immediate (acute) Health Hazard, Delayed (chronic) Health Hazard

Information On Ingredients:

Polysulfide Polymer: Immediate (acute) Health Hazard

Phenolic Polymer: Immediate (acute) Health Hazard, Fire Hazard

Toluene: Fire Hazard, Immediate (acute) Health Hazard, Delayed (chronic) Health Hazard

Methylated Silica : Not Available

Sudden Release Of Pressure: No Products

Reactivity: No Products

California Prop. 65 : Warning

This product contains a chemical or chemicals known by the State of California to cause cancer, birth defects, or other reproductive harm.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

Listed National Pollutant Release Inventory (NPRI):TOLUENE CAS:108-88-3

Calcium Carbonate CAS# 471-34-1

Liquid Polysulfide Polymer cas# N/A

Liquid Phenol Polymer cas# N/A

Methylated Silica Cas# 67762-90-7

16. OTHER INFORMATION

| | |
|--------------|---|
| HEALTH | 2 |
| FLAMMABILITY | 2 |
| REACTIVITY | 0 |

| | |
|--------------|---|
| HEALTH | 2 |
| FLAMMABILITY | 2 |
| REACTIVITY | 0 |

Customer and / or end user is responsible for determining PPE.

NFPA**HMIS**

Preparer:

Flamemaster / Compliance

Revision Date: 08/22/2019

Conversion to ANSI format

Supersedes (conversion)

Containers:

plastic jars, metal cans
cartridge kits

Limited Quantity

See SDS Section 14

Maximum container size 50 Gallons / 190 Liters

Notice to reader:

This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.

This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.

Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.

End of Safety Data Sheet