



**FLAMEMASTER**  
 Flamemaster Corp.  
 13576 Desmond Street  
 Pacoima, CA 91331 - USA

**SAFETY DATA SHEET**  
**AUGUST 01, 2019**

**File: CS5500N BB GSA 07-10**  
**High Temperature Fuel Tank**  
**Sealant / Catalyst**

**Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

1.1. Product Identifier: CS-5500N Part B Class B All  
 - Product Name: High Temperature Fuel Tank Sealant / Catalyst Part B  
 - Product reference: CS-5500N-B

1.2. Product Use:  
 - High Temperature Fuel Tank Sealant

1.3. Manufacturer's Name:  
**CAGE Code: 14439**  
 Flamemaster Corp.  
 Chem Seal Division  
 13576 Desmond Street  
 Pacoima, CA 91333 – USA

1.3.1 Suppliers Name ( if not manufacturer )

Technical Contact:  
 Flamemaster Corp.  
 Tel: 818-890-1401  
 Fax: 818-890-6001  
[www.flamemaster.com](http://www.flamemaster.com)

1.4. Emergency Telephone:  
 Chemtrec – Chemtrec International  
 800-424-9300 ( North America)  
 703-527-3887 (Outside North America))

**Specification: AMS 3276/FMS1044/FMS3055/MIL-S-83430 Catalyst /Part B CLASS B All**

<b>NSN:</b>	8030-01-252-7963 CS5500N B1/2 2.5 OZ	8030-00-602-0045 CS5500N B1/2 6OZ	8030-00-602-0039 CS5500N B1/2 1/2 PINT	8030-00-348-7888 CS5500N B1/2 PINT	8030-00-322-7275 CS5500N B1/2 50 GAL
	8030-01-214-0374 CS5500N B1/4 6OZ.	8030-00-560-8758 CS5500N B-2 6 OZ.	8030-00-485-3237 CS5500N B-2 PINT	8030-01-066-6444 CS5500N B-2 QUART	8030-00-585-4900 CS5500N B-2 GAL
	8030-00-560-8759 CS5500N B-2 5-GAL	8030-00-035-0083 CS5500N B-2 50 GAL	8030-00-602-0035 CS5500N B-6 6OZ.	8030-00-602-0038 CS5500N B-6 5-GAL	8030-01-195-0655 CS5500 B-4 Quart

---

---

**Section -2. HAZARD ( S ) IDENTIFICATION**

---

---

ASPIRATION HAZARD - CATEGORY 1  
ACUTE TOXICITY (ORAL) 4, H302  
ACUTE TOXICITY (INHALATION) 4, H332  
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2  
SKIN CORROSION/IRRITATION - Category 2  
SKIN SENSITIZATION 1, H317  
CARCINOGENICITY 2, H351  
TOXIC TO REPRODUCTION (FERTILITY) 2, H361f  
SPECIFIC TARGET ORGAN TOXICITY (STOT) REPEATED EXPOSURE 2, H373  
AQUATIC (ACUTE) - CATEGORY 3  
AQUATIC (CHRONIC) - CATEGORY 3

**OSHA / HCS STATUS :** THIS MATERIAL IS CONSIDERED HAZARDOUS BY THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

Human and Environmental Hazards:

**HAZARD STATEMENTS:**

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - H304  
HARMFUL IF SWALLOWED - H302  
HARMFUL IF INHALED - H332  
CAUSES SERIOUS EYE IRRITATION - H319  
CAUSES SKIN IRRITATION - H315  
MAY CAUSE AN ALLERGIC SKIN REACTION - H317  
SUSPECTED OF CAUSING CANCER - H351  
SUSPECTED OF DAMAGING FERTILITY - H361f  
MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE - H373  
HARMFUL TO AQUATIC LIFE  
HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS - H412

**HAZARD PICTOGRAMS:**



**SIGNAL WORD :** DANGER

**GENERAL PRECAUTIONARY STATEMENTS:**

P101: If medical advise is needed, have product container or label at hand.  
P102: keep out of reach of children.  
P103: Read label before use.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage,use and disposal are beyond our control and may be beyond our knowledge.

**SPECIFIC PRECAUTIONARY STATEMENTS ASSOCIATED WITH THIS PRODUCT:**

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P260: Do not breathe dust / fumes / gas / mist / vapors / spray.
- P261: Avoid breathing dust / fumes / gas / mist / vapors / spray.
- P264: Wash thoroughly after handling.
- P270: Do not eat, drink, or smoke when using this product.
- P271: Use only outdoors or in a well - ventilated area.
- P272: Contaminated work clothing should not be allowed out of the workplace.
- P273: Avoid release to the environment.
- P280: Wear protective gloves / protective clothing / eye protection / face protection.
- P281: Use personal protection equipment as required.
- P301+310: IF SWALLOWED: Immediately call a POISON CENTER / doctor / ...
- P301+312: IF SWALLOWED: Call a POISON CENTER / doctor / .../ if you feel unwell.
- P302+352: IF ON SKIN: Wash with plenty of water / ...
- P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+351+338: IF IN EYES: Rinse cautiously for several minutes. Remove contact lenses if present and easy to do-continue rinsing.
- P308+313: If exposed: Call a POISON CENTER or doctor / physician.
- P312: Call a POISON CENTER / doctor /... / if you feel unwell.
- P314: Get medical advise / attention if you feel unwell.
- P321: Specific treatment...See Label Information
- P330: Rinse mouth
- P331: Do NOT induce vomiting.
- P332+313: If skin irritation occurs: Get medical advice / attention.
- P333+313: If skin irritation or a rash occurs: Get medical advice / attention.
- P337+313: If eye irritation persists: Get medical advice / attention.
- P362: Take off all contaminated clothing.
- P363: Wash contaminated clothing before reuse.
- P391: Collect spillage.
- P405: Store locked up.
- P501: Dispose of contents / containers in accordance with local / regional / national / international regulations

**HAZARDS NOT OTHERWISE CLASSIFIED: OXIDISING POTENTIAL:** Contact with combustible material may result in fire. Keep away from combustible materials. This material increases the risk of fire and may aid in combustion. In the event of sanding, grinding, or abrading:  
 H372 Causes damage to organs through prolonged or repeated exposure.

**Other Hazards that do not result in classification:**  
 Prolonged or repeated exposure may dry skin and / or cause irritation

---

**Section -3. COMPOSITION / INFORMATION ON INGREDIENTS**

---

**Chemical family :** Mixture of organic compounds  
 For the hazards of the composition, ( SDS see Section 2).

---

<b>CHEMICAL NAME: MANGANESE DIOXIDE</b>	CAS# 1313-13-9	EC# 215-202-6	<65% by weight
OSHA HAZARDS: TARGET ORGAN EFFECT,TOXIC BY INHALATION			
TARGET ORGANS: NERVES, LUNGS			
GHS CLASSIFICATION:			
ACUTE TOXICITY,ORAL (CATEGORY 4) - H302			
ACUTE TOXICITY,INHALATION (CATEGORY 4) - H332			
<b>CHEMICAL NAME: TERPHENYL, HYDROGENATED</b>	CAS# 61788-32-7	EC# 262-967-7	<50% by weight
AQUATIC CHRONIC (CATEGORY 4) - H413			

<b>CHEMICAL NAME: ZEOLITES</b> NOT CLASSIFIED	CAS#1318-02-1	EC# 215-283-8	<15% by weight
<b>CHEMICAL NAME: TALC</b> NOT CLASSIFIED	CAS# 14807-96-6	EC# 238-877-9	<10% by weight
<b>CHEMICAL NAME: CARBON BLACK</b> NOT CLASSIFIED	CAS# 1333-86-4	EC# 215-609-9	<10% by weight
<b>CHEMICAL NAME: TERPHENYL</b> AQUATIC ACUTE (CATEGORY 1) - H400 AQUATIC CHRONIC (CATEGORY 1) - H410	CAS# 26140-60-3	EC# 247-477-3	<10% by weight
<b>CHEMICAL NAME: 1,3 DIPHENYLGUANIDINE</b> ACUTE TOXICITY (CATEGORY 4) - H302 SKIN IRRITATION (CATEGORY 2) - H315 EYE IRRITATION (CATEGORY 2) - H319 REPRODUCTIVE (CATEGORY 2) - H361f (FERTILITY) STOT-SINGLE EXPOSURE (CATEGORY 3) - H335	CAS# 102-06-7	EC# 203-002-1	<10% by weight
<b>CHEMICAL NAME: BIS(PIPERIDINOTHIOCARBONYL) TETRASULFIDE</b> SKIN SENSITIVITY (CATEGORY 1) - H317	CAS# 120-54-7	EC# 204-406-0	<3% by weight
<b>CHEMICAL NAME: POLYPHENYL, QUATER AND HIGHER</b>	CAS# 68956-74-1		<10% by weight
<b>MAGNESIUM CARBONATE</b>	CAS# 546-93-0		<10% by weight

---



---

#### Section -4. FIRST-AID MEASURES

---

**General:** When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

**Inhalation:** Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

**Eye contact:** Check for and remove any contact lenses. Irrigate with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek immediate medical attention.

**Skin contact:** Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

**Ingestion:** If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

---



---

#### Section -5. FIRE-FIGHTING MEASURES

---

##### Extinguishing agents

**Recommended:** Universal resistant foam, CO2, water, powder.

**Agents to avoid:** None known

##### Attention

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

**HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE BUT MAY NOT BE LIMITED TO THE FOLLOWING:**

- Carbon monoxide
- Sulfur oxides
- Carbon Dioxide
- Oxides of nitrogen
- Metal Oxide / Oxides
- Manganese Compounds
- Smoke
- Toxic Fumes

Emits toxic fumes when heated.

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

---

---

**Section -6. ACCIDENTAL RELEASE MEASURES**

---

---

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

---

---

**Section -7. HANDLING AND STORAGE**

---

---

**7.1 Handling:**

No smoking, eating and drinking during handling.

Avoid exposure during pregnancy/while nursing.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

**7.2 Storage:**

Observe label precautions. Store between 32/F and 95/F ( 0/C and 35/C ) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

---

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

---

**8.1 Engineering measures:**

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

---

---

## 8.2 Exposure limits

---

### Work place exposure limits ( 8 hour )

Substance	ACGIH TLV
Manganese Dioxide	TWA: 0.1mg/m <sup>3</sup> (as Mn) 8 hours (Inhalable Fraction)
	TWA: 0.02mg/m <sup>3</sup> (as Mn) 8 hours (Respirable Fraction)
Terphenyl, Hydrogenated	TWA: 4.9 mg/m <sup>3</sup> 8 hours
	TWA: 0.5 ppm 8 hours
Zeolites	TWA: 1mg/m <sup>3</sup> 8 hours (Respirable Fraction)
Talc	TWA: 2mg/m <sup>3</sup> 8 hours (Respirable Fraction)
Carbon Black	TWA: 3mg/m <sup>3</sup> 8 hours ( Inhalable Fraction)
Terphenyl	C: 5mg/m <sup>3</sup>
	C: 0.53 ppm
MAGNESIUM CARBONATE	TWA: 5mg/m <sup>3</sup> (Respirable Fraction)
	TWA: 15 mg/m <sup>3</sup> 8 hours (Total Dust)

### 8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

#### Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

#### Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

#### Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

#### Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

---

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

---

- Physical state at: 68 ° F (20 ° C) Liquid
- Flash point: 200 ° F (93 ° C) Method: TCC
- Color: BLACK
- Appearance: PASTE
- Odor: NEGLIGIBLE OILY ODOR
- Odor Threshold : Data Not Available for Mixture
- pH : Data Not Available for Mixture
- Melting Point / Freezing Point : Data Not Available for Mixture
- Initial Boiling Point and Boiling Range : Data Not Available for Mixture
- Evaporation Rate : Data Not Available for Mixture
- Flammability (solid, gas) : Data Not Available for Mixture
- Upper / Lower Flammability or Explosive Limits : Data Not Available for Mixture
- Vapor Pressure : Data Not available for Mixture
- Vapor Density : Data Not Available for Mixture
- Relative Density : Data Not Available For Mixture
- Solubility (ies) : Data Not Available for Mixture
- Partition Coefficient : n-octanol / water : Data Not Available for Mixture
- Auto-ignition Temperature : Data Not Available for Mixture
- Decomposition Temperature : Data Not Available for Mixture
- Viscosity : Data Not Available for Mixture

---

---

## 10. STABILITY AND REACTIVITY

---

---

Stable under recommended storage and handling conditions (see SDS section 7).

**HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE BUT MAY NOT BE LIMITED TO THE FOLLOWING:**

- |                   |                        |               |
|-------------------|------------------------|---------------|
| • Carbon monoxide | • Oxides of nitrogen   | • Smoke       |
| • Sulfur oxides   | • Metal Oxide / Oxides |               |
| • Carbon Dioxide  | • Manganese Compounds  | • Toxic Fumes |

Emits toxic fumes when heated.

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

Reactivity : Data Not Available for Mixture

Chemical Stability : Data Not Available for Mixture

Possibility of Hazardous Reactions : Data Not Available for Mixture

Conditions to Avoid : Data Not Available for Mixture

Incompatible Materials : Data Not Available for Mixture

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

---

---

**11. TOXICOLOGICAL INFORMATION**

---

---

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health

**ACUTE TOXICITY:**

PRODUCT:	RESULT	SPECIES	DOSE	EXPOSURE
Manganese Dioxide	LD50 ORAL	Rat	3478 mg/kg	-
Terphenyl,Hydrogenated	LD50 ORAL	Rat	17500 mg/kg	-
Zeolites	LD50 ORAL	Rat	>5 g/kg	-
Carbon Black	LD50 Dermal	Rabbit	>3 g/kg	-
	LD50 Oral	Rat	>15400mg/kg	-
Terphenyl	LD50 Oral	Rat	>1400 mg/kg	-
Magnesium Carbonate	LD50 Oral	Rat	8000mg/kg	-
1, 3-Diphenylguanidine	LD50 Oral	Rat	323mg/kg	-

**CARCINOGENICITY:**

INGREDIENT	IARC	OSHA	NTP
Zeolites	3	-	-
Carbon Black, Respirable Powder	2B	-	-

**Specific Target Organ Toxicity (STOT)- Single Exposure**

1,3-Diphenylguanidine - (Category 3)

Zeolites - (Category 3)

Talc - (Category 3)

This Product is Harmful if Swallowed or Inhaled.

This Product also Causes Serious Eye Irritation.

This Product Causes Skin Irritation, Defatting of the Skin, and May Cause an Allergic Reaction.

**Specific Target Organ Toxicity (STOT) - Repeated Exposure:**

Manganese Dioxide - (Category 2)

**Potential chronic health effects include the following:**

May cause damage to organs through prolonged or repeated exposure. May lead to defatting of the skin and / or irritation.

May lead to allergic reactions.

Suspected of causing cancer.

Suspected of damaging fertility

**Target Organs:** lungs, skin, central nervous system, blood, kidneys, nervous system, liver, spleen, lymphatic system, cardiovascular system, upper respiratory tract, bone marrow, eye, lens, cornea

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage,use and disposal are beyond our control and may be beyond our knowledge.



---

---

**12. ECOLOGICAL INFORMATION**

---

---

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

**Bioaccumulative Potential:**

Product	LogPow	BCF	Potential
1,3 Diphenylguanidine	1.69	19.95	Low
Bis(piperidinothiocarbonyl) tetrasulfide	2.8	16.98	Low

PERSISTENCE AND DEGRADABILITY: No Data Available for Finished Product

AQUATIC HALF LIFE : No Data Available for Finished Product

PHOTOLYSIS : No Data Available for Finished Product

BIODEGRADABILITY : No Data Available for Finished Product

BIOACCUMULATIVE POTENTIAL : No Data Available for Finished Product

MOBILITY IN SOIL : No Data Available for Finished Product

---

---

**13. DISPOSAL CONSIDERATIONS**

---

---

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.

React with base and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

---

---

**14. TRANSPORT INFORMATION**

---

---

**DOT:** Not regulated

**UN Number:** Not regulated

**IATA:** Not regulated

**IMDG/IMO:** Not regulated

**NMFC:** 4620 SUB.5 – CL.60

**Schedule B #** 3506.91.0000

---

---

**15. REGULATORY INFORMATION**

---

---

**Other EU Regulations:**

1,3-Diphenylguanidine - Reproductive (Category 2) H361f (Fertility)

**SARA 311/312**

Classification: Immediate (acute) health hazard

Delayed (chronic) health hazard

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

**Composition of Ingredients :**

Manganese Dioxide : Immediate (acute) health hazard  
 Delayed (chronic) health hazard

Zeolites : Immediate (acute) health hazard

Polyphenyls, quater and higher : Immediate (acute) health hazard

Talc : Immediate (acute) health hazard

Carbon Black : Fire Hazard  
 Delayed (chronic) health hazard

Terphenyl : Immediate (acute) health hazard

1,3-Diphenylguanidine : Fire Hazard  
 Immediate (acute) health hazard  
 Delayed (chronic) health hazard

Bis(piperidinothiocarbonyl) : Fire Hazard  
 tetrasulfide Immediate (acute) health hazard

**US Regulations Federal**

chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA)	Chemical Name	CAS No	Weight %	Threshold limit
	Manganese Dioxide	1313-13-9	<65%	Unknown

SARA notifications must remain attached to this SDS. Any copies and /or distribution of this SDS must include all SARA notifications.

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

**US Regulations State**

California Proposition 65 (Developmental – Female)	<b>MANGANESE DIOXIDE</b>	1313-13-9	< 65%	unknown
Massachusetts	<b>MANGANESE DIOXIDE</b>	1313-13-9	< 65%	unknown
New Jersey	<b>MANGANESE DIOXIDE</b>	1313-13-9	< 65%	unknown
Pennsylvania	<b>MANGANESE DIOXIDE</b>	1313-13-9	<65%	unknown
Rhode Island	<b>MANGANESE DIOXIDE</b>	1313-13-9	<65%	unknown

**California Prop 65 Warning :**

This Product contains one or more ingredients known by the state of California to cause cancer or reproductive harm.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR. Listed National Pollutant Release Inventory (NPRI):Manganese Dioxide cas#1313-13-9

HEALTH	3	HEALTH	3	Customer and / or end user is responsible for determining PPE.
FLAMMABILITY	1	FLAMMABILITY	1	
REACTIVITY	1	REACTIVITY	1	

**NFPA**

**HMIS**

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage,use and disposal are beyond our control and may be beyond our knowledge.

---

---

**Section 16 Other Information**

---

---

Preparer-Flamemaster/Compliance  
Supercedes(Conversion)

Revision Date: 08/01/2019    Conversion to ANSI format

Containers: Plastic Jars, Metal Cans, Cartridge Kits

Maximum Container Size: 50 Gallons/190 Liters

**Notice to reader:**

**This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.**

**In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.**

**This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.**

**Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.**

**END OF SAFETY DATA SHEET**