



FLAMEMASTER
 Flamemaster Corp.
 13576 Desmond Street
 Pacoima, CA 91331 - USA

SAFETY DATA SHEET
 JANUARY 2018

File: CS7707B GSA 07-10
 NYLON EPOXY COATING
 COMPOUND /CATALYST

Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1. Product Identifier: CS-7707 PT B - NYLON EPOXY COATING-CATALYST
 - Product Name : NYLON EPOXY COATING COMPOUND
 - Product reference: CS-7707-B

1.2. Product Use:
 - NYLON EPOXY COATING COMPOUND

1.3. Manufacturer's Name:
 CAGE Code: 14439
 Flamemaster Corp.
 Chem Seal Division
 13576 Desmond Street
 Pacoima, CA 91333 – USA

1.3.1 Suppliers Name (if not manufacturer)

Technical Contact:
 Flamemaster Corp.
 Tel: 818-890-1401
 Fax: 818-890-6001
www.flamemaster.com

1.4. Emergency Telephone:
 Chemtrec – Chemtrec International
 800-424-9300 (North America)
 703-527-3887 (Outside North America))

| | | | |
|--------------------------------|------------------------------|---------------------|-----------|
| Specification: Boeing DPM 2389 | | Nylon Epoxy Coating | Base PT B |
| NSN: | NONE ISSUED FOR THIS PRODUCT | | |

Section -2. HAZARD (S) IDENTIFICATION

OSHA/HCS STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

CLASSIFICATION OF THE MIXTURE:

FLAMMABLE LIQUID - CATEGORY 2

ASPIRATION HAZARD - CATEGORY 1

ACUTE TOXICITY, ORAL - CATEGORY 4

ACUTE TOXICITY (INHALATION) - CATEGORY 4

ACUTE TOXICITY (DERMAL) - CATEGORY 4

CARCINOGENICITY - Category 1A

SKIN CORROSION/IRRITATION - Category 1B

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

SKIN SENSITIZATION - CATEGORY 1

TOXIC TO REPRODUCTION - CATEGORY 2

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE - (NARCOTIC EFFECTS) - CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY-REPEAT EXPOSURE -CATEGORY 2

REPRODUCTIVE TOXICITY, EFFECTS ON OR VIA LACTATION

AQUATIC (ACUTE) - CATEGORY 2

AQUATIC (CHRONIC) - CATEGORY 2

GHS LABEL REQUIREMENTS:

HAZARD PICTOGRAMS:



SIGNAL WORD : DANGER

HAZARD STATEMENTS:

HIGHLY FLAMMABLE LIQUID AND VAPOR - H225

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - H304

HARMFUL IF SWALLOWED - H302

HARMFUL IF INHALED - H332

HARMFUL IN CONTACT WITH SKIN - H312

MAY CAUSE CANCER - H350

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE - H314

MAY CAUSE AN ALLERGIC SKIN REACTION - H317

SUSPECTED OF DAMAGING FERTILITY. SUSPECTED OF DAMAGING THE UNBORN CHILD - H361fd

MAY CAUSE DROWSINESS OR DIZZINESS - H336

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE - H373

MAY CAUSE HARM TO BREAST-FED CHILDREN - H362

VERY TOXIC TO AQUATIC LIFE - H400

TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS - H411

In the event of sanding, grinding, or abrading:

H372 Causes damage to organs through prolonged or repeated exposure.

Hazards Not Otherwise Classified (HNOC):

Sanding and grinding dust may be harmful if inhaled. Sanding and grinding dust may form combustible concentrations in air. Emits toxic fumes when heated.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

PRECAUTIONARY STATEMENTS:

- P101+P102+P103: If medical advice is needed, have product container or label at hand. Keep out of reach of children.
- Read label before use
- P202: Do not handle until all safety precautions have been read and understood
- P210: Keep away from heat/sparks/open flames and hot surfaces-No Smoking
- P240:Ground/bond container and receiving equipment
- P261+P262+P263+P264:Avoid breathing dust/fumes/gas/mist/vapours/spray.Do not get in eyes , on skin, or on clothing. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling.
- P270+P271+P273: Do not eat drink or smoke when using this product. Use only outdoors or in a well ventilated area. Avoid release to the environment.
- P281+P280: Use personal protective equipment as required. Wear protective gloves/ protective clothing/ eye protection/face protection
- P301+P310+P331: If swallowed: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting.
- P305+P351+P338+P315: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,if present and easy to do. Continue rinsing. Get immediate medical advice attention.
- P304+P340+P314: If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell
- P342+P340+P315: If experiencing respiratory symptoms: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice/attention.
- P302+P352: If on skin (or in hair) : Wash with plenty of soap and water. If skin irritation occurs seek medical attention
- P306+P361: If on clothing: Remove/ take off immediately all contaminated clothing
- P402+P403+P404: Store in a dry place. Store in a well ventilated space. Store in a closed container.
- P233+P234+P235: Keep container tightly closed. Keep only in original container. Keep cool.

SUPPLEMENTAL LABEL ELEMENTS:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of concentrations above recommended limits causes headaches, drowsiness and nausea and could lead to unconsciousness or possibly death.
 irritating to the mucous membranes and may cause the skin to become sensitized.
 Avoid any contact with skin or clothing and wash thoroughly after handling.
 Emits toxic fumes when heated.

HAZARDS NOT OTHERWISE CLASSIFIED:

Prolonged or repeated exposure may dry skin and / or cause skin irritation.
 Sanding and grinding dust may be harmful if inhaled. Sanding and grinding dust may form combustible concentrations in air.

In the event of sanding, grinding, or abrading:

H372 Causes damage to organs through prolonged or repeated exposure.

Section -3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical family : Mixture of organic compounds
 For the hazards of the composition, (SDS see Section 2).

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS):

| % BY WEIGHT IN PRODUCT- | HAZARDOUS INGREDIENT | CAS#- |
|--|-------------------------------------|--------------|
| <70% | ETHANOL VANZOL PROPRIETARY SOLUTION | N/A |
| FLAMMABLE LIQUID - CATEGORY 2 H225 | | |
| SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A - H319 | | |
| CARCINOGENICITY - Category 1A - H350 | | |
| AQUATIC (ACUTE) - CATEGORY 2 - H401 | | |
| AQUATIC (CHRONIC) - CATEGORY 2 - H411 | | |

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage, use and disposal are beyond our control and may be beyond our knowledge.

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS) :

TRIETHYLENETETRAMINE

112-24-3

<10%

HARMFUL IF SWALLOWED - (302)

HARMFUL IN CONTACT WITH SKIN - H312

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE - H314

CAUSES SERIOUS EYE DAMAGE - (H318)

MAY CAUSE AN ALLERGIC SKIN REACTION - H317

Section -4. FIRST-AID MEASURES

General: When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

Eye contact: Check for and remove any contact lenses. Irrigate with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek immediate medical attention.

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

Section -5. FIRE-FIGHTING MEASURES

Extinguishing agents

Recommended: Universal resistant foam, CO₂, water, powder.

Agents to avoid: None known

Attention

Promptly remove all persons in the event of a fire from the fire area. If safe to do so, remove all containers from fire area as well.

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Do not allow run-off from fire fighting to enter drains or water courses.

Emits toxic fumes when heated.

HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE BUT MAY NOT BE LIMITED TO THE FOLLOWING:

- Carbon Dioxide
- Carbon Monoxide
- Carbon Oxides
- Airborn Solids and Liquid Particulates
- Nitric Acid
- Nitrogen Oxides
- Nitrogen Oxides can react with water vapors to form corrosive nitric acid
- Unidentified Organic and Inorganic Compounds
- Toxic Fumes
- Smoke
- Ammonia Gas
- Nitrosamines
- Other Hazardous Materials

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

Section -6. ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Section -7. HANDLING AND STORAGE

7.1 Handling:

No smoking, eating and drinking during handling.

Avoid exposure during pregnancy/while nursing.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

7.2 Storage:

Observe label precautions. Store between 32/F and 95/F (0/C and 35/C) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Engineering measures:

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

8.2 Exposure limits

Work place exposure limits (8 hour)

| OSHA | PRODUCT | ACGIH |
|------|-------------------------------------|-------|
| | ETHANOL VANZOL PROPRIETARY SOLUTION | |
| | No Data Available on the Mixture | |

TRIETHYLENETETRAMINE (TWA) : WEEL 1 ppm - 6mg /m3

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

9. PHYSICAL AND CHEMICAL PROPERTIES

- **Physical state at: 68 ° F (20 ° C) LIQUID**

- Flash point: 61 ° F (16.1 ° C) Method: TCC
- Specific gravity at: 68 ° F (20 ° C) .89 g/cm³
- Vapor Density: 1.4
- Lower Explosive Limit (% vol.): 3.3
- Upper Explosive Limit (% vol.): 19.0
- Miscibility in water at 20 ° C: MODERATE

- **Ph : 10.5**

- % Volatile by Volume: 88
- Vapor pressure at: 68 ° F (20 ° C): 30
- Color: AMBER
- Appearance: SYRUP
- Odor: ALCOHOL ODOR
- Boiling Point: 174 ° F

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see SDS section 7). In case of combustion, may produce hazardous decomposition products such as :

HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE BUT MAY NOT BE LIMITED TO THE FOLLOWING:

- Carbon Dioxide
- Carbon Monoxide
- Carbon Oxides
- Airborn Solids and Liquid Particulates
- Nitric Acid
- Nitrogen Oxides
- Nitrogen Oxides can react with water vapors to form corrosive nitric acid
- Unidentified Organic and Inorganic Compounds
- Toxic Fumes
- Smoke
- Ammonia Gas
- Nitrosamines
- Other Hazardous Materials

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs of overexposure include headache, dizziness, fatigue, muscular weakness, drowsiness, reduced fetal weight, increase in fetal deaths, skeletal malformations, and in extreme cases loss of consciousness

Repeated or prolonged contact with the preparation may cause Defatting of the skin resulting in non-allergic dermatitis and absorption through the skin.

The liquid splashed in the eyes causes serious eye irritation and damage.

Irritating to mouth, throat and stomach. Ingestion causes reduced fetal weight, increased fetal deaths and skeletal malformations

ACUTE TOXICITY:**ETHANOL VANZOL PROPRIETARY SOLUTION**

Oral - ATEmix (): 3,094.125932 mg/kg

Dermal - ATEmix (): 40,000.000002 mg/kg

Inhalation : No Data Available

| ENDPOINT | SPECIES | PRODUCT | DOSE | EXPOSURE |
|-------------|---------|----------------------|------------|----------|
| LD50 ORAL | Rat | TRIETHYLENETETRAMINE | 1716 mg/kg | - |
| LD50 Dermal | Rabbit | | 1465 mg/kg | - |

CORROSION / IRRITATION**PRODUCT**

TRIETHYLENETETRAMINE - Severe Eye / skin Irritation

CARCINOGENICITY:**PRODUCT**

| IARC | OSHA | NTP | CAS# |
|---|------|-----|------|
| TRIETHYLENETETRAMINE - No Data Available | | | |
| ETHANOL VANZOL PROPRIETARY SOLUTION - No Data Available | | | |

Sensitizer:

TRIETHYLENETETRAMINE - May Cause Sensitization by Skin Contact

TARGET ORGANS: BRAIN, BLOOD, KIDNEYS, LUNGS, REPRODUCTIVE SYSTEM, LIVER, HEART, PERIPHERAL NERVOUS SYSTEM, GASTROINTESTINAL TRACT, UPPER RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, NERVOUS SYSTEM, EYE, LENS AND/OR CORNEA

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

TOXICITY : No Data Available

PERSISTANCE AND DEGRADABILITY: No Data Available

AQUATIC HALF LIFE : No Data Available

PHOTOLYSIS : No Data Available

BIODEGRADABILITY : No Data Available

BIOACCUMULATIVE POTENTIAL : No Data Available

MOBILITY IN SOIL : No Data Available

13. DISPOSAL CONSIDERATIONS

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.

React with curing agent and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

14. TRANSPORT INFORMATION

DOT: § 172.101 HAZARDOUS MATERIALS TABLE

UN Number: UN 1987

Proper Shipping Name: ALCOHOLS N.O.S.

Labels: Flammable Liquid

IATA:

UN Number: 1987

Proper Shipping Name: ALCOHOLS N.O.S.

Labels: Flammable Liquid

Hazard Class: 3 Subclass: NO

Packaging Group: II

Passenger Air Packing Instruction : 309

Passenger aircraft: 60 Liter (16 gallon)

Cargo Air Packing Instruction : 310

Cargo aircraft only: 220 Liter (58 gallon)

Hazard Class: 3 Subclass: NO

Packaging Group: II

Limited Quantity: Passenger aircraft: 60 Liter (16 gallon)

Cargo aircraft only: 220 Liter (58 gallon)

Vessel stowage: A

ERG: 128

NMFC: 4620 SUB.5 – CL.60

Schedule B # 3506.91.0000

IMDG:

UN Number: 1987

Proper Shipping Name: ALCOHOLS N.O.S.

Label: 3

Hazard Class: 3 Subclass: NO

Packaging Group: II

EMS No: F, E – S, D

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

15. REGULATORY INFORMATION

US Regulations Federal

| chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA) | Chemical Name | CAS No | Weight % | Reporting Requirements |
|---|---|----------|----------|------------------------|
| | Ethanopl Vanzol Proprietary solution | N/A | <70% | UNKNOWN |
| | Triethylene Tetramine | 112-24-3 | <10% | UNKNOWN |

SARA notifications must remain attached to this SDS. Any copies and /or distribution of this SDS must include all SARA notifications.

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

United States: Sara 302/304 (Sara 304 RQ): Not Applicable
Information On Ingredients: None Were Found

Sara 311/312

Classification: Fire Hazard, Immediate (acute) Health Hazard, Delayed (chronic) Health Hazard

ETHANOL VANZOL PROPRIETARY SOLUTION - No Data Available

TRIETHYLENETETRAMINE - Acute Health Hazard, Chronic Health Hazard

US Regulations State

US REGULATIONS STATE:

PRODUCT: CAS# STATE:

ETHANOL VANZOL PROPRIETARY SOLUTION APPLICABLE INGREDIENTS LISTED ON STATE RIGHT TO KNOW LISTS:

| | | |
|--------------------------|---------|---|
| ETHANOL | 64-17-5 | New Jersey (RTK) - Listed |
| | | Massachusetts (RTK) - Listed |
| | | Pennsylvania (RTK) - Listed |
| | | Rhode Island (RTK) - Listed |
| | | California Proposition 65 (RTK) - Listed |
| ISOPROPYL ALCOHOL | 67-63-0 | New Jersey (RTK) - Listed |
| | | |
| METHANOL | 67-56-1 | New Jersey (RTK) - Listed |
| | | Massachusetts (RTK) - Listed |
| | | Pennsylvania (RTK) - Listed |
| | | Rhode Island (RTK) - Listed |
| | | California Proposition 65 (RTK) - Listed |

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

METHYL ISOBUTYL KETONE

108-10-1

New Jersey (RTK) - Listed

Massachusetts (RTK) - Listed

Pennsylvania (RTK) - Listed

Rhode Island (RTK) - Listed

California Proposition 65 (RTK) - Listed

California Prop. 65 : Warning


This product contains a chemical or chemicals known by the state of California to cause cancer, birth defects, or other reproductive harm.

Canada



Class B – Flammable

ETHANOL VANZOL
PROPRIETARY SOLUTION



**Class D - Poisonous and Infectious
materials Division 2: Materials Causing
Other Toxic Effects D2A D2B**

ETHANOL VANZOL
PROPRIETARY SOLUTION

TRIETHYLENETETRAMINE
CAS#112-24-3

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

16. OTHER INFORMATION

| | |
|--------------|---|
| HEALTH | 3 |
| FLAMMABILITY | 3 |
| REACTIVITY | 0 |

| | |
|--------------|---|
| HEALTH | 3 |
| FLAMMABILITY | 3 |
| REACTIVITY | 0 |

Customer and / or end user is responsible for determining PPE

NFPA**HMIS**

Preparer:

Flamemaster / Compliance

Revision Date: January 2018

Conversion to ANSI format

Containers:

plastic jars, metal cans
cartridge kits

Limited Quantity

See SDS Section 14

Maximum container size 50 Gallons / 190 Liters

Notice to reader:

This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.

This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.

Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.

End of Safety Data Sheet