



FLAMEMASTER
 Flamemaster Corp.
 13576 Desmond Street
 Pacoima, CA 91331 - USA

SAFETY DATA SHEET
AUGUST 22, 2019

File: CS3201AB GSA 07-10
 Optical Sealant Base

Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1. Product Identifier: CS-3201 Part-A Class-B Base (all application times) Black
 - Product Name: Sealing Compound Part-A
 - Product reference: CS-3201-B (BLACK)

1.2. Product Use:
 - Aircraft Sealant

1.3. Manufacturer's Name:
CAGE Code: 14439
Flamemaster Corp.
Chem Seal Division
13576 Desmond Street
Pacoima, CA 91333 – USA

1.3.1 Suppliers Name (if not manufacturer)

Technical Contact:
Flamemaster Corp.
Tel: 818-890-1401
Fax: 818-890-6001
www.flamemaster.com

Emergency Contact Information :
 See Below

Specification: AMS 7124 / MIL-S-7502

Base PART A

CLASS B

NSN:		8030-00-262-9045 CS3201 B4 PINT KIT	8030-00-031-7781 CS3201 B1/2 PINT KIT	8030-00-322-6928 CS3201 B4 GAL KIT	
		8030-00-851-8379 CS3201 B-2 2.5 OZ	8030-00-613-9083 CS3201 B-2 PINT KIT	8030-01-839-2099 CS3201 B4 QT KIT	

Emergency Contact:

CHEMTEL: WWW.CHEMTELINE.COM

Flamemaster Corporation Contract Number MIS2644301

Shipments of hazardous materials within United States, Canada, Puerto Rico, and U.S. Virgin Island should

reference Chemtel's toll free phone number: 1-800-255-3924 - Reference Number MIS2644301

Shipments and safety applications outside of United States, Canada, Puerto Rico, and the U.S. Virgin Islands

must reference Chemtel phone number +1-813-248-0585 - Reference Number MIS2644301

Collect Calls will be accepted. To ensure a bilingual operator please call collect.

Shipments originating in U.S.A. and going overseas must use both numbers.

Shipments originating overseas and destined for US, Canada, Puerto Rico or the Virgin Islands must also use both numbers.

Calls originating on board vessels should follow normal ship to shore protocols. Use international access number

and alert the ship to shore operator you are involved in an emergency incident.

Shipments of hazardous materials within the listed countries should reference Chemtel's in-country phone numbers:

Australia : 1-300-954-583 : Reference Number MIS2644301

Brazil : 0-800-591-6042 : Reference Number MIS2644301

China : 400-120-0751 : Reference Number MIS2644301

India : 000-800-100-4086 : Reference Number MIS2644301

Mexico : 01-800-099-0731 : Reference Number MIS2644301

Section -2. HAZARD (S) IDENTIFICATION

OSHA/HCS STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

CLASSIFICATION OF THE MIXTURE:

ASPIRATION HAZARD - CATEGORY 1
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION (UNBORN CHILD) - Category 2
TOXIC TO AQUATIC LIFE - Category 4

GHS LABEL REQUIREMENTS

HAZARD PICTOGRAMS



SIGNAL WORD : DANGER

HAZARD STATEMENTS:

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - H304
CAUSES SERIOUS EYE IRRITATION - (H319)
CAUSES SKIN IRRITATION - (H315)
SUSPECTED OF DAMAGING THE UNBORN CHILD - (H361d)
SUSPECTED OF CAUSING CANCER - (H351)
MAY CAUSE LONG LASTING HARMFUL EFFECTS TO AQUATIC LIFE - (H413)

PRECAUTIONARY STATEMENTS:

- P101+P102+P103: If medical advice is needed, have product container or label at hand. Keep out of reach of children.
- Read label before use
- P202: Do not handle until all safety precautions have been read and understood
- P210: Keep away from heat/sparks/open flames and hot surfaces-No Smoking
- P240:Ground/bond container and receiving equipment
- P261+P262+P263+P264:Avoid breathing dust/fumes/gas/mist/vapours/spray.Do not get in eyes , on skin, or on clothing. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling.
- P270+P271+P273: Do not eat drink or smoke when using this product. Use only outdoors or in a well ventilated area. Avoid release to the environment.
- P281+P280: Use personal protective equipment as required. Wear protective gloves/ protective clothing/ eye protection/face protection
- P301+P310+P331: If swallowed: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting.
- P305+P351+P338+P315: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
- P304+P340+P314: If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell
- P342+P340+P315: If experiencing respiratory symptoms: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice/attention.
- P302+P352: If on skin (or in hair) : Wash with plenty of soap and water. If skin irritation occurs seek medical attention
- P306+P361: If on clothing: Remove/ take off immediately all contaminated clothing
- P402+P403+P404: Store in a dry place. Store in a well ventilated space. Store in a closed container.
- P233+P234+P235: Keep container tightly closed. Keep only in original container. Keep cool.

SUPPLEMENTAL LABEL ELEMENTS:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of concentrations above recommended limits causes headaches, drowsiness and nausea and could lead to unconsciousness or possibly death.

1-component mixtures: formaldehyde is released during the curing phase. Formaldehyde may cause irreversible effects, is irritating to the mucous membranes and may cause the skin to become sensitized.

Avoid any contact with skin or clothing and wash thoroughly after handling.

Emits toxic fumes when heated.

HAZARDS NOT OTHERWISE CLASSIFIED:

Prolonged or repeated exposure may dry skin and / or cause skin irritation.

Sanding and grinding dust may be harmful if inhaled. Sanding and grinding dust may form combustible concentrations in air.

Section -3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical family : Mixture of organic compounds

For the hazards of the composition, (SDS see Section 2).

GHS CLASSIFICATION:LIQUID POLYMER

EYE IRRITATION (CATEGORY 2)

SKIN IRRITATION (CATEGORY 2)

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE-(CATEGORY 3)

AQUATIC, CHRONIC (CATEGORY 3)

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS): TOLUENE

FLAMMABLE LIQUIDS (CATEGORY 2),H225

SKIN IRRITATION (CATEGORY 2),H315

REPRODUCTIVE TOXICITY (CATEGORY 2),H361

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE-(CATEGORY 3),CENTRAL NERVOUS SYSTEM,H336

SPECIFIC TARGET ORGAN TOXICITY-REPEATED EXPOSURE (CATEGORY 2),H373

ASPIRATION HAZARD (CATEGORY 1),H304

ACUTE AQUATIC TOXICITY (CATEGORY 2),H401

CALCIUM CARBONATE:

GHS CLASSIFICATION: CALCIUM CARBONATE

EYE DAMAGE (CATEGORY 1)

SKIN IRRITATION (CATEGORY 2)

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE-(CATEGORY 3)

Epoxy Resin with Toluene

FLAMMABLE LIQUIDS - CATEGORY 2

SKIN CORROSION/IRRITATION - CATEGORY 2

SERIOUS EYE DAMAGE/EYE IRRITATION - CATEGORY 2A

SKIN SENSITIZATION - CATEGORY 1

TOXIC TO REPRODUCTION (UNBORN CHILD) - CATEGORY 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (NARCOTIC EFFECTS) - CATEGORY 3

AQUATIC HAZARD (ACUTE) - CATEGORY 2

AQUATIC HAZARD (LONG TERM) - CATEGORY 3

CARBON BLACK:

MAY FORM COMBUSTIBLE DUST CONCENTRATIONS IN AIR

SUBSTANCE % by weight in the product	H&P STATEMENTS	CAS	EINECS/ELINCS
LIQUID POLYMER < 70%	H319,H335,H315,H412,H223, P210,P270,P305+P351+P338 +P313,P306+P361,P370+P260	N/A	POLYMER
TOLUENE (Methylbenzene) < 2%	H225,H304,H315,H319,H332,H336, H361,H371,H401, P210P260,P281,P301+P310,P305+ P351+ P338,P331	108-88-3	203-625-9
Calcium Carbonate <45%	H319 P305+P351+P313,P280	471-34-1	207-439-9
Epoxy Resin with Toluene <3%	H225, H319, H315, H317, H361d, H336, H400, H412	N/A	N/A
CARBON BLACK <3%	May form combustible dust concentrations in air.	1333-86-4	N/A

Section -4. FIRST-AID MEASURES

General: When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

Eye contact: Remove any contact lenses if present and easy to do. Irrigate with clean, fresh water for at least 15 minutes, holding the eye lids apart, and seek immediate medical attention.

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

Section -5. FIRE-FIGHTING MEASURES**Extinguishing agents**

Recommended: Universal resistant foam, CO₂, water, powder.

Agents to avoid: None known

Attention

Promptly remove all persons in the event of a fire from the fire area. If safe to do so, remove all containers from fire area as well.

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE: CARBON DIOXIDE, CARBON MONOXIDE, HALOGENATED COMPOUNDS, METAL OXIDE / OXIDES, SULPHUR OXIDES AND FORMALDEHYDE

Emits toxic fumes when heated.

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

Section -6. ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Section -7. HANDLING AND STORAGE

7.1 Handling:

No smoking, eating and drinking during handling. Wash hands and face before eating, drinking, or smoking.

Avoid exposure during pregnancy/while nursing.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

7.2 Storage:

Observe label precautions. Store between 32/F and 95/F (0/C and 35/C) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Engineering measures:

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

8.2 Exposure limits

Work place exposure limits (8 hour)

Substance	OSHA	ACGIH TWA
LIQUID POLYMER	Not known	Not known
TOLUENE (Methylbenzene)*	200 ppm	20 ppm
CALCIUM CARBONATE *	5 mg/m ³ (RESPIRABLE FRACTION)	3 mg/m ³ (RESPIRABLE FRACTION)
CALCIUM CARBONATE *	15mg/m ³ (TOTAL DUST)	10 mg/m ³ (TOTAL DUST)
CARBON BLACK *	3.5 mg/m ³	3.0 mg/m ³
* can be absorbed through skin		

8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state at: 68 ° F (20 ° C) Liquid
- Flash point: 200 ° F (93 ° C) Method: TCC
- Specific gravity at: 68 ° F (20 ° C) N/A
- Vapor Density: NIL
- Lower Explosive Limit (% vol.): N/A
- Upper Explosive Limit (% vol.): N/A
- Miscibility in water at 20 ° C: NEGLIGIBLE
- VOC: N/A
- Ph : N/A
- Volatile by VOLUME: N/A
- Vapor pressure at: 68 ° F (20 ° C) NIL
- Color: Black
- Appearance: PASTE
- Odor: Polysulfide Odor
- Boiling Point: Unknown
- Material Supports Combustion: Yes

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see SDS section 7).

HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE BUT MAY NOT BE LIMITED TO THE FOLLOWING:

- Carbon Monoxide
- Sulfur Oxides
- Carbon Dioxide
- Formaldehyde
- Halogenated Compounds
- Oxides of Carbon, Nitrogen, Sulfur Dioxide, Trace Hydrogen Sulfide
- Metal Oxide / Oxides
- Smoke

Emits toxic fumes when heated.

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs of overexposure include headache, dizziness, fatigue, muscular weakness, drowsiness, reduced fetal weight, increase in fetal deaths, skeletal malformations, and in extreme cases loss of consciousness

Repeated or prolonged contact with the preparation may cause Defatting of the skin resulting in non-allergic dermatitis and absorption through the skin.

The liquid splashed in the eyes causes serious eye irritation and damage.

Irritating to mouth, throat and stomach. Ingestion causes reduced fetal weight, increased fetal deaths and skeletal malformations

Formaldehyde is released during curing.

ACUTE TOXICITY:

PRODUCT:	RESULT	SPECIES	DOSE	EXPOSURE
Calcium Carbonate	LD50 ORAL	Rat	6450 mg/kg	-
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 Hours
	LC50 Inhalation Vapor	Rat	8000 ppm	4 Hours
	LD50 Dermal	Rabbit	8.39 g/kg	-
Epoxy Resin with Toluene	LD50 ORAL	Rat	636 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
Carbon Black	LD50 ORAL	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>8000 mg/kg	-

May cause damage to organs through prolonged or repeated exposure.
 Suspected of causing cancer. Risk depends on level and duration of exposure.
 Suspected of damaging the unborn child.

CARCINOGENICITY:

INGREDIENT	IARC	OSHA	NTP	CAS#
TOLUENE :	3	-	-	108-88-3
Carbon Black	2B			1333-86-4

SPECIFIC TARGET ORGAN TOXICITY-STOT (SINGLE EXPOSURE)

LIQUID POLYMER - CATEGORY 3

TOLUENE - CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY-STOT (REPEATED EXPOSURE)

TOLUENE - CATEGORY 2

TARGET ORGANS: BRAIN, BLOOD, KIDNEYS, LUNGS, REPRODUCTIVE SYSTEM, LIVER, HEART, PERIPHERAL NERVOUS SYSTEM, GASTROINTESTINAL TRACT, UPPER RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, EYE, LENS AND/OR CORNEA.

ASPIRATION HAZARD:

TOLUENE - CATEGORY 1

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Toxicity :

Toxicity :

Product / Ingredient	Test / Exposure	Species	Result
Carbon Black	LC50 (96 Hrs.)	Brachydanio Rerio	>1000 mg/L
	EC50 (24 Hrs.)	Daphnia Magna	>5600 mg/L
Toluene	EC50 (48 Hrs.)	Daphnia	3.78 mg/l
	LC50 (96 Hrs.)	Fish	5.5 mg/l

Persistence and Degradability :

Product / Ingredient	Aquatic Half Life	Photolysis	Biodegradability
Toluene	-	-	Readily (5 days - 81 %)
Epoxy Resins with Toluene	-	-	Not Readily Biodegradeable (28 days - 5%)

Bioaccumulative Potential :

Product / Ingredient	LogP(ow)	BCF	Potential
Toluene	2.73	8.32	low
Epoxy Resins with Toluene	-	31	low

Mobility in Soil : Not Available

13. DISPOSAL CONSIDERATIONS

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.

React with curing agent and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

14. TRANSPORT INFORMATION

DOT: Not regulated

UN Number: Not regulated

IATA: Not regulated

IMDG/IMO: Not regulated

NMFC: 4620 SUB.5 – CL.60

Schedule B # 3506.91.0000

15. REGULATORY INFORMATION

US Regulations Federal

chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA)	Chemical Name	CAS No	Weight %	Threshold limit (Reporting Value)
	TOLUENE (Methylbenzene)	108-88-3	<2%	Unknown
	LIQUID POLYMER	N/A	<70%	Unknown
	Calcium Carbonate	471-34-1	<45%	Unknown
	Carbon Black	1333-86-4	<3 %	Unknown

SARA notifications must remain attached to this SDS. Any copies and /or distribution of this SDS must include all SARA notifications.

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

US Regulations State

California Proposition 65 (Developmental – Female)	TOLUENE	108-88-3	<2%	>= 1.0%
Massachusetts	TOLUENE	108-88-3	<2%	>= 1.0%
New Jersey	TOLUENE	108-88-3	<2%	>= 1.0%
Pennsylvania	TOLUENE	108-88-3	<2%	>= 1.0%
Rhode Island	TOLUENE	108-88-3	<2%	>= 1.0%
California Proposition 65 (Developmental – Female)	LIQUID POLYMER	N/A	<70%	>= 1.0%
Massachusetts	LIQUID POLYMER	N/A	<70%	>= 1.0%
New Jersey	LIQUID POLYMER	N/A	<70%	>= 1.0%
Pennsylvania	LIQUID POLYMER	N/A	<70%	>= 1.0%
Rhode Island	LIQUID POLYMER	N/A	<70%	>= 1.0%
California Proposition 65 (Developmental – Female)	Calcium Carbonate	471-34-1	<45%	>= 1.0%
Massachusetts	Calcium Carbonate	471-34-1	<45%	>= 1.0%
New Jersey	Calcium Carbonate	471-34-1	<45%	>= 1.0%
Pennsylvania	Calcium Carbonate	471-34-1	<45%	>= 1.0%
Rhode Island	Calcium Carbonate	471-34-1	<45%	>= 1.0%
California Proposition 65 (Developmental – Female)	Carbon Black	1333-86-4	<3%	>= 1.0%
Massachusetts	Carbon Black	1333-86-4	<3%	>= 1.0%
New Jersey	Carbon Black	1333-86-4	<3%	>= 1.0%
Pennsylvania	Carbon Black	1333-86-4	<3%	>= 1.0%
Rhode Island	Carbon Black	1333-86-4	<3%	>= 1.0%

United States: Sara 302/304 (Sara 304 RQ): Not Applicable

Information On Ingredients: None Were Found

Sara 311/312

Classification: Immediate (acute) Health Hazard, Delayed (chronic) Health Hazard

Information On Ingredients:

Liquid Polymer: Immediate (acute) Health Hazard

Toluene: Fire Hazard, Immediate (acute) Health Hazard, Delayed (chronic) Health Hazard

Epoxy Resin with Toluene : Fire Hazard, Immediate (acute) Health Hazard, Delayed (chronic) Health Hazard

Carbon Black : Chronic Health Hazard, Fire Hazard

Sudden Release Of Pressure: No Products

Reactivity: No Products

California Prop. 65 : Warning

This product contains a chemical or chemicals known by the State of California to cause cancer, birth defects, or other reproductive harm.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

Listed National Pollutant Release Inventory (NPRI):TOLUENE CAS:108-88-3

Calcium Carbonate CAS# 471-34-1

Liquid Polymer cas# N/A

carbon Black Cas# 1333-86-4

16. OTHER INFORMATION

HEALTH	2
FLAMMABILITY	0
REACTIVITY	0

HEALTH	2
FLAMMABILITY	0
REACTIVITY	0

* Customer and / or end user is responsible for determining Personal Protection Equipment

NFPA

HMIS

Preparer:

Flamemaster / Compliance

Revision Date: 08/22/2019

Conversion to ANSI format

Containers:

plastic jars, metal cans
cartridge kits

Limited Quantity

See SDS Section 14

Maximum container size 50 Gallons / 190 Liters

Notice to reader:

This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.

This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.

Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.

End of Safety Data Sheet