



**FLAMEMASTER**  
**Flamemaster Corp.**  
 13576 Desmond Street  
 Pacoima, CA 91331 - USA

**SAFETY DATA SHEET**  
**DECEMBER 28, 2021**

**File: CS3330C.I.AA GSA 7-10**

Access Door Sealant/ Base

**CORROSION INHIBITING**

**Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

1.1. Product Identifier: CS-3330 C.I. PT A Class A BASE (ALL CLASSES)  
 - Product Name: Access Door Sealant / Base compound Part-A /CORROSION INHIBITOR  
 - Product reference: CS-3330 C.I. PT A Class A Base Compound

**1.2. Product Use:**  
 - Access Door Sealant / Base Compound/CORROSION INHIBITOR

**1.3. Manufacturer's Name:**  
**CAGE Code: 14439**  
**Flamemaster Corp.**  
**Chem Seal Division**  
**13576 Desmond Street**  
**Pacoima, CA 91333 – USA**

**1.3.1 Suppliers Name ( if not manufacturer )**

**Technical Contact:**  
**Flamemaster Corp.**  
 Tel: 818-890-1401  
 Fax: 818-890-6001  
[www.flamemaster.com](http://www.flamemaster.com)

**1.4. Emergency Telephone:**  
  
 Emergency Contact Information :  
 See Below

**Specification: AMS 3284 / MIL-S-8784 Base PT A CLA TYPE 2 ALL**

<b>NSN:</b>	8030-00-291-8380	8030-00-264-6583	8030-00-152-0062	8030-00-598-2090	
	CS3330C.I. A1/2 1/2 PT	CS3330C.I. A1/2 PINT	CS3330C.I. A-2 2.5OZ	CS3330C.I.A-2 PINT	

Emergency Contact:  
 CHEMTEL: WWW.CHEMTELINE.COM  
 Flamemaster Corporation Contract Number MIS2644301  
 Shipments of hazardous materials within United States, Canada, Puerto Rico, and U.S. Virgin Island should reference Chemtel's toll free phone number: 1-800-255-3924 - Reference Number MIS2644301  
 Shipments and safety applications outside of United States, Canada, Puerto Rico, and the U.S. Virgin Islands must reference Chemtel phone number +1-813-248-0585 - Reference Number MIS2644301  
 Collect Calls will be accepted. To ensure a bilingual operator please call collect.  
 Shipments originating in U.S.A. and going overseas must use both numbers.  
 Shipments originating overseas and destined for US, Canada, Puerto Rico or the Virgin Islands must also use both numbers.  
 Calls originating on board vessels should follow normal ship to shore protocols. Use international access number and alert the ship to shore operator you are involved in an emergency incident.  
 Shipments of hazardous materials within the listed countries should reference Chemtel's in-country phone numbers:  
 Australia : 1-300-954-583 : Reference Number MIS2644301  
 Brazil : 0-800-591-6042 : Reference Number MIS2644301  
 China : 400-120-0751 : Reference Number MIS2644301  
 India : 000-800-100-4086 : Reference Number MIS2644301  
 Mexico : 01-800-099-0731 : Reference Number MIS2644301

## Section -2. HAZARD ( S ) IDENTIFICATION

OSHA/HCS STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

### CLASSIFICATION OF THE MIXTURE:

ASPIRATION - CATEGORY 1

ACUTE TOXICITY, ORAL - CATEGORY 4

ACUTE TOXICITY (INHALATION) - CATEGORY 4

FLAMMABLE LIQUIDS - Category 2

CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION (UNBORN CHILD) - Category 2

SPECIFIC TARGET ORGAN TOXICITY (STOT RE) (REPEATED EXPOSURE) - Category 2

AQUATIC CHRONIC - Category 4

### GHS LABEL REQUIREMENTS

#### HAZARD PICTOGRAMS



#### SIGNAL WORD : DANGER

#### HAZARD STATEMENTS:

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - (H304)

HARMFUL BY INHALATION AND / OR SWALLOWING - (H302+H332)

HIGHLY FLAMMABLE LIQUID AND VAPOR - (H225)

SUSPECTED OF DAMAGING THE UNBORN CHILD - (H361d)

SUSPECTED OF CAUSING CANCER - (H351)

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE - (H373)

MAY CAUSE LONG LASTING HARMFUL EFFECTS TO AQUATIC LIFE - (H413)

#### PRECAUTIONARY STATEMENTS:

- P101+P102+P103: If medical advice is needed, have product container or label at hand. Keep out of reach of children.
- Read label before use
- P202: Do not handle until all safety precautions have been read and understood
- P210: Keep away from heat/sparks/open flames and hot surfaces-No Smoking
- P240:Ground/bond container and receiving equipment
- P261+P262+P263+P264:Avoid breathing dust/fumes/gas/mist/vapours/spray.Do not get in eyes , on skin, or on clothing. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling.
- P270+P271+P273: Do not eat drink or smoke when using this product. Use only outdoors or in a well ventilated area. Avoid release to the environment.
- P281+P280: Use personal protective equipment as required. Wear protective gloves/ protective clothing/ eye protection/face protection
- P301+P310+P331: If swallowed: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting.
- P305+P351+P338+P315: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,if present and easy to do. Continue rinsing. Get immediate medical advice attention.
- P304+P340+P314: If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell
- P342+P340+P315: If experiencing respiratory symptoms: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice/attention.
- P302+P352: If on skin (or in hair) : Wash with plenty of soap and water. If skin irritation occurs seek medical attention
- P306+P361: If on clothing: Remove/ take off immediately all contaminated clothing
- P402+P403+P404: Store in a dry place. Store in a well ventilated space. Store in a closed container.
- P233+P234+P235: Keep container tightly closed. Keep only in original container. Keep cool.

#### SUPPLEMENTAL LABEL ELEMENTS:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of concentrations above recommended limits causes headaches, drowsiness and nausea and could lead to unconsciousness or possibly death.

1-component mixtures: formaldehyde is released during the curing phase. Formaldehyde may cause irreversible effects, is irritating to the mucous membranes and may cause the skin to become sensitized.

Avoid any contact with skin or clothing and wash thoroughly after handling.

Emits toxic fumes when heated.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

HAZARDS NOT OTHERWISE CLASSIFIED:

Prolonged or repeated exposure may dry skin and / or cause skin irritation.

Sanding and grinding dust may be harmful if inhaled. Sanding and grinding dust may form combustible concentrations in air.

---

---

**Section -3. COMPOSITION / INFORMATION ON INGREDIENTS**

---

---

**Chemical family** : Mixture of organic compounds

For the hazards of the composition, (SDS see Section 2).

---

**GHS CLASSIFICATION: LIQUID POLYSULFIDE POLYMER** // OSHA HAZARDS: TARGET ORGAN EFFECT, IRRITANT, FLAMMABLE LIQUID  
EYE IRRITATION (CATEGORY 2)  
SKIN IRRITATION (CATEGORY 2)  
SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE-(CATEGORY 3)  
AQUATIC, CHRONIC (CATEGORY 3)

**2-BUTANONE**

OSHA HAZARDS: FLAMMABLE LIQUID, TARGET ORGAN EFFECT, IRRITANT

TARGET ORGANS: CENTRAL NERVOUS SYSTEM

GHS CLASSIFICATION: 2-BUTANONE

FLAMMABLE LIQUIDS (CATEGORY 2)

ACUTE TOXICITY, ORAL (CATEGORY 5)

EYE IRRITATION (CATEGORY 2A)

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE (CATEGORY 3), CENTRAL NERVOUS SYSTEM

OTHER HAZARDS: REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS AND CRACKING

**CALCIUM CARBONATE:**

GHS CLASSIFICATION: CALCIUM CARBONATE

EYE DAMAGE (CATEGORY 1)

SKIN IRRITATION (CATEGORY 2)

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE-(CATEGORY 3)

**TITANIUM DIOXIDE**

OSHA HAZARDS: CARCINOGEN

GHS CLASSIFICATION: TITANIUM DIOXIDE

SKIN IRRITATION: (CATEGORY 3)

CARCINOGENICITY (CATEGORY 2)

**LIMESTONE:**

GHS CLASSIFICATION: LIMESTONE

Acute Toxicity : Oral (Category 4)

Skin Corrosion/Irritation - (Category 2)

Eye Damage / Irritation - (Category 2B)

Carcinogenicity (CATEGORY 1A)

Specific Target Organ Toxicity - Repeated Exposure -STOT RE- (Category 1)

Specific Target Organ Toxicity - Single Exposure -STOT SE- (Category 3)

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

SUBSTANCE % by weight in the product	H&P STATEMENTS	CAS	EINECS/ELINCS
LIQUID POLYSULFIDE-POLYMER < 71%	H319,H335,H315,H412,H223, P210,P270,P305+P351+P338 +P313,P306+P361,P370+P260	N/A	POLYMER
2-BUTANONE (MEK) <15%	H225,H303+H333,H319,H336,P210, P261,P305+P351+P338	78-93-3	201-159-0
Titanium Dioxide <3%	H319,H335,H315,H332,H312,H302 H373,P305+P351+P313,P280+ P281,P262,P102,P280	13463-67-7	236-675-5
Calcium Carbonate <35%	H319 P305+P351+P313,P280	72608-12-9	207-439-9
Limestone <15%	H315, H318,H335,H319 P305+P351+P338+P313,P280	1317-65-3	207-439-9

#### Section -4. FIRST-AID MEASURES

**General:** When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

**Inhalation:** Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

Sanding and grinding dust may be harmful if inhaled. Sanding and grinding dust may form combustible concentrations in air.

**Eye contact:** Check for and remove any contact lenses. Irrigate with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek immediate medical attention.

**Skin contact:** Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

**Ingestion:** If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

---



---

#### Section -5. FIRE-FIGHTING MEASURES

##### Extinguishing agents

**Recommended:** Universal resistant foam, CO<sub>2</sub>, water, powder.

**Agents to avoid:** None known

##### Attention

Promptly remove all persons in the event of a fire from the fire area. If safe to do so, remove all containers from fire area as well.

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Do not allow run-off from fire fighting to enter drains or water courses.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

**HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE:** CARBON DIOXIDE, CARBON MONOXIDE, NITROGEN OXIDES, SULFUR OXIDES HALOGENATED COMPOUNDS, METAL OXIDE / OXIDES, AND FORMALDEHYDE

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

## Section -6. ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

## Section -7. HANDLING AND STORAGE

### 7.1 Handling:

No smoking, eating and drinking during handling.

Avoid exposure during pregnancy/while nursing.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

### 7.2 Storage:

Observe label precautions. Store between 32/F and 95/F ( 0/C and 35/C ) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Engineering measures:

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

### 8.2 Exposure limits

Work place exposure limits ( 8 hour )

Substance	OSHA	ACGIH TWA
ALIPHATIC POLYSULFIDE-POLYMER	Not known	Not known
2-BUTANONE (MEK) *	200 ppm	200 ppm
CALCIUM CARBONATE *	5 mg/m <sup>3</sup> ( RESPIRABLE FRACTION)	3 mg/m <sup>3</sup> (RESPIRABLE FRACTION)
CALCIUM CARBONATE *	15mg/m <sup>3</sup> (TOTAL DUST)	10 mg/m <sup>3</sup> (TOTAL DUST)
TITANIUM DIOXIDE *	15mg/m <sup>3</sup> (TOTAL DUST)	10 mg/m <sup>3</sup> (TOTAL DUST)
LIMESTONE *	5 mg/m <sup>3</sup> ( RESPIRABLE FRACTION)	Not known
	15mg/m <sup>3</sup> (TOTAL DUST)	Not known
* can be absorbed through skin		

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

### 8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

#### Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

#### Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

#### Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

#### Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

---

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

---

- |   |  |
|---|--|
| • Physical state at: 68 ° F (20 ° C) Liquid                   | • Ph : 8.5                                   |
| • Flash point: 72 ° F (22.22 ° C) Method: TCC                 | • Volatile by Volume % : 15                  |
| • Specific gravity at: 68 ° F (20 ° C) 1.55 g/cm <sup>3</sup> | • Vapor pressure at: 68 ° F (20 ° C) 2 mm Hg |
| • Vapor Density: N/A  | • Color: Red                                 |
| • Lower Explosive Limit (% vol.): 1.3                         | • Appearance: Paste                          |
| • Upper Explosive Limit (% vol.): 7.1                         | • Odor: Polysulfide Odor                     |
| • Miscibility in water at 20 ° C: Negligible                  | • Boiling Point: >100 ° F                    |
| • VOC : 218 g/l   | • Material Supports Combustion : Yes         |

---

---

## 10. STABILITY AND REACTIVITY

---

---

Stable under recommended storage and handling conditions (see SDS section 7). In case of combustion, may produce hazardous decomposition products such as :

- |                   |  |
|-------------------|--|
| • Carbon Monoxide | • Halogenated Compounds  |
| • Sulfur Oxides   | • Oxides of Carbon, Nitrogen, Sulfur Dioxide, Trace Hydrogen Sulfide |
| • Carbon Dioxide  | • Metal Oxide / Oxides   |
| • Formaldehyde    | • Smoke  |

---

---

## 11. TOXICOLOGICAL INFORMATION

---

---

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs of overexposure include headache, dizziness, fatigue, muscular weakness, drowsiness, reduced fetal weight, increase in fetal deaths, skeletal malformations, and in extreme cases loss of consciousness

Repeated or prolonged contact with the preparation may cause Defatting of the skin resulting in non-allergic dermatitis and absorption through the skin.

The liquid splashed in the eyes causes serious eye irritation and damage.

Irritating to mouth, throat and stomach. Ingestion causes reduced fetal weight, increased fetal deaths and skeletal malformations

**ACUTE TOXICITY:**

PRODUCT:	RESULT	SPECIES	DOSE	EXPOSURE
Calcium Carbonate	LD50 ORAL	Rat	6450 mg/kg	-
Butanone	LC50 Inhalation Vapor	Rat	11243 ppm	4 Hours
	LD50 Dermal	Rabbit	6480 mg/kg	-
	LD50 ORAL	Rat	2737 mg/kg	-
Titanium Dioxide	LD50 ORAL	Rat	>10g/kg	-

May cause damage to organs through prolonged or repeated exposure.

Suspected of causing cancer. Risk depends on level and duration of exposure.

Suspected of damaging the unborn child.

**CARCINOGENICITY:**

INGREDIENT	IARC	OSHA	NTP	CAS#
TITANIUM DIOXIDE :	2B	-	-	13463-67-7

**SPECIFIC TARGET ORGAN TOXICITY-STOT (SINGLE EXPOSURE)**

BUTANONE - CATEGORY 3

LIQUID POLYMER - CATEGORY 3

LIQUID POLYMER - CATEGORY 3

**TARGET ORGANS:** BRAIN, BLOOD, KIDNEYS, LUNGS, REPRODUCTIVE SYSTEM, LIVER, HEART, PERIPHERAL NERVOUS SYSTEM, GASTROINTESTINAL TRACT, UPPER RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, EYE, LENS AND/OR CORNEA.

**12. ECOLOGICAL INFORMATION**

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Toxicity :

Product / Ingredient	Result	Species	Exposure
Titanium Dioxide	Acute LC50>100mg/l Fresh Water	Daphnia	48 Hours

Bioaccumulative Potential :

Product / Ingredient	LogP(ow)	BCF	Potential
Butanone	.29	-	low

**Mobility in Soil :** Not Available

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

**13. DISPOSAL CONSIDERATIONS**

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.  
 React with curing agent and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.  
 Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

**14. TRANSPORT INFORMATION**

DOT: § 172.101 HAZARDOUS MATERIALS TABLE  
 UN Number: 1133  
 Proper Shipping Name: Adhesives  
 Labels: Flammable Liquid



IATA:  
 UN Number: 1133  
 Proper Shipping Name: Adhesives  
 Labels: Flammable Liquid  
  
 Hazard Class: 3 Subclass: NO  
 Packaging Group: III  
 Passenger Air Packing Instruction : 309  
 Passenger aircraft: 60 Liter (16 gallon)  
 Cargo Air Packing Instruction : 310  
 Cargo aircraft only: 220 Liter (58 gallon)

Hazard Class: 3 Subclass: NO  
 Packaging Group: III  
 Limited Quantity: Passenger aircraft: 60 Liter (16 gallon)  
 Cargo aircraft only: 220 Liter (58 gallon)  
 Vessel stowage: A  
 ERG: 128  
 NMFC: 4620 SUB.6 – CL.60  
 Schedule B # 3506.91.0000

IMDG:  
 UN Number: 1133  
 Proper Shipping Name: Adhesives  
 Label: 3  
 Hazard Class: 3 Subclass: NO  
 Packaging Group: III  
 EMS No: F, E – S, D

**15. REGULATORY INFORMATION**

**US Regulations Federal**

chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA)	Chemical Name	CAS No	Weight %	Threshold limit (Reporting Value)
	LIQUID POLYMER	N/A	50%-71%	Unknown
	2-BUTANONE	78-93-3	<15%	Unknown
	Calcium Carbonate	72608-12-9	<35%	Unknown
	LIMESTONE	1317-65-3	<15%	Unknown
	Titanium Dioxide	*13463-67-7	< 3%	Unknown
	*(DELETED CAS# 98084-96-9)			

SARA notifications must remain attached to this SDS. Any copies and /or distribution of this SDS must include all SARA notifications.

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.



**US Regulations State**

California Proposition 65 (Developmental – Female)	LIQUID POLYMER	N/A	50%-71%	>=1.0%
Massachusetts	LIQUID POLYMER	N/A	50%-71%	>=1.0%
New Jersey	LIQUID POLYMER	N/A	50%-71%	>=1.0%
Pennsylvania	LIQUID POLYMER	N/A	50%-71%	>=1.0%
Rhode Island	LIQUID POLYMER	N/A	50%-71%	>=1.0%
California Proposition 65 (Developmental – Female)	2-BUTANONE	78-93-3	<15%	>=1.0%
Massachusetts	2-BUTANONE	78-93-3	<15%	>=1.0%
New Jersey	2-BUTANONE	78-93-3	<15%	>=1.0%
Pennsylvania	2-BUTANONE	78-93-3	<15%	>=1.0%
Rhode Island	2-BUTANONE	78-93-3	<15%	>=1.0%
California Proposition 65 (Developmental – Female)	Calcium Carbonate	72608-12-9	<35%	>=1.0%
Massachusetts	Calcium Carbonate	72608-12-9	<35%	>=1.0%
New Jersey	Calcium Carbonate	72608-12-9	<35%	>=1.0%
Pennsylvania	Calcium Carbonate	72608-12-9	<35%	>=1.0%
Rhode Island	Calcium Carbonate	72608-12-9	<35%	>=1.0%
California Proposition 65 (Developmental – Female)	Titanium Dioxide	13463-67-7	<3%	>=1.0%
Massachusetts	Titanium Dioxide	13463-67-7	<3%	>=1.0%
New Jersey	Titanium Dioxide	13463-67-7	<3%	>=1.0%
Pennsylvania	Titanium Dioxide	13463-67-7	<3%	>=1.0%
Rhode Island	Titanium Dioxide	13463-67-7	<3%	>=1.0%
California Proposition 65 (Developmental – Female)	Limestone	1317-65-3	<15%	>=1.0%
Massachusetts	Limestone	1317-65-3	<15%	>=1.0%
New Jersey	Limestone	1317-65-3	<15%	>=1.0%
Pennsylvania	Limestone	1317-65-3	<15%	>=1.0%
Rhode Island	Limestone	1317-65-3	<15%	>=1.0%

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

**United States:** Sara 302/304 (Sara 304 RQ): Not Applicable

Information On Ingredients: None Were Found

Sara 311/312

Classification: Fire Hazard, Immediate (acute) Health Hazard, Delayed (chronic) Health Hazard

**Information On Ingredients:**

**Butanone:** Fire Hazard, Immediate (acute) Health Hazard

**Polysulfide Polymer:** Immediate (acute) Health Hazard

**Titanium Dioxide:** Delayed (chronic) Health Hazard

**Sudden Release Of Pressure:** No Products

**Reactivity:** No Products

Sara 313 Notification: \*

Barium bis[2-[(2-hydroxynaphthyl)azo] naphthalenesulphonate	CAS #1103-38-4	Percentage of Mixture - < 2%
--	----------------	------------------------------

\* Do not detach SARA 313 notifications from SDS. All copies of SDS must include SARA 313 notifications.

**California Prop. 65 : Warning**

This product contains a chemical or chemicals known by the State of California to cause cancer, birth defects or other reproductive harm.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

Listed National Pollutant Release Inventory (NPRI):TOLUENE CAS:108-88-3

2-BUTANONE CAS#78-93-3

Liquid Polysulfide Polymer cas# N/A

Calcium Carbonate CAS#72608-12-9

Titanium Dioxide CAS#13463-67-7

Limestone CAS# 1317-65-3

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

---

---

**16. OTHER INFORMATION**

---

---

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PPE	H

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PPE	H

Customer and / or end user is responsible for determining PPE.

**NFPA****HMIS**

Preparer:

Flamemaster / Compliance  
Rev-A 4/20/2015  
Supersedes (conversion)

Revision Date : 12/28/2021

Conversion to ANSI format

Containers:

plastic jars, metal cans  
cartridge kits

Limited Quantity

See SDS Section 14

Maximum container size 50 Gallons / 190 Liters

**Notice to reader:**

This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.

This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.

Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.

**End of Safety Data Sheet**

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.