



FLAMEMASTERR
Flamemaster Corp.
13576 Desmond Street
Pacoima, CA 91331 - USA

SAFETY DATA SHEET
FEBRUARY 03, 2020

File: CS3808AA GSA 07-10
Silicone Base

Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1. Product Identifier: CS-3808 Part-A Class-A Base (all application times)
 - Product Name: Room Temperature Silicone Base compound Part-A
 - Product reference: CS-3808-CLASS A ALL

1.2. Product Use:

-Room Temperature Silicone

1.3. Manufacturer's Name:

CAGE Code: 14439
Flamemaster Corp.
Chem Seal Division
13576 Desmond Street
Pacoima, CA 91333 – USA

1.3.1 Suppliers Name (if not manufacturer)

Technical Contact:

Flamemaster Corp.
 Tel: 818-890-1401
 Fax: 818-890-6001
www.flamemaster.com

1.4. Emergency Telephone:

Emergency Contact Information :
 See Below

Specification: BMS-8-68 MMS-M138 BASE PART A CLASS A ALL

NSN:	5970-01-084-4932 CS3808 A2 GALLON			
-------------	--------------------------------------	--	--	--

Section -2. HAZARD (S) IDENTIFICATION

Emergency Contact:

CHEMTEL: WWW.CHEMTELINC.COM

Flamemaster Corporation Contract Number MIS2644301

Shipments of hazardous materials within United States, Canada, Puerto Rico, and U.S. Virgin Island should reference Chemtel's toll free phone number: 1-800-255-3924 - Reference Number MIS2644301

Shipments and safety applications outside of United States, Canada, Puerto Rico, and the U.S. Virgin Islands must reference Chemtel phone number +1-813-248-0585 - Reference Number MIS2644301

Collect Calls will be accepted. To ensure a bilingual operator please call collect.

Shipments originating in U.S.A. and going overseas must use both numbers.

Shipments originating overseas and destined for US, Canada, Puerto Rico or the Virgin Islands must also use both numbers.

Calls originating on board vessels should follow normal ship to shore protocols. Use international access number and alert the ship to shore operator you are involved in an emergency incident.

Shipments of hazardous materials within the listed countries should reference Chemtel's in-country phone numbers:

Australia : 1-300-954-583 : Reference Number MIS2644301

Brazil : 0-800-591-6042 : Reference Number MIS2644301

China : 400-120-0751 : Reference Number MIS2644301

India : 000-800-100-4086 : Reference Number MIS2644301

Mexico : 01-800-099-0731 : Reference Number MIS2644301

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

OSHA/HCS STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

CLASSIFICATION OF THE MIXTURE:

ASPIRATION HAZARD - (CATEGORY 1)

ACUTE TOXICITY, ORAL - CATEGORY 4

CAUSES SERIOUS EYE IRRITATION - H319

TOXIC TO REPRODUCTION - CATEGORY 2

CARCINOGEN- CATEGORY 1A

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

TOXIC TO AQUATIC LIFE - CATEGORY 4

GHS LABEL REQUIREMENTS

HAZARD PICTOGRAMS



SIGNAL WORD : DANGER

HAZARD STATEMENTS:

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - (H304)

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD - H361

CAUSES SERIOUS EYE IRRITATION - H319

MAY CAUSE CANCER - (H350)

CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE - H372

MAY CAUSE LONG LASTING HARMFUL EFFECTS TO AQUATIC LIFE - H413

HARMFUL IF SWALLOWED - H302

SUPPLEMENTAL LABEL ELEMENTS:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of concentrations above recommended limits causes headaches, drowsiness and nausea and could lead to unconsciousness or possibly death.

Avoid any contact with skin or clothing and wash thoroughly after handling.

Emits toxic fumes when heated.

Sanding and grinding dust may be harmful if inhaled.

HAZARDS NOT OTHERWISE CLASSIFIED:

Prolonged or repeated exposure may dry skin and / or cause skin irritation.

In the event of sanding, grinding, or abrading:

H372 Causes damage to organs through prolonged or repeated exposure.

GENERAL PRECAUTIONARY STATEMENTS:

P101: If medical advice is needed, have product container or label at hand.

P102: keep out of reach of children.

P103: Read label before use.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

SPECIFIC PRECAUTIONARY STATEMENTS ASSOCIATED WITH THIS PRODUCT:

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P260: Do not breathe dust / fumes / gas / mist / vapors / spray.
- P264: Wash thoroughly after handling.
- P270: Do not eat, drink, or smoke when using this product.
- P273: Avoid release to the environment.
- P280: Wear protective gloves / protective clothing / eye protection / face protection.
- P281: Use personal protection equipment as required.
- P301+310: IF SWALLOWED: Immediately call a POISON CENTER / doctor / ...
- P301+312: IF SWALLOWED: Call a POISON CENTER / doctor / .../ if you feel unwell.
- P305+351+338: IF IN EYES: Rinse cautiously for several minutes. Remove contact lenses if present and easy to do-continue rinsing.
- P308+313: If exposed: Call a POISON CENTER or doctor / physician.
- P314: Get medical advise / attention if you feel unwell.
- P330: Rinse mouth
- P331: Do NOT induce vomiting.
- P337+313: If eye irritation persists: Get medical advice / attention.
- P405: Store locked up.
- P501: Dispose of contents / containers in accordance with local / regional / national / international regulations

Section -3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical family : Mixture of organic compounds

HAZARDOUS INGREDIENTS	% By WEIGHT	CAS NUMBER
Polysilicic Acid, Ethyl Ester	<10%	11099-06-2
Octamethylcyclotetrasiloxane	.1-1%	556-67-2
Crystalline Silica	<40%	14808-60-7

Section -4. FIRST-AID MEASURES

General: When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

Eye contact: Irrigate with clean, fresh water for at least 15 minutes, holding the eyelids apart, and seek medical attention.

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products. If skin irritation/sensitization occurs seek medical attention.

Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

Section -5. FIRE-FIGHTING MEASURES

Extinguishing agents

Recommended: Universal resistant foam, CO₂, water, powder.

Agents to avoid: None known

Attention

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Do not allow run-off from fire fighting to enter drains or water courses.

Emits toxic fumes when heated.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE: Carbon Monoxide, Carbon Dioxide (CO₂), Formaldehyde (from oxidative degradation), Sulfur Oxides, Oxides of Carbon, Silicone Dioxide, Ethanol. Silica when exposed to hydrofluoric acid will dissolve and produce a corrosive gas, silicone tetrafluoride.

Section -6. ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

Section -7. HANDLING AND STORAGE

7.1 Handling:

No smoking, eating and drinking during handling.

Avoid exposure during pregnancy/while nursing.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

7.2 Storage:

Observe label precautions. Store at 50° F max. in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Engineering measures:

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

8.2 Exposure limits

Work place exposure limits (8 hour)

Substance	OSHA	ACGIH TLV
SILICA (CRYSTALLINE)	0.1mg m ³	0.025 mg m ³ TWA
KROMA RED IRON OXIDE	10 mg/m ³ (fume)	5 mg/m ³ (respirable faction)
	15 mg/m ³ (total dust)	
	5 mg/m ³ (respirable faction)	

8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state at: 68 ° F (20 ° C) Liquid
- Flash point: 200 ° F (93 ° C) Method: TCC
- Specific gravity at: 68 ° F (20 ° C) N/A
- Vapor Density: N/A
- Lower Explosive Limit (% vol.): N/A
- Upper Explosive Limit (% vol.): N/A
- Miscibility in water at 20 ° C: NEGLIGIBLE
- Ph : N/A
- Volatile by VOLUME: N/A
- Vapor pressure at: 68 ° F (20 ° C) N/A
- Color: RED PASTE
- Appearance: PASTE
- Odor: SLIGHT ODOR
- Boiling Point: N/A

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see SDS section 7). In case of combustion, may produce hazardous decomposition products such as :

- Carbon monoxide
- Sulfur oxides
- OXIDES OF CARBON, SILICONE DIOXIDE, ETHANOL, OTHER TOXIC FUMES
- Formaldehyde
- Carbon Dioxide

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

Avoid contact with powerful oxidizing agents, such as fluorine, chlorine trifluoride, and oxygen difluoride. Which may cause fires.

Silica when exposed to hydrofluoric acid will dissolve and produce a corrosive gas, silicone tetrafluoride.

11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health

SPECIFIC TARGET ORGAN TOXICITY-STOT (SINGLE EXPOSURE)

Polysilicic Acid, Ethyl Ester Category 3 Respiratory Tract Irritation

SPECIFIC TARGET ORGAN TOXICITY-STOT (REPEATED EXPOSURE)

Silica (Crystalline Quartz) Category 1

CARCINOGEN

INGREDIENT	IARC	OSHA	NTP	CAS#
Silica (Crystalline Quartz)	1A			14808-60-7

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

See sections 3 and 5

13. DISPOSAL CONSIDERATIONS

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.

React with curing agent and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

14. TRANSPORT INFORMATION

DOT: Not regulated

UN Number: Not regulated

IATA: Not regulated

IMDG/IMO: Not regulated

NMFC: 4620 SUB.6 – CL.60

Schedule B # 3506.91.0000

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

15. REGULATORY INFORMATION

US Regulations Federal

chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA) SILICA (CRYSTALLINE)	Chemical Name	CAS No	Weight %	Threshold limit
	SILICA	14808-60-7	<40%	Unknown

SARA 311/312

Silicone Elastomer - Delayed (chronic) Health Hazard

Octamethylcyclotetrasiloxane - Fire Hazard - Chronic Health Hazard

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

US Regulations State

STATE	PRODUCT	CAS#	%WT
California Proposition 65 (Developmental – Female)	QUARTZ	14808-60-7	<40%
Massachusetts	QUARTZ	14808-60-7	<40%
New Jersey	QUARTZ	14808-60-7	<40%
Pennsylvania	QUARTZ	14808-60-7	<40%
Rhode Island	QUARTZ	14808-60-7	<40%
Texas	QUARTZ	14808-60-7	<40%
Pennsylvania	Octamethylcyclotetrasiloxane	556-67-2	.1-1%
Massachusetts	Octamethylcyclotetrasiloxane	556-67-2	.1-1%
New Jersey	Octamethylcyclotetrasiloxane	556-67-2	.1-1%

California Prop 65 Warning :

This product contains one or more ingredients known by the state of California to cause cancer, birth defects, or other reproductive harm.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the sds contains all of the information required by CPR. Listed National Pollutant Release Inventory (NPRI):

Silica Cas#14808-60-7, octamethylcyclotetrasiloxane cas#556-67-2 and polysilicicacid ethyl ester cas#11099-06-2

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

16. OTHER INFORMATION

HEALTH-1 *
FLAMMABILITY-0
REACTIVITY-0
CHRONIC *

* Customer and / or end user is responsible
for determining Personal Protection Equipment

HMIS

Preparer-Flamemaster/Compliance

Revision Date: 02/03/2020

Containers: Plastic Jars, Metal Cans, Cartridge Kits

Maximum Container Size: 50 Gallons/190 Liters

Notice to reader:

This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.

This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.

Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.

End of Safety Data Sheet