

**Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

1.1. Product Identifier: E-400 Moldable / Pourable Epoxy Polyamide Compound (Part A)  
 - Product Name: E-400 Moldable / Pourable- Low Density Epoxy Polyamide Compound / Part A  
 - Product reference: E-400 Moldable / Pourable Compound (Part A) Base

**1.2. Product Use:**  
 - Low Density Epoxy Polyamide Compound

**1.3. Manufacturer's Name:**  
**CAGE Code: 14439**  
 Flamemaster Corp.  
 Chem Seal Division  
 13576 Desmond Street  
 Pacoima, CA 91333 – USA

**1.3.1 Suppliers Name ( if not manufacturer )**

**Technical Contact:**  
 Flamemaster Corp.  
 Tel: 818-890-1401  
 Fax: 818-890-6001  
[www.flamemaster.com](http://www.flamemaster.com)

**1.4. Emergency Telephone:**  
  
 Emergency Contact Information :  
 See Below

<b>Specification: AS1129 EPOXY POLYAMIDE COMPOUND PART A</b>	
<b>NSN:</b>	8030-01-067-7587 E-400P Moldable Putty Pint Kit

**Emergency Contact:**  
**CHEMTEL: WWW.CHEMTELINE.COM**  
**Flamemaster Corporation Contract Number MIS2644301**  
 Shipments of hazardous materials within United States, Canada, Puerto Rico, and U.S. Virgin Island should reference Chemtel's toll free phone number: 1-800-255-3924 - Reference Number MIS2644301  
 Shipments and safety applications outside of United States, Canada, Puerto Rico, and the U.S. Virgin Islands must reference Chemtel phone number +1-813-248-0585 - Reference Number MIS2644301  
 Collect Calls will be accepted. To ensure a bilingual operator please call collect.  
 Shipments originating in U.S.A. and going overseas must use both numbers.  
 Shipments originating overseas and destined for US, Canada, Puerto Rico or the Virgin Islands must also use both numbers.  
 Calls originating on board vessels should follow normal ship to shore protocols. Use international access number and alert the ship to shore operator you are involved in an emergency incident.  
 Shipments of hazardous materials within the listed countries should reference Chemtel's in-country phone numbers:  
 Australia : 1-300-954-583 : Reference Number MIS2644301  
 Brazil : 0-800-591-6042 : Reference Number MIS2644301  
 China : 400-120-0751 : Reference Number MIS2644301  
 Reference Number MIS2644301  
 Reference Number MIS2644301

Section -2. HAZARD ( S ) IDENTIFICATION

**OSHA/HCS STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

**CLASSIFICATION OF THE MIXTURE:**

FLAMMABLE LIQUIDS - CATEGORY 4  
ASPIRATION HAZARD - CATEGORY 1  
ACUTE TOXICITY, ORAL - CATEGORY 4  
ACUTE TOXICITY (INHALATION) - CATEGORY 4  
CARCINOGENICITY - Category 2  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2  
SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE - (RESPIRATORY TRACT IRRITATION) - CATEGORY 3  
SKIN SENSITIZATION - CATEGORY 1  
GERM CELL MUTAGENICITY-CATEGORY 2  
TOXIC TO REPRODUCTION - CATEGORY 2  
SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE - (NARCOTIC EFFECTS) - CATEGORY 3  
SPECIFIC TARGET ORGAN TOXICITY-REPEAT EXPOSURE -CATEGORY 2  
REPRODUCTIVE TOXICITY, EFFECTS ON OR VIA LACTATION  
AQUATIC (CHRONIC) - CATEGORY 3

**GHS LABEL REQUIREMENTS:**

**HAZARD PICTOGRAMS:**



**SIGNAL WORD : DANGER**

**HAZARD STATEMENTS:**

COMBUSTIBLE LIQUID - H227  
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - H304  
HARMFUL IF SWALLOWED - H302  
HARMFUL IF INHALED - H332  
SUSPECTED OF CAUSING CANCER - H351  
CAUSES SKIN IRRITATION - H315  
CAUSES SERIOUS EYE IRRITATION - H319  
MAY CAUSE RESPIRATORY IRRITATION - H335  
MAY CAUSE AN ALLERGIC SKIN REACTION - H317  
SUSPECTED OF CAUSING GENETIC DEFECTS - H341  
SUSPECTED OF DAMAGING FERTILITY. SUSPECTED OF DAMAGING THE UNBORN CHILD - H361fd  
MAY CAUSE DROWSINESS OR DIZZINESS - H336  
MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE - H373  
MAY CAUSE HARM TO BREAST-FED CHILDREN - H362  
MAY CAUSE LONG LASTING HARMFUL EFFECTS TO AQUATIC LIFE - H412

**In the event of sanding, grinding, or abrading:**

H372 Causes damage to organs through prolonged or repeated exposure.

**Hazards Not Otherwise Classified (HNOC):**

Sanding and grinding dust may be harmful if inhaled. Sanding and grinding dust may form combustible concentrations in air.  
Emits toxic fumes when heated.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

**GENERAL PRECAUTIONARY STATEMENTS:**

P101: If medical advise is needed, have product container or label at hand.  
P102: keep out of reach of children.  
P103: Read label before use.

**SPECIFIC PRECAUTIONARY STATEMENTS ASSOCIATED WITH THIS PRODUCT:**

P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking  
P260: Do not breathe dust / fumes / gas / mist / vapors / spray.  
P261: Avoid breathing dust / fumes / gas / mist / vapors / spray.  
P263: Avoid contact during pregnancy / while nursing.  
P264: Wash thoroughly after handling.  
P270: Do not eat, drink, or smoke when using this product.  
P271: Use only outdoors or in a well - ventilated area.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P273: Avoid release to the environment.  
P280: Wear protective gloves / protective clothing / eye protection / face protection.  
P281: Use personal protection equipment as required.  
P301+310: IF SWALLOWED: Immediately call a POISON CENTER / doctor / ...  
P301+312: IF SWALLOWED: Call a POISON CENTER / doctor / .../ if you feel unwell.  
P302+352: IF ON SKIN: Wash with plenty of water / ...  
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+351+338: IF IN EYES: Rinse cautiously for several minutes. Remove contact lenses if present and easy to do-continue rinsing.  
P308+313: If exposed: Call a POISON CENTER or doctor / physician.  
P312: Call a POISON CENTER / doctor /... / if you feel unwell.  
P314: Get medical advise / attention if you feel unwell.  
P321: Specific treatment...See Label Information  
P330: Rinse mouth  
P331: Do NOT induce vomiting.  
P332+313: If skin irritation occurs: Get medical advice / attention.  
P333+313: If skin irritation or a rash occurs: Get medical advice / attention.  
P337+313: If eye irritation persists: Get medical advice / attention.  
P362: Take off all contaminated clothing.  
P363: Wash contaminated clothing before reuse.  
P370+378: In case of fire: Use ... to extinguish.  
P391: Collect spillage.  
P403+233: Store in a well ventilated place. Keep container tightly closed.  
P403+235: Store in a well ventilated place. Keep cool.  
P405: Store locked up.  
P501: Dispose of contents / containers in accordance with local / regional / national / international regulations

**SUPPLEMENTAL LABEL ELEMENTS:**

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of concentrations above recommended limits causes headaches, drowsiness and nausea and could lead to unconsciousness or possibly death.  
irritating to the mucous membranes and may cause the skin to become sensitized.  
Avoid any contact with skin or clothing and wash thoroughly after handling.  
Emits toxic fumes when heated.

**HAZARDS NOT OTHERWISE CLASSIFIED:**

Prolonged or repeated exposure may dry skin and / or cause skin irritation.  
Sanding and grinding dust may be harmful if inhaled. Sanding and grinding dust may form combustible concentrations in air.

**In the event of sanding, grinding, or abrading:**

H372 Causes damage to organs through prolonged or repeated exposure.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

---

---

**Section -3. COMPOSITION / INFORMATION ON INGREDIENTS**

---

---

**Chemical family** : Mixture of organic compounds

For the hazards of the composition, (SDS see Section 2).

---

<b>% BY WEIGHT IN PRODUCT-</b>	<b>HAZARDOUS INGREDIENT</b>	<b>CAS#-</b>
<50%	Bisphenol A Epoxy Resin	25068-38-6
CAUSES SKIN IRRITATION - H315		
MAY CAUSE AN ALLERGIC SKIN REACTION - H317		
CAUSES SERIOUS EYE IRRITATION - H319		
SUSPECTED OF CAUSING GENETIC DEFECTS - H341		
SUSPECTED OF CAUSING CANCER - H351		
TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS - H411		

<b>% BY WEIGHT IN PRODUCT-</b>	<b>HAZARDOUS INGREDIENT</b>	<b>CAS#-</b>
<10%	Butyl Glycidyl Ether	2426-08-6
FLAMMABLE LIQUID AND VAPOR - H226		
HARMFUL IF SWALLOWED - H302		
HARMFUL IF INHALED - H332		
CAUSES SKIN IRRITATION - H315		
MAY CAUSE AN ALLERGIC SKIN REACTION - H317		
CAUSES SERIOUS EYE IRRITATION - H319		
MAY CAUSE RESPIRATORY IRRITATION - H335		
SUSPECTED OF CAUSING GENETIC DEFECTS - H341		
SUSPECTED OF CAUSING CANCER - H351		
CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE - H372		
HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS - H412		

**Section -4. FIRST-AID MEASURES**

**General:** When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

**Inhalation:** Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

**Eye contact:** Check for and remove any contact lenses. Irrigate with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek immediate medical attention.

**Skin contact:** Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

**Ingestion:** If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

---

---

**Section -5. FIRE-FIGHTING MEASURES**

---

---

**Extinguishing agents**

**Recommended:** Universal resistant foam, CO<sub>2</sub>, water, powder.

**Agents to avoid:** None known

**Attention**

Promptly remove all persons in the event of a fire from the fire area. If safe to do so, remove all containers from fire area as well.

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Do not allow run-off from fire fighting to enter drains or water courses.

Emits toxic fumes when heated.

**HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE BUT MAY NOT BE LIMITED TO THE FOLLOWING:**

- Carbon Dioxide
- Carbon Monoxide
- Halogenated Compounds
- Airborne Solids
- Sulfur Oxides
- Nitrogen Oxides
- Nitrogen Oxides can react with water vapors to form corrosive nitric acid
- Unidentified Organic Compounds
- Toxic Fumes
- Smoke
- Phenolic Compounds
- Other Hazardous Materials

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

---

---

**Section -6. ACCIDENTAL RELEASE MEASURES**

---

---

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

---

---

**Section -7. HANDLING AND STORAGE**

---

---

**7.1 Handling:**

No smoking, eating and drinking during handling.

Avoid exposure during pregnancy/while nursing.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

---

**7.2 Storage:**

Observe label precautions. Store between 32/F and 95/F ( 0/C and 35/C ) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

---

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

---

**8.1 Engineering measures:**

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

---

**8.2 Exposure limits**

---

**Work place exposure limits ( 8 hour )**

---

OSHA	PRODUCT	ACGIH
50 ppm 8 Hours	Butyl Glycidyl Ether	3 ppm 8 hours
15mg/m <sup>3</sup> (TWA)	Aluminum Oxide	TWA: 1mg/m <sup>3</sup> (Respirable Fraction)
15mg/m <sup>3</sup> (TWA)	Titanium Dioxide	10 mg/m <sup>3</sup> (TWA)
15mg/m <sup>3</sup> (TWA) TOTAL DUST 5 mg/m <sup>3</sup> RESPIRABLE	Silica	10 mg/m <sup>3</sup> TWA INHALABLE 3 mg/m <sup>3</sup> (RESPIRABLE) TWA
0.8mg/m <sup>3</sup> TWA	Amorphous Silica	N/A

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

### 8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

#### Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

#### Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

#### Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

#### Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

---

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

---

- |   |  |
|---|--|
| <ul style="list-style-type: none"><li>• Physical state at: 68 ° F (20 ° C) Liquid</li><li>• Flash point: &gt;79 ° C --- &gt;173 Deg. F Method: TCC</li><li>• Specific gravity at: 68 ° F (20 ° C) 1.48 g/cm<sup>3</sup></li><li>• Vapor Density: &lt; 1</li><li>• Lower Explosive Limit-None</li><li>• Upper Explosive Limit-None</li><li>• Miscibility in water at 20 ° C: Insoluble</li></ul> | <ul style="list-style-type: none"><li>• Ph : 8.5</li><li>• Volatile % by volume: 0.90 %</li><li>• Vapor pressure at: 68 ° F (20 ° C) N/A</li><li>• Color: White /Off White</li><li>• Appearance: Viscous Fluid</li><li>• Odor: Sweet Aromatic Odor</li><li>• Boiling Point: &gt;200 Deg. F</li></ul> |
|---|--|

---

---

## 10. STABILITY AND REACTIVITY

---

---

Stable under recommended storage and handling conditions (see SDS section 7). In case of combustion, may produce hazardous decomposition products such as :

HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE BUT MAY NOT BE LIMITED TO THE FOLLOWING:

- |  |  |
|--|--|
| <ul style="list-style-type: none"><li>• Carbon Dioxide</li><li>• Carbon Monoxide</li><li>• Halogenated Compounds</li><li>• Airborne Solids</li><li>• Sulfur Oxides</li><li>• Nitrogen Oxides</li><li>• Nitrogen Oxides can react with water vapors to form corrosive nitric acid</li></ul> | <ul style="list-style-type: none"><li>• Unidentified Organic Compounds<ul style="list-style-type: none"><li>• Toxic Fumes</li></ul></li><li>• Smoke</li><li>• Phenolic Compounds</li><li>• Other Hazardous Materials</li></ul> |
|--|--|

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

**11. TOXICOLOGICAL INFORMATION**

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs of overexposure include headache, dizziness, fatigue, muscular weakness, drowsiness, reduced fetal weight, increase in fetal deaths, skeletal malformations, and in extreme cases loss of consciousness. Repeated or prolonged contact with the preparation may cause Defatting of the skin resulting in non-allergic dermatitis and absorption through the skin.

The liquid splashed in the eyes causes serious eye irritation and damage.

Irritating to mouth, throat and stomach. Ingestion causes reduced fetal weight, increased fetal deaths and skeletal malformations

**ACUTE TOXICITY:**

ENDPOINT	SPECIES	PRODUCT	DOSE	EXPOSURE
		<b>Bisphenol A Epoxy Resin</b>		
LC50 Inhalation Vapor	Rat		.00001 ppm	-
LD50 Dermal	Rat		>2,000 mg/kg	-
LD50 ORAL	Rat		>2,000 mg/kg	-

**CORROSION / IRRITATION**

PRODUCT	SPECIES	RESULT
Bisphenol A Epoxy Resin	Rabbit	SKIN-IRRITANT
	Rabbit	EYES -IRRITANT
Butyl Glycidyl Ether	Rabbit	SKIN-IRRITANT
	Rabbit	EYES-SEVERE IRRITANT

**Sensitizer:**

ROUT OF EXPOSURE	PRODUCT:	SPECIES	RESULT
Skin	Bisphenol A Epoxy Resin	Mouse	sensitizing

**CARCINOGENICITY:**

Bisphenol A Epoxy Resin - Suspected of Causing Cancer

Butyl Glycidyl Ether - Suspected of Causing Cancer

**MUTAGENICITY:**

Bisphenol A Epoxy Resin - Suspected of Causing Genetic Effects

Butyl Glycidyl Ether - Suspected of Causing Genetic Defects

**SPECIFIC TARGET ORGAN TOXICITY-STOT (SINGLE EXPOSURE)**

Butyl Glycidyl Ether      Respiratory Tract Irritation

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.



**TARGET ORGANS:** BRAIN, BLOOD, KIDNEYS, LUNGS, REPRODUCTIVE SYSTEM, LIVER, HEART, PERIPHERAL NERVOUS SYSTEM, GASTROINTESTINAL TRACT, UPPER RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, NERVOUS SYSTEM, EYE, LENS AND/OR CORNEA

**ASPIRATION HAZARD :**

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS

---



---

**12. ECOLOGICAL INFORMATION**

---



---

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

**Toxicity :**

Product / Ingredient	Result	Dosage	Species	Exposure
Bisphenol A Epoxy Resin	EC50 Static	9.4 mg/L	Algae	72 Hours
	EC50 Static	1.7 mg/l	Daphnia Magna	48 Hours
<b>Bioaccumulative Potential :</b>				
Product / Ingredient	LogP(ow)	BCF	Potential	
Bisphenol A Epoxy Resin	3.242	31	low	

**PERSISTANCE AND DEGRADABILITY:**

TEST	PRODUCT PERIOD	RESULT
OECD 301F	Bisphenol A Epoxy Resin 28 DAYS	5%
AQUATIC HALF LIFE	PRODUCT PHOTOLYSIS	BIODEGRADABILITY
Fresh Water 4.83 days	Bisphenol A Epoxy Resin -	Not Readily
Fresh water 3.58 days	-	Not Readily
Fresh water 7.1 days	-	Not Readily
Bisphenol A Epoxy Resin - Not Readily Biodegradable		

**Mobility in Soil :** Not Available

---

**13. DISPOSAL CONSIDERATIONS**

---

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.

React with curing agent and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

---

---

**14. TRANSPORT INFORMATION**

---

---

**DOT: Not regulated**

UN Number: Not regulated

IATA: Not regulated

IMDG/IMO: Not regulated

NMFC: 4620 SUB.5 – CL.60

Schedule B # 3506.91.0000

---

---

**15. REGULATORY INFORMATION**

---

---

**US Regulations Federal**

Chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA)

To the best of our knowledge, this material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

**United States:** Sara 302/304 (Sara 304 RQ): Not Applicable

Information On Ingredients: None Were Found

**Sara 311/312**

**Classification: Fire Hazard, Immediate (acute) Health Hazard, Delayed (chronic) Health Hazard**

**US Regulations State**

**Butyl Glycidyl Ether**

**Pennsylvania (RTK) - Listed**

**California Proposition 65 (RTK) - Listed**

**(Developmental Female)**

**California Prop. 65 : Warning**

This product contains a chemical or chemicals known by the state of California to cause cancer, birth defects, or other reproductive harm.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

Listed National Pollutant Release Inventory (NPRI):

BUTYL GLYCIDYL ETHER

Bisphenol A Epoxy Resin

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

---

---

**16. OTHER INFORMATION**

---

---

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0

Customer and / or end user is responsible for determining PPE

### HMIS

Preparer:

Flamemaster / Compliance

Revision Date: 05/12/2020

Containers:

plastic jars, metal cans  
cartridge kits

Limited Quantity

See SDS Section 14

Maximum container size 50 Gallons / 190 Liters

**Notice to reader:**

**This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.**

**In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.**

**This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.**

**Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.**

**End of Safety Data Sheet**