

Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1. Product Identifier: E400/E400X Part B (Top Coat) - White
 - Product Name: Tough Epoxy Coating
 - Product reference: E400/E400X Part B (Top Coat) - White

1.2. Product Use:

Tough Epoxy Coating

1.3. Manufacturer's Name:

CAGE Code: 14439
Flamemaster Corp.
Chem Seal Division
13576 Desmond Street
Pacoima, CA 91333 – USA

1.3.1 Suppliers Name (if not manufacturer)

Technical Contact:

Flamemaster Corp.
Tel: 818-890-1401
Fax: 818-890-6001
www.flamemaster.com

Emergency Contact Information :
 See Below

Specification

AS1129

CATALYST PART B

NSN:		6850-00-009-5032
		E-400/E400X T/C White Quart Kit

Emergency Contact:

CHEMTEL: WWW.CHEMTELINE.COM

Flamemaster Corporation Contract Number MIS2644301

Shipments of hazardous materials within United States, Canada, Puerto Rico, and U.S. Virgin Island should reference Chemtel's toll free phone number: 1-800-255-3924 - Reference Number MIS2644301

Shipments and safety applications outside of United States, Canada, Puerto Rico, and the U.S. Virgin Islands must reference Chemtel phone number +1-813-248-0585 - Reference Number MIS2644301

Collect Calls will be accepted. To ensure a bilingual operator please call collect.

Shipments originating in U.S.A. and going overseas must use both numbers.

Shipments originating overseas and destined for US, Canada, Puerto Rico or the Virgin Islands must also use both numbers. Calls originating on board vessels should follow normal ship to shore protocols. Use international access number and alert the ship to shore operator you are involved in an emergency incident.

Shipments of hazardous materials within the listed countries should reference Chemtel's in-country phone numbers:

Australia : 1-300-954-583 : Reference Number MIS2644301

Brazil : 0-800-591-6042 : Reference Number MIS2644301

China : 400-120-0751 : Reference Number MIS2644301

India : 000-800-100-4086 : Reference Number MIS2644301

Mexico : 01-800-099-0731 : Reference Number MIS2644301

Section -2. HAZARD (S) IDENTIFICATION

OSHA/HCS STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

CLASSIFICATION OF THE MIXTURE:

FLAMMABLE LIQUID - CATEGORY 2

ASPIRATION HAZARD - CATEGORY 1

ACUTE TOXICITY, ORAL - CATEGORY 4

ACUTE TOXICITY (INHALATION) - CATEGORY 4

CARCINOGENICITY - Category 2

SKIN CORROSION/IRRITATION - Category 1B

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

SKIN SENSITIZATION - CATEGORY 1

GERM CELL MUTAGENICITY-CATEGORY 2

TOXIC TO REPRODUCTION - CATEGORY 2

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE - (NARCOTIC EFFECTS) - CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY-REPEAT EXPOSURE -CATEGORY 2

REPRODUCTIVE TOXICITY, EFFECTS ON OR VIA LACTATION

AQUATIC (CHRONIC) - CATEGORY 4

GHS LABEL REQUIREMENTS:

HAZARD PICTOGRAMS:



SIGNAL WORD : DANGER

HAZARD STATEMENTS:

HIGHLY FLAMMABLE LIQUID AND VAPOR - H225

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - H304

HARMFUL IF SWALLOWED - H302

HARMFUL IF INHALED - H332

SUSPECTED OF CAUSING CANCER - H351

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE - H314

MAY CAUSE AN ALLERGIC SKIN REACTION - H317

SUSPECTED OF CAUSING GENETIC DEFECTS - H341

SUSPECTED OF DAMAGING FERTILITY. SUSPECTED OF DAMAGING THE UNBORN CHILD - H361fd

MAY CAUSE DROWSINESS OR DIZZINESS - H336

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE - H373

MAY CAUSE HARM TO BREAST-FED CHILDREN - H362

MAY CAUSE LONG LASTING HARMFUL EFFECTS TO AQUATIC LIFE - H413

In the event of sanding, grinding, or abrading:

H372 Causes damage to organs through prolonged or repeated exposure.

Hazards Not Otherwise Classified (HNOC):

Sanding and grinding dust may be harmful if inhaled. Sanding and grinding dust may form combustible concentrations in air. Emits toxic fumes when heated.

GENERAL PRECAUTIONARY STATEMENTS:

P101: If medical advice is needed, have product container or label at hand.

P102: keep out of reach of children.

P103: Read label before use.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

PRECAUTIONARY STATEMENTS:

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking
- P233: Keep container tightly closed.
- P240: Ground / bond container and receiving equipment.
- P241: Use explosion-proof electrical / ventilating / lighting /.../ equipment.
- P242: Use only non-sparking tools.
- P243: Take precautionary measures against static discharge.
- P260: Do not breathe dust / fumes / gas / mist / vapors / spray.
- P261: Avoid breathing dust / fumes / gas / mist / vapors / spray.
- P263: Avoid contact during pregnancy / while nursing.
- P264: Wash thoroughly after handling.
- P270: Do not eat, drink, or smoke when using this product.
- P271: Use only outdoors or in a well - ventilated area.
- P272: Contaminated work clothing should not be allowed out of the workplace.
- P273: Avoid release to the environment.
- P280: Wear protective gloves / protective clothing / eye protection / face protection.
- P281: Use personal protection equipment as required.
- P301+310: IF SWALLOWED: Immediately call a POISON CENTER / doctor / ...
- P301+312: IF SWALLOWED: Call a POISON CENTER / doctor / .../ if you feel unwell.
- P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P302+352: IF ON SKIN: Wash with plenty of water / ...
- P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
- P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+351+338: IF IN EYES: Rinse cautiously for several minutes. Remove contact lenses if present and easy to do-continue rinsing
- P308+313: If exposed: Call a POISON CENTER or doctor / physician.
- P310: Immediately call a POISON CENTER / doctor/...
- P312: Call a POISON CENTER / doctor /... / if you feel unwell.
- P314: Get medical advise / attention if you feel unwell.
- P321: Specific treatment...See Label Information
- P330: Rinse mouth
- P331: Do NOT induce vomiting.
- P333+313: If skin irritation or a rash occurs: Get medical advice / attention.
- P363: Wash contaminated clothing before reuse.
- P370+378: In case of fire: Use ... to extinguish.
- P403+233: Store in a well ventilated place. Keep container tightly closed.
- P403+235: Store in a well ventilated place. Keep cool.
- P405: Store locked up.
- P501: Dispose of contents / containers in accordance with local / regional / national / international regulations

SUPPLEMENTAL LABEL ELEMENTS:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of concentrations above recommended limits causes headaches, drowsiness and nausea and could lead to unconsciousness or possibly death.

Irritating to the mucous membranes and may cause the skin to become sensitized.

Avoid any contact with skin or clothing and wash thoroughly after handling.

Emits toxic fumes when heated.

HAZARDS NOT OTHERWISE CLASSIFIED:

Prolonged or repeated exposure may dry skin and / or cause skin irritation.

Sanding and grinding dust may be harmful if inhaled. Sanding and grinding dust may form combustible concentrations in air.

In the event of sanding, grinding, or abrading:

H372 Causes damage to organs through prolonged or repeated exposure.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

Section -3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical family : Mixture of organic compounds

For the hazards of the composition, (SDS see Section 2).

% BY WEIGHT IN PRODUCT-	HAZARDOUS INGREDIENT	CAS#-
<20%	Glycol Ether EB	111-76-2
Combustible Liquid		
Causes Skin Irritation		
Causes Eye Irritation		
May Cause Respiratory Irritation		
	fatty Acids, C18-unsatd., Dimers, Oligomeric Reaction Products with Tall-Oil Fatty Acids and Triethylenetetramine	
<50%		68082-29-1 / 112-24-3
Skin Corrosion / Irritation (Category 2)		
Serious Eye Damage / Eye Irritation (Category 1)		
Skin Sensitization (Category 1A)		
Aquatic Hazard (Acute) - (Category 2)		
Aquatic Hazard (Long Term) - (Category 2)		
	1,2-ETHANEDIAMINE N1,N2-BIS (2-AMINOETHYL)	
<40%		90640-67-8
Skin Corrosion / Irritation (Category 1B)		
Serious Eye Damage / Eye Irritation (Category 1)		
Skin Sensitization (Category 1A)		
Aquatic Hazard (Acute) - (Category 2)		
Aquatic Hazard (Long Term) - (Category 2)		
	2-PROPANOL	
<10%		67-63-0
OSHA HAZARDS: FLAMMABLE LIQUIDS,TARGET ORGAN EFFECT,IRRITANT		
OTHER HAZARDS THAT DO NOT RESULT IN CLASSIFICATION: MAY FORM EXPLOSIVE PEROXIDES		
GHS CLASSIFICATION: 2-PROPANOL		
FLAMMABLE LIQUIDS (CATEGORY2)		
SKIN IRRITATION (CATEGORY3)		
EYE IRRITATION (CATEGORY 2A)		
SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE (CATEGORY3)		
ACUTE TOXICITY ORAL (CATEGORY 5)		
	Butanol	
<20%		71-36-3
HARMFUL IF SWALLOWED - H302		
CAUSES SKIN IRRITATION - H315		
FLAMMABLE LIQUID AND VAPOR - H226		
MAY CAUSE RESPIRATORY IRRITATION - H335		
MAY CAUSE DROWSINESS OR DIZZINESS - H336		
CAUSES SERIOUS EYE DAMAGE - H318		

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage, use and disposal are beyond our control and may be beyond our knowledge.

TOLUENE

<1%

108-88-3

HIGHLY FLAMMABLE LIQUID AND VAPOR - H225
SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD - H361
SUSPECTED OF CAUSING CANCER - H351
CAUSES SKIN IRRITATION - H315
CAUSES SERIOUS EYE IRRITATION - H319
TOXIC TO AQUATIC LIFE - H400

BISPHENOL-A-EPOXY RESIN

<5%

25068-38-6

OSHA HAZARDS: Skin Sensitiser,Irritant
GHS CLASSIFICATION: EPOXY RESIN
SKIN IRRITATION (CATEGORY 2)
EYE IRRITATION (CATEGORY 2A)
SKIN SENSITIZATION (CATEGORY 1)
ACUTE AQUATIC TOXICITY (CATEGORY 2)
CHRONIC AQUATIC TOXICITY (CATEGORY 2)

Section -4. FIRST-AID MEASURES

General: When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

Eye contact: Check for and remove any contact lenses. Irrigate with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek immediate medical attention.

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

Section -5. FIRE-FIGHTING MEASURES

Extinguishing agents

Recommended: Universal resistant foam, CO₂, water, powder.

Agents to avoid: None known

Attention

Promptly remove all persons in the event of a fire from the fire area. If safe to do so, remove all containers from fire area as well.

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Do not allow run-off from fire fighting to enter drains or water courses.

Emits toxic fumes when heated.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage, use and disposal are beyond our control and may be beyond our knowledge.

HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE BUT MAY NOT BE LIMITED TO THE FOLLOWING:

- Carbon Dioxide
- Carbon Monoxide
- Carbon Oxides
- Halogenated Compounds
- Airborn Solids and Liquid Particulates
- Nitrogen Oxides
- Nitrogen Oxides can react with water vapors to form corrosive nitric acid
- Calcium Oxides
- Unidentified Organic and Inorganic Compounds
- Toxic Fumes
- Smoke
- Phenolic Compounds
- Sulfur Oxides
- Other Hazardous Materials

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

Section -6. ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Section -7. HANDLING AND STORAGE

7.1 Handling:

No smoking, eating and drinking during handling.

Avoid exposure during pregnancy/while nursing.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

7.2 Storage:

Observe label precautions. Store between 32/F and 95/F (0/C and 35/C) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Engineering measures:

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

8.2 Exposure limits

Work place exposure limits (8 hour)

OSHA	PRODUCT	ACGIH
25 ppm	Glycol Ether EB	20 ppm
400 ppm	2-PROPANOL	200 ppm
50 ppm	Butanol	20 ppm
15 mg/m ³ Total Dust	Calcium Carbonate	-
5 mg/m ³ Respirable Fraction		-
100 ppm	Toluene	20 ppm

8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state at: 68 ° F (20 ° C) Liquid
- Flash point: 5 ° C-----40 ° F Method: TCC
- Specific gravity at: 68 ° F (20 ° C) n/a
- Vapor Density: N/A
- Lower Explosive Limit (% vol.): N/A
- Upper Explosive Limit (% vol.): N/A
- Miscibility in water at 20 ° C: SLIGHT
- VOC : N/A
- Ph : N/A
- % Volatile by Volume: N/A
- Vapor pressure at: 68 ° F (20 ° C) N/A
- Color: WHITE
- Appearance: liquid
- Odor: ALCOHOL ODOR
- Boiling Point: N/A
- Material Supports Combustion : Yes

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see SDS section 7). In case of combustion, may produce hazardous decomposition products such as :

HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE BUT MAY NOT BE LIMITED TO THE FOLLOWING:

- Carbon Dioxide
- Carbon Monoxide
- Carbon Oxides
- Halogenated Compounds
- Airborn Solids and Liquid Particulates
- Nitrogen Oxides
- Nitrogen Oxides can react with water vapors to form corrosive nitric acid
- Calcium Oxides
- Unidentified Organic and Inorganic Compounds
 - Toxic Fumes
 - Smoke
 - Phenolic Compounds
 - Sulfur Oxides
 - Other Hazardous Materials

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs of overexposure include headache, dizziness, fatigue, muscular weakness, drowsiness, reduced fetal weight, increase in fetal deaths, skeletal malformations, and in extreme cases loss of consciousness

Repeated or prolonged contact with the preparation may cause Defatting of the skin resulting in non-allergic dermatitis and absorption through the skin.

The liquid splashed in the eyes causes serious eye irritation and damage.

Irritating to mouth, throat and stomach. Ingestion causes reduced fetal weight, increased fetal deaths and skeletal malformations

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

ACUTE TOXICITY:

ENDPOINT	SPECIES	PRODUCT	DOSE	EXPOSURE
fatty Acids, C18-unsatd., Dimers, Oligomeric Reaction Products with Tall-Oil Fatty Acids and Triethylenetetramine				
LD50 ORAL	Rat		1761.2 mg/kg	-
2-PROPANOL				
LD50 Oral	Rat		4710 mg/kg	-
LD50 Oral	Mouse		3600 mg/kg	-
LD50 Dermal	Rabbit		12870 mg/kg	-
Butanol				
LD50 ORAL	Rat		700 mg/kg	-
LD50 ORAL	Rat		790 mg/kg	-
LD50 Dermal	Rabbit		3400 mg/kg	-
LD50 Dermal	Rabbit		3402 mg/kg	-
BISPHENOL-A-EPOXY RESIN				
LD50 DERMAL	Rabbit		>2 g/kg	-
LD50 ORAL	Rat		11.4 g/kg	-

CORROSION / IRRITATION**PRODUCT**

2-propanal Causes mild skin irritation
Causes serious eye irritation

BISPHENOL-A-EPOXY RESIN Skin - Mild Irritant
Eyes - Causes serious eye irritation

1,2-ETHANEDIAMINE N1,N2-BIS (2-AMINOETHYL)

Causes severe skin burns and eye damage

Sensitizer:

fatty Acids, C18-unsatd., Dimers, Oligomeric Reaction Products with Tall-Oil Fatty Acids and Triethylenetetramine
- Causes Sensitization

1,2-ETHANEDIAMINE N1,N2-BIS (2-AMINOETHYL)
Causes Skin Sensitization

BISPHENOL-A-EPOXY RESIN May cause an allergic skin reaction

SPECIFIC TARGET ORGAN TOXICITY-STOT (SINGLE EXPOSURE)

2-PROPANOL May Cause Drowsiness or dizziness

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

TARGET ORGANS: BRAIN, BLOOD, KIDNEYS, LUNGS, REPRODUCTIVE SYSTEM, LIVER, HEART, PERIPHERAL NERVOUS SYSTEM, GASTROINTESTINAL TRACT, UPPER RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, NERVOUS SYSTEM, EYE, LENS AND/OR CORNEA

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Toxicity :

RESULT	PRODUCT SPECIES	EXPOSURE
Glycol Ether EB		
LC50 1575 mg/l	Carp	48 Hours
LC50 1720 mg/l	Daphnia Magna	24 Hours
Triethylenetetramine		
LC50 Static 330mg/l	Pimephales Promelas	96 Hours
EC50 31.1 mg/l	Daphnia Magna	48 Hours
ErC50 20 mg/l	Algae	72 Hours
EC10 1.9 mg/l	Daphnia Magna	21 Days
EC50 Static 800mg/l	Bacteria	0.5 HOURS
BUTANOL		
EC50 500 mg/L	Desmodesmus Subspicatus	96 Hours
EC50 500 mg/L	Desmodesmus Subspicatus	72 Hours
EC50 1983 mg/L	Daphnia Magna	48 Hours
EC50 Static 1897-2072 mg/L	Daphnia Magna	48 Hours
BISPHENOL-A-EPOXY RESIN		
EC50 9.4 mg/L	Algae	72 Hours Static
EC50 1.7 mg/L	Daphnia Magna	48 Hours Static
IC50 >100 mg/L	Bacteria	3 Hours Static
LC50 1.5 mg/L	Fish	96 Hours

PERSISTANCE AND DEGRADABILITY:

TEST	PRODUCT PERIOD	RESULT
301D	Triethylenetetramine 162 Days	0%
301F	BISPHENOL-A-EPOXY RESIN 28 Days	5%

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

AQUATIC HALF LIFE	PRODUCT PHOTOLYSIS	BIODEGRADABILITY
	BISPHENOL-A-EPOXY RESIN	
Fresh Water 4.83 Days	-	Not Readily
Fresh Water 3.58 Days	-	Not Readily
Fresh Water 7.1 Days	-	Not Readily

Bioaccumulative Potential :
Product / Ingredient

Product / Ingredient	LogP(ow)	BCF	Potential
Triethylenetetramine	-2.65		
Butanol	Partition Coefficient - 0.785		
BISPHENOL-A-EPOXY RESIN	3.8	-	low
BISPHENOL-A-EPOXY RESIN	3.242	31	low

Mobility in Soil : Not Available

13. DISPOSAL CONSIDERATIONS

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.
 React with curing agent and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.
 Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.
 Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

14. TRANSPORT INFORMATION

DOT: § 172.101 HAZARDOUS MATERIALS TABLE
UN Number: 1263
Proper Shipping Name: Paint Related Material
Labels: Flammable Liquid

IATA:
 UN Number: 1263
 Proper Shipping Name: Paint Related Material
 Labels: Flammable Liquid
 Hazard Class: 3 Subclass: NO
 Packaging Group: II
 Passenger Air Packing Instruction : 355
 Passenger aircraft: 60 Liter (16 gallon)
 Cargo Air Packing Instruction : 366
 Cargo aircraft only: 220 Liter (58 gallon)

Hazard Class: 3 Subclass: NO
 Packaging Group: II
 Limited Quantity: Passenger aircraft: 10 Liter (2.64 Gallons)
 Cargo aircraft only: 220 Liter (58 gallon)
 Vessel stowage: A
 ERG: 128
 NMFC 4620 sub.5-CL.60
 Schedule B # 3506.91.0000

IMDG:
 UN Number: 1263
 Proper Shipping Name: Paint Related Material
 Label: 3
 Hazard Class: 3 Subclass: NO
 Packaging Group: II
 EMS No: F, E – S, D

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

15. REGULATORY INFORMATION

US Regulations Federal

chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA)	Chemical Name	CAS No	Weight %	Threshold limit (Reporting Value)
	2-Propanal	67-63-0	<10%	unknown
	BUTANOL	71-36-3	<20%	unknown
	Toluene	108-88-3	<1%	unknown

SARA notifications must remain attached to this SDS. Any copies and /or distribution of this SDS must include all SARA notifications.

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

United States: Sara 302/304 (Sara 304 RQ): Not Applicable

Information On Ingredients: None Were Found

Sara 311/312

Classification: Fire Hazard, Immediate (acute) Health Hazard, Delayed (chronic) Health Hazard

US Regulations State

Glycol Ether EB	New Jersey	(RTK)	- Listed
	Massachusetts	(RTK)	- Listed
	Pennsylvania	(RTK)	- Listed
	Rhode Island	(RTK)	- Listed
2-propanal	New Jersey	(RTK)	- Listed
	Massachusetts	(RTK)	- Listed
	Pennsylvania	(RTK)	- Listed
	Rhode Island	(RTK)	- Listed
Calcium Carbonate	New Jersey	(RTK)	- Listed
	Massachusetts	(RTK)	- Listed
BUTANOL	New Jersey	(RTK)	- Listed
	Massachusetts	(RTK)	- Listed
	Pennsylvania	(RTK)	- Listed
	Rhode Island	(RTK)	- Listed

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

TOLUENE

California Prop. 65 Warning:

This Product Contains a Chemical or Chemicals known to the State of California to Cause Cancer, Birth Defects or Other Reproductive Harm

Rhode Island (RTK) - Listed

Pennsylvania (RTK) - Listed

Massachusetts (RTK) - Listed

New Jersey (RTK) - Listed

California Prop. 65 : Warning

This product contains a chemical or chemicals known by the state of California to cause cancer, birth defects, or other reproductive harm.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

Listed National Pollutant Release Inventory (NPRI):

- fatty Acids, C18-unsatd., Dimers, Oligomeric Reaction Products with Tall-Oil Fatty Acids and Triethylenetetramine
- Glycol Ether EB
- 2-Propanol Cas# 67-63-0
- BUTANOL Cas# 71-36-3

16. OTHER INFORMATION

HEALTH	3
FLAMMABILITY	3
REACTIVITY	0

NFPA

HEALTH	3
FLAMMABILITY	3
REACTIVITY	0

HMIS

Customer and / or end user is responsible for determining PPE

LIST OF ABBREVIATIONS :

OSHA - OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGENISTS

PNOC - PARTICULATES NOT OTHERWISE CLASSIFIED (ACGIH)

TWA - TIME WEIGHTED AVERAGE

IARC - INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

NTP - NATIONAL TOXICOLOGY PROGRAM

SARA - SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT

NFPA - NATIONAL FIRE PROTECTION ASSOCIATION

HMIS - HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

Preparer:

Flamemaster / Compliance

Revision Date: 08/10/2022

Containers:

plastic jars, metal cans
cartridge kits

Limited Quantity

See SDS Section 14

Maximum container size 50 Gallons / 190 Liters

Notice to reader:

This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.

This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.

Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.

End of Safety Data Sheet