

**Safety Data Sheet (HazCom 2012)
CS-3204 Part A Class B - TESTFP**

Safety Data Sheet date: 12/5/2024, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:
Trade name: CS-3204 Part A Class B
Other means of identification:
SDS code: TESTFP

Recommended use of the chemical and restrictions on use

Recommended use:
Industrial uses
Sealant
Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Manufacturers:

Flamemaster Corp., 13576 Desmond Street, Pacoima, CA 91331 - USA CAGE Code: 14439

Distributors:

Flamemaster Corp., Tel 818-890-1401, Fax 818-890-6001, www.flamemaster.com

Competent person responsible for the safety data sheet:

Flamemaster Corp., Tel 818-890-1401, Fax 818-890-6001, www.flamemaster.com


Emergency phone number:


CHEMTEL: +1-813-248-0585 (International); 1-800-255-3924 (USA)


2. HAZARD(S) IDENTIFICATION


Classification of the chemical


Warning, Flam. Liq. 4, Combustible liquid.

 Danger, Resp. Sens. 1, May cause allergy or asthma symptoms or breathing difficulties if inhaled.

 Warning, Skin Sens. 1, May cause an allergic skin reaction.

 Danger, Carc. 1A, May cause cancer.

 Warning, Repr. 2, Suspected of damaging fertility or the unborn child.

 Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictograms:



Safety Data Sheet (HazCom 2012)
CS-3204 Part A Class B - TESTFP

Danger

Hazard statements:

- H227 Combustible liquid.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H350 May cause cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P284 [In case of inadequate ventilation] wear respiratory protection.
- P302+P352 IF ON SKIN: Wash with plenty of water/...
- P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor/...
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use Alcohol foam, carbon dioxide (CO₂), dry chemical, water spray/water fog to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:


>= 60% - < 70% Aliphatic polysulfide polymer

CAS: 68611-50-7







US-HAE/C3 Aquatic Chronic 3 H412

>= 1% - < 3% Toluene

CAS: 108-88-3

 B.6/2 Flam. Liq. 2 H225

Safety Data Sheet (HazCom 2012)
CS-3204 Part A Class B - TESTFP

-  A.2/2 Skin Irrit. 2 H315
-  A.3/2A Eye Irrit. 2A H319
-  A.7/2 Repr. 2 H361d
-  A.8/3 STOT SE 3 H336
-  A.9/2 STOT RE 2 H373
-  A.10/1 Asp. Tox. 1 H304

US-HAE/A2 Aquatic Acute 2 H401
US-HAE/C3 Aquatic Chronic 3 H412

>= 0.5% - < 1% Bisphenol A - epoxy resins, number average MW >700-<1100
CAS: 67924-34-9

-  B.6/2 Flam. Liq. 2 H225
-  A.3/2A Eye Irrit. 2A H319
-  A.2/2 Skin Irrit. 2 H315
-  A.4.2/1 Skin Sens. 1 H317
-  A.7/2 Repr. 2 H361d

US-HAE/A2 Aquatic Acute 2 H401
US-HAE/C3 Aquatic Chronic 3 H412

>= 0.1% - < 0.25% tetramethylthiuram disulphide
CAS: 137-26-8

-  A.1/4/Oral Acute Tox. 4 H302
-  A.1/4/Inhal Acute Tox. 4 H332
-  A.2/2 Skin Irrit. 2 H315
-  A.3/2A Eye Irrit. 2A H319
-  A.4.2/1 Skin Sens. 1 H317
-  A.9/2 STOT RE 2 H373

>= 0.1% - < 0.25% Magnesium oxide
CAS: 1309-48-4

Safety Data Sheet (HazCom 2012) CS-3204 Part A Class B - TESTFP

 A.4.1/1 Resp. Sens. 1 H334

 A.8/3 STOT SE 3 H335

 A.9/1 STOT RE 1 H372

>= 0.1% - < 0.25% Crystalline Silica (Quartz SiO₂)
CAS: 14808-60-7, EC: 238-878-4

 A.3/2A Eye Irrit. 2A H319

 A.6/1A Carc. 1A H350

 A.8/1 STOT SE 1 H370

 A.8/3 STOT SE 3 H335

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.
Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire: Use Alcohol foam, carbon dioxide (CO₂), dry chemical, water spray/water fog to extinguish.

Unsuitable extinguishing media

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.A.

Safety Data Sheet (HazCom 2012) CS-3204 Part A Class B - TESTFP

Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Storage temperature:

Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Toluene - CAS: 108-88-3

- OEL Type: ACGIH - TWA: 20 ppm

- OEL Type: NIOSH REL - TWA: 375 mg/m³, 100 ppm

- OEL Type: ST - TWA: 560 mg/m³, 150 ppm

- OEL Type: TWA - TWA: 200 ppm

tetramethylthiuram disulphide - CAS: 137-26-8

- OEL Type: ACGIH - TWA: 5 mg/m³ - Notes: Inhalable fraction and vapor

- OEL Type: NIOSH - TWA: 0.05 mg/m³

- OEL Type: OSHA PEL - TWA: 5 mg/m³

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

Safety Data Sheet (HazCom 2012)
CS-3204 Part A Class B - TESTFP

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	White	--	--
Odour:	Polysulfide Odor	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash Point (°F):	200	--	--
Flash point (°C):	93	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	N.A.	--	--
Relative density:	N.A.	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes
------------	-------	---------	-------

Safety Data Sheet (HazCom 2012)
CS-3204 Part A Class B - TESTFP

Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

None

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

CS-3204 Part A Class B

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

Skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

Serious eye damage/irritation

Not classified

Based on available data, the classification criteria are not met

Respiratory or skin sensitisation

The product is classified: Resp. Sens. 1 H334;Skin Sens. 1 H317

Germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

Carcinogenicity

The product is classified: Carc. 1A H350

Reproductive toxicity

The product is classified: Repr. 2 H361

STOT-single exposure

Not classified

Based on available data, the classification criteria are not met

STOT-repeated exposure

The product is classified: STOT RE 2 H373

Aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

Aliphatic polysulfide polymer - CAS: 68611-50-7

Safety Data Sheet (HazCom 2012)
CS-3204 Part A Class B - TESTFP

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Toluene - CAS: 108-88-3

Acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat (male) 6700 ppm - Duration: 4h - Notes: The component/mixture is moderately toxic after short term inhalation.

Test: LD50 - Route: Skin - Species: Rat (male) 1700 mg/kg - Notes: The component/mixture is moderately toxic after single contact with skin.

tetramethylthiuram disulphide - CAS: 137-26-8

Acute toxicity:

Test: LD50 - Route: Skin - Species: Rat > 1000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 3.46 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat 1800 mg/kg

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

None.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

CS-3204 Part A Class B

The product is classified: Aquatic Chronic 3 - H412

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

No harmful effects expected.

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number

Not classified as dangerous in the meaning of ADR, IATA and IMDG transport regulations.

UN proper shipping name

N.A.

Transport hazard class(es)

N.A.

Packing group

Safety Data Sheet (HazCom 2012)
CS-3204 Part A Class B - TESTFP

N.A.
Environmental hazards
ADR-Environmental Pollutant: No
IMDG-Marine pollutant: No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
N.A.
Special precautions
N.A.

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

List of substances included in the TSCA inventory: Aliphatic polysulfide polymer, Toluene, Bisphenol A - epoxy resins, number average MW >700-<1100.

List of substances not included in the TSCA inventory: tetramethylthiuram disulphide, Magnesium oxide, Crystalline Silica (Quartz SiO₂).

TSCA sections for substances listed in section 3:

Aliphatic polysulfide polymer is listed in TSCA Section 8b

Toluene is listed in TSCA Section 8a - CAIR, Section 8d HSDR, Section 8b

Bisphenol A - epoxy resins, number average MW >700-<1100 is listed in TSCA Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 Extremely Hazardous Substances: no substances listed.

Section 304 Hazardous substances: Toluene.

Section 313 Toxic chemical list: Toluene.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: Toluene - Reportable quantity: 1000 pounds.

Reportable quantity for mixture: 49217.44266 pounds.

CAA - Clean Air Act

CAA listed substances:

Toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

Toluene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

Toluene - Listed as reproductive toxicant.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

No substances listed.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Toluene.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Safety Data Sheet (HazCom 2012) CS-3204 Part A Class B - TESTFP

Toluene.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

- H412 Harmful to aquatic life with long lasting effects.
- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H361d Suspected of damaging the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H304 May be fatal if swallowed and enters airways.
- H401 Toxic to aquatic life.
- H317 May cause an allergic skin reaction.
- H302 Harmful if swallowed.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H350 May cause cancer.
- H370 Causes damage to organs.

According to TSCA section 3(2)(B)(i) : a hydrated form of a chemical substance is considered a mixture of the corresponding anhydrous form and water.

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization"

Safety Data Sheet (HazCom 2012)
CS-3204 Part A Class B - TESTFP

(ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
NFPA: National Fire Protection Association
NIOSH: National Institute for Occupational Safety and Health
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PNEC: Predicted No Effect Concentration.
RID: Regulation Concerning the International Transport of Dangerous Goods
by Rail.

TOTAL
VOC'S
(TVOC) /
NONEXEMPT
VOC'S
(CVOC):
Using
California
South Coast
Air Quality
Management
District
(SCAQMD)
Rule 1143.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average

Safety Data Sheet date: 12/5/2024, version 1