

Safety Data Sheet (HazCom 2012)

CS-3204 Part B 20-Hour Weld Through - CS3204BWT20

Safety Data Sheet date: 12/11/2024, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: CS-3204 Part B 20-Hour Weld Through

Other means of identification:

SDS code: CS3204BWT20

Recommended use of the chemical and restrictions on use

Recommended use:

Industrial uses

Sealant

Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Manufacturers:

Flamemaster Corp., 13576 Desmond Street, Pacoima, CA 91331 - USA CAGE Code: 14439

Distributors:

Flamemaster Corp., Tel 818-890-1401, Fax 818-890-6001, www.flamemaster.com

Competent person responsible for the safety data sheet:

Flamemaster Corp., Tel 818-890-1401, Fax 818-890-6001, www.flamemaster.com


Emergency phone number:

CHEMTEL: +1-813-248-0585 (International); 1-800-255-3924 (USA)


2. HAZARD(S) IDENTIFICATION


Classification of the chemical


Warning, Flam. Liq. 4, Combustible liquid.

 Warning, Acute Tox. 4, Harmful if swallowed.

 Warning, Acute Tox. 4, Harmful if inhaled.

 Warning, Skin Irrit. 2, Causes skin irritation.

 Warning, Eye Irrit. 2A, Causes serious eye irritation.

 Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Label elements

Hazard pictograms:



Warning

Hazard statements:

H227 Combustible liquid.

H302 Harmful if swallowed.

H332 Harmful if inhaled.

Safety Data Sheet (HazCom 2012)

CS-3204 Part B 20-Hour Weld Through - CS3204BWT20

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/clothing and eye/face protection.

P301+P312 IF SWALLOWED: Immediately call a POISON CENTER/doctor/... if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water/...

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P330 Rinse mouth.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use Alcohol foam, carbon dioxide (CO₂), dry chemical, water spray/water fog to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 60% - < 70% Manganese Dioxide

CAS: 1313-13-9



A.1/4/Oral Acute Tox. 4 H302



A.1/4/Inhal Acute Tox. 4 H332



A.2/2 Skin Irrit. 2 H315



A.3/2A Eye Irrit. 2A H319



A.9/2 STOT RE 2 H373 (Inhalation)

Safety Data Sheet (HazCom 2012)

CS-3204 Part B 20-Hour Weld Through - CS3204BWT20

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do NOT induce vomiting.
- Give nothing to eat or drink.

In case of Inhalation:

- If breathing is irregular or stopped, administer artificial respiration.
- In case of inhalation, consult a doctor immediately and show the packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

- In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

- In case of fire: Use Alcohol foam, carbon dioxide (CO₂), dry chemical, water spray/water fog to extinguish.

Unsuitable extinguishing media

None in particular.

Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.A.

Oxidizing properties:

N.A.

Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus .
 - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 - Move undamaged containers from immediate hazard area if it can be done safely.
-

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

- Wear personal protection equipment.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.
- Provide adequate ventilation.
- Use appropriate respiratory protection.
- See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

- Wash with plenty of water.
-

7. HANDLING AND STORAGE

Precautions for safe handling

- Avoid contact with skin and eyes, inhalation of vapours and mists.

Safety Data Sheet (HazCom 2012)

CS-3204 Part B 20-Hour Weld Through - CS3204BWT20

Do not use on extensive surface areas in premises where there are occupants.
 Use localized ventilation system.
 Don't use empty container before they have been cleaned.
 Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.
 See also section 8 for recommended protective equipment.
 Advice on general occupational hygiene:
 Contaminated clothing should be changed before entering eating areas.
 Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities
 Always keep in a well ventilated place.
 Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
 Keep away from food, drink and feed.
 Incompatible materials:
 None in particular.
 Instructions as regards storage premises:
 Cool and adequately ventilated.
 Storage temperature:
 Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters
 Manganese Dioxide - CAS: 1313-13-9
 - OEL Type: TWA - TWA: 0.1 mg/m3 - Notes: (as Mn) Inhalable fraction.
 DNEL Exposure Limit Values
 N.A.
 PNEC Exposure Limit Values
 N.A.
 Appropriate engineering controls:
 None
 Individual protection measures
 Eye protection:
 Use close fitting safety goggles, don't use eye lens.
 Protection for skin:
 Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.
 Protection for hands:
 Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.
 Respiratory protection:
 Use adequate protective respiratory equipment.
 Thermal Hazards:
 None

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	Black	--	--
Odour:	Negligible Oily Odor	--	--
Odour threshold:	N.A.	--	--
pH:	9	--	--

Safety Data Sheet (HazCom 2012)

CS-3204 Part B 20-Hour Weld Through - CS3204BWT20

Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash Point (°F):	200	--	--
Flash point (°C):	93	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	N.A.	--	--
Relative density:	N.A.	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

10. STABILITY AND REACTIVITY

Reactivity
 Stable under normal conditions
 Chemical stability
 Stable under normal conditions
 Possibility of hazardous reactions
 None
 Conditions to avoid
 Stable under normal conditions.
 Incompatible materials
 None in particular.
 Hazardous decomposition products
 None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects
 Toxicological information of the product:
 CS-3204 Part B 20-Hour Weld Through
 Acute toxicity

Safety Data Sheet (HazCom 2012)

CS-3204 Part B 20-Hour Weld Through - CS3204BWT20

The product is classified: Acute Tox. 4 H302; Acute Tox. 4 H332
ATEmix - Oral 756.876 mg/kg bw
ATEmix - Inhalation (Vapours) 16.6513 mg/l

Skin corrosion/irritation
The product is classified: Skin Irrit. 2 H315

Serious eye damage/irritation
The product is classified: Eye Irrit. 2A H319

Respiratory or skin sensitisation
Not classified
Based on available data, the classification criteria are not met

Germ cell mutagenicity
Not classified
Based on available data, the classification criteria are not met

Carcinogenicity
Not classified
Based on available data, the classification criteria are not met

Reproductive toxicity
Not classified
Based on available data, the classification criteria are not met

STOT-single exposure
Not classified
Based on available data, the classification criteria are not met

STOT-repeated exposure
The product is classified: STOT RE 2 H373

Aspiration hazard
Not classified
Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:
Manganese Dioxide - CAS: 1313-13-9
Acute toxicity:
Test: LD50 - Route: Oral - Species: Rat >= 14900 mg/kg

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

None.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

CS-3204 Part B 20-Hour Weld Through

Not classified for environmental hazards

Based on available data, the classification criteria are not met

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

No harmful effects expected.

Safety Data Sheet (HazCom 2012)

CS-3204 Part B 20-Hour Weld Through - CS3204BWT20

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number

Not classified as dangerous in the meaning of ADR, IATA and IMDG transport regulations.

UN proper shipping name

N.A.

Transport hazard class(es)

N.A.

Packing group

N.A.

Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions

N.A.

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: All the components of this product are listed as active on or are exempt from the TSCA Inventory..

TSCA sections for substances listed in section 3:

Manganese Dioxide is listed in TSCA Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 Extremely Hazardous Substances: no substances listed.

Section 304 Hazardous substances: no substances listed.

Section 313 Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

No substances listed.

CAA - Clean Air Act

CAA listed substances:

None.

CWA - Clean Water Act

CWA listed substances:

None.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

Safety Data Sheet (HazCom 2012)

CS-3204 Part B 20-Hour Weld Through - CS3204BWT20

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

No substances listed.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

No substances listed.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

No substances listed.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H302 Harmful if swallowed.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H373 (Inhalation) May cause damage to organs through prolonged or repeated exposure if inhaled.

According to TSCA section 3(2)(B)(i) : a hydrated form of a chemical substance is considered a mixture of the corresponding anhydrous form and water.

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

HMIS: Hazardous Materials Identification System

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

Safety Data Sheet (HazCom 2012)

CS-3204 Part B 20-Hour Weld Through - CS3204BWT20

KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
NFPA: National Fire Protection Association
NIOSH: National Institute for Occupational Safety and Health
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PNEC: Predicted No Effect Concentration.
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

TOTAL
VOC'S
(TVOC) /
NONEXEMPT
VOC'S
(CVOC):
Using
California
South Coast
Air Quality
Management
District
(SCAQMD)
Rule 1143.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average

Safety Data Sheet date: 12/11/2024, version 1