

Safety Data Sheet (HazCom 2012)
CS-3213 Part B Class B - CS3213BB

Safety Data Sheet date: 4/17/2025, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: CS-3213 Part B Class B

Other means of identification:

SDS code: CS3213BB

Recommended use of the chemical and restrictions on use

Recommended use:

Industrial uses

Sealant

Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Manufacturers:

Flamemaster Corp., 13576 Desmond Street, Pacoima, CA 91331 - USA CAGE Code: 14439

Distributors:

Flamemaster Corp., Tel 818-890-1401, Fax 818-890-6001, www.flamemaster.com

Competent person responsible for the safety data sheet:

Flamemaster Corp., Tel 818-890-1401, Fax 818-890-6001, www.flamemaster.com

Emergency phone number:

CHEMTEL: +1-813-248-0585 (International); 1-800-255-3924 (USA)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

Warning, Flam. Liq. 4, Combustible liquid.



Warning, Acute Tox. 4, Harmful if swallowed.



Danger, Acute Tox. 3, Toxic if inhaled.



Warning, Skin Irrit. 2, Causes skin irritation.



Danger, Eye Dam. 1, Causes serious eye damage.



Warning, Skin Sens. 1, May cause an allergic skin reaction.



Danger, Muta. 1B, May cause genetic defects.



Danger, Carc. 1B, May cause cancer.



Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.



Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Label elements

Hazard pictograms:

Safety Data Sheet (HazCom 2012)
CS-3213 Part B Class B - CS3213BB



Danger

Hazard statements:

H227 Combustible liquid.
 H302 Harmful if swallowed.
 H331 Toxic if inhaled.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H317 May cause an allergic skin reaction.
 H340 May cause genetic defects.
 H350 May cause cancer.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash hands and all exposed skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/clothing and eye/face protection.
 P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor/... if you feel unwell.
 P302+P352 IF ON SKIN: Wash with plenty of water/...
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P310 Immediately call a POISON CENTER/doctor/...
 P311 Call a POISON CENTER/doctor/...
 P314 Get medical advice/attention if you feel unwell.
 P330 Rinse mouth.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P363 Wash contaminated clothing before reuse.
 P370+P378 In case of fire: Use CO2, dry sand, dry chemical, alcohol-resistant foam, or water to extinguish.
 P391 Collect spillage.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

Safety Data Sheet (HazCom 2012)
CS-3213 Part B Class B - CS3213BB

None.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 60% - < 70% Manganese dioxide

CAS: 1313-13-9



A.1/4/Oral Acute Tox. 4 H302



A.1/4/Inhal Acute Tox. 4 H332



A.2/2 Skin Irrit. 2 H315



A.3/2A Eye Irrit. 2A H319



A.9/2 STOT RE 2 H373

>= 7% - < 10% Magnesium Chromate

CAS: 13423-61-5



A.1/3/Oral Acute Tox. 3 H301



A.1/4/Dermal Acute Tox. 4 H312



A.1/2/Inhal Acute Tox. 2 H330



A.2/2 Skin Irrit. 2 H315



A.3/1 Eye Dam. 1 H318



A.4.2/1 Skin Sens. 1 H317



A.5/1B Muta. 1B H340



A.6/1B Carc. 1B H350



A.8/3 STOT SE 3 H335



US-HAE/C1 Aquatic Chronic 1 H410

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Safety Data Sheet (HazCom 2012)
CS-3213 Part B Class B - CS3213BB

Immediately take off all contaminated clothing.
OBTAIN IMMEDIATE MEDICAL ATTENTION.
Remove contaminated clothing immediately and dispose of safely.
After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.
Give nothing to eat or drink.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.
In case of inhalation, consult a doctor immediately and show the packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire: Use CO₂, dry sand, dry chemical, alcohol-resistant foam, or water to extinguish.

Unsuitable extinguishing media

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

Material supports combustion

Oxidizing properties:

N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Safety Data Sheet (HazCom 2012) CS-3213 Part B Class B - CS3213BB

Don't use empty container before they have been cleaned.
 Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.
 See also section 8 for recommended protective equipment.
 Advice on general occupational hygiene:
 Contaminated clothing should be changed before entering eating areas.
 Do not eat or drink while working.
 Conditions for safe storage, including any incompatibilities
 Always keep in a well ventilated place.
 Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
 Keep away from food, drink and feed.
 Incompatible materials:
 None in particular.
 Instructions as regards storage premises:
 Cool and adequately ventilated.
 Storage temperature:
 Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Manganese dioxide - CAS: 1313-13-9

- OEL Type: OSHA PEL - TWA: 5 mg/m³ - Notes: (as Mn)

- OEL Type: ACGIH - TWA: 0.02 mg/m³ - Notes: (as Mn) Respirable

fraction.

- OEL Type: ACGIH - TWA: 0.1 mg/m³ - Notes: (as Mn) Inhalable

fraction.

Magnesium Chromate - CAS: 13423-61-5

- OEL Type: TWA - TWA: 0.05 mg/m³

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	Black	--	--
Odour:	Negligible oily	--	--

Safety Data Sheet (HazCom 2012)
CS-3213 Part B Class B - CS3213BB

	odor		
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash Point (°F):	200 °F	--	--
Flash point (°C):	93 °C	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	N.A.	--	--
Relative density:	16.981 lbs/gallon	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	Material supports combustion	--	--
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

None

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

Safety Data Sheet (HazCom 2012)
CS-3213 Part B Class B - CS3213BB

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

CS-3213 Part B Class B

Acute toxicity

The product is classified: Acute Tox. 4 H302; Acute Tox. 3 H331

ATEmix - Oral 517.54 mg/kg bw

ATEmix - Dermal 15582.8 mg/kg bw

ATEmix - Inhalation (Vapours) 5.07813 mg/l

Skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

Serious eye damage/irritation

The product is classified: Eye Dam. 1 H318

Respiratory or skin sensitisation

The product is classified: Skin Sens. 1 H317

Germ cell mutagenicity

The product is classified: Muta. 1B H340

Carcinogenicity

The product is classified: Carc. 1B H350

Reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

STOT-single exposure

Not classified

Based on available data, the classification criteria are not met

STOT-repeated exposure

The product is classified: STOT RE 2 H373

Aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

Manganese dioxide - CAS: 1313-13-9

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat \geq 14900 mg/kg

Magnesium Chromate - CAS: 13423-61-5

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 3478 mg/kg

Substance(s) listed on the NTP report on Carcinogens:

Magnesium Chromate.

Substance(s) listed on the IARC Monographs:

Magnesium Chromate - Group 1.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

CS-3213 Part B Class B

The product is classified: Aquatic Chronic 2 - H411

Persistence and degradability

N.A.

Bioaccumulative potential

Safety Data Sheet (HazCom 2012) CS-3213 Part B Class B - CS3213BB

N.A.
 Mobility in soil
 N.A.
 Other adverse effects
 No harmful effects expected.

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION



UN number

ADR-UN Number: 3082

DOT number: UN3082

IATA-UN Number: 3082

IMDG-UN Number: 3082

UN proper shipping name

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Magnesium Chromate)

DOT-Shipping Name: Environmentally hazardous substance, liquid, n.o.s.(Magnesium Chromate)

IATA-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Magnesium Chromate)

IMDG-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Magnesium Chromate)

Transport hazard class(es)

ADR-Class: 9

DOT Hazard Class: 9

ADR - Hazard identification number: 90

IATA-Class: 9

IATA-Label: 9

IMDG-Class: 9

Packing group

ADR-Packing Group: III

DOT Packing group: III

IATA-Packing group: III

IMDG-Packing group: III

Environmental hazards

ADR-Environmental Pollutant: Yes

IMDG-Marine pollutant: Yes

Most important toxic component: Magnesium Chromate

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions

DOT Special provisions: 8, 146, 173, 335,441, IB3, T4, TP1, TP29

DOT Labels: 6.1

ADR-Subsidiary hazards: -

Safety Data Sheet (HazCom 2012)
CS-3213 Part B Class B - CS3213BB

ADR-S.P.: 274 335 375 601
 ADR-Transport category (Tunnel restriction code): 3 (-)
 IATA-Passenger Aircraft: 964
 IATA-Subsidiary hazards: -
 IATA-Cargo Aircraft: 964
 IATA-S.P.: A97 A158 A197 A215
 IATA-ERG: 9L
 IMDG-EmS: F-A , S-F
 IMDG-Subsidiary hazards: -
 IMDG-Stowage and handling: Category A
 IMDG-Segregation: -
 Q.L.: 5L
 Q.E.: E1

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: All the components of this product are listed as active on or are exempt from the TSCA Inventory..

TSCA sections for substances listed in section 3:

Manganese dioxide is listed in TSCA Section 8b

Magnesium Chromate is listed in TSCA Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 Extremely Hazardous Substances: no substances listed.

Section 304 Hazardous substances: no substances listed.

Section 313 Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

No substances listed.

CAA - Clean Air Act

CAA listed substances:

None.

CWA - Clean Water Act

CWA listed substances:

None.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Magnesium Chromate.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

No substances listed.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Magnesium Chromate.

Safety Data Sheet (HazCom 2012) CS-3213 Part B Class B - CS3213BB

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

- H302 Harmful if swallowed.
- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
- H301 Toxic if swallowed.
- H312 Harmful in contact with skin.
- H330 Fatal if inhaled.
- H318 Causes serious eye damage.
- H317 May cause an allergic skin reaction.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H335 May cause respiratory irritation.
- H410 Very toxic to aquatic life with long lasting effects.

According to TSCA section 3(2)(B)(i) : a hydrated form of a chemical substance is considered a mixture of the corresponding anhydrous form and water.

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

- | | |
|-----------|--|
| ADR: | European Agreement concerning the International Carriage of Dangerous Goods by Road. |
| ATE: | Acute Toxicity Estimate |
| ATEmix: | Acute toxicity Estimate (Mixtures) |
| CAS: | Chemical Abstracts Service (division of the American Chemical Society). |
| CLP: | Classification, Labeling, Packaging. |
| DNEL: | Derived No Effect Level. |
| EINECS: | European Inventory of Existing Commercial Chemical Substances. |
| GHS: | Globally Harmonized System of Classification and Labeling of Chemicals. |
| HMIS: | Hazardous Materials Identification System |
| IARC: | International Agency for Research on Cancer |
| IATA: | International Air Transport Association. |
| IATA-DGR: | Dangerous Goods Regulation by the "International Air Transport Association" (IATA). |
| ICAO: | International Civil Aviation Organization. |
| ICAO-TI: | Technical Instructions by the "International Civil Aviation Organization" (ICAO). |
| IMDG: | International Maritime Code for Dangerous Goods. |
| INCI: | International Nomenclature of Cosmetic Ingredients. |
| KSt: | Explosion coefficient. |
| LC50: | Lethal concentration, for 50 percent of test population. |

Safety Data Sheet (HazCom 2012)
CS-3213 Part B Class B - CS3213BB

LD50: Lethal dose, for 50 percent of test population.
NFPA: National Fire Protection Association
NIOSH: National Institute for Occupational Safety and Health
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PNEC: Predicted No Effect Concentration.
RID: Regulation Concerning the International Transport of Dangerous Goods
by Rail.

TOTAL
VOC'S
(TVOC) /
NONEXEMPT
VOC'S
(CVOC):
Using
California
South Coast
Air Quality
Management
District
(SCAQMD)
Rule 1143.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average

Safety Data Sheet date: 4/17/2025, version 1