

Safety Data Sheet (HazCom 2012)
CS-4406 Part A Class B - CS4406AB

Safety Data Sheet date: 1/15/2025, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: CS-4406 Part A Class B

Other means of identification:

SDS code: CS4406AB

Recommended use of the chemical and restrictions on use

Recommended use:

Industrial uses

Sealant

Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Manufacturers:

Flamemaster Corp., 13576 Desmond Street, Pacoima, CA 91331 - USA CAGE Code: 14439

Distributors:

Flamemaster Corp., Tel 818-890-1401, Fax 818-890-6001, www.flamemaster.com

Competent person responsible for the safety data sheet:

Flamemaster Corp., Tel 818-890-1401, Fax 818-890-6001, www.flamemaster.com

Emergency phone number:

CHEMTEL: +1-813-248-0585 (International); 1-800-255-3924 (USA)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

Warning, Flam. Liq. 4, Combustible liquid.



Warning, Skin Sens. 1, May cause an allergic skin reaction.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictograms:



Warning

Hazard statements:

H227 Combustible liquid.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water/...

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Safety Data Sheet (HazCom 2012)
CS-4406 Part A Class B - CS4406AB

P370+P378 In case of fire: Use Alcohol foam, carbon dioxide (CO₂), dry chemical, water spray/water fog to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 60% - < 70% Aliphatic polysulfide polymer

CAS: 68611-50-7

US-HAE/C3 Aquatic Chronic 3 H412

>= 1% - < 3% Methyl ethyl ketone

CAS: 78-93-3



A.2/2 Skin Irrit. 2 H315



B.6/2 Flam. Liq. 2 H225



A.3/2A Eye Irrit. 2A H319



A.8/3 STOT SE 3 H336

>= 1% - < 3% Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]

REACH No.: Polymer-----, CAS: 25036-25-3



A.8/3 STOT SE 3 H336



A.2/2 Skin Irrit. 2 H315



A.3/2A Eye Irrit. 2A H319



A.4.2/1 Skin Sens. 1 H317

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

Safety Data Sheet (HazCom 2012) CS-4406 Part A Class B - CS4406AB

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
In case of Ingestion:
Do not induce vomiting. Obtain a medical examination.
In case of Inhalation:
Remove casualty to fresh air and keep warm and at rest.
Most important symptoms/effects, acute and delayed
None
Indication of immediate medical attention and special treatment needed
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
Treatment:
No particular treatment.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:
In case of fire: Use Alcohol foam, carbon dioxide (CO₂), dry chemical, water spray/water fog to extinguish.
Unsuitable extinguishing media
None in particular.
Specific hazards arising from the chemical
Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
Hazardous combustion products:
None
Explosive properties: N.A.
Oxidizing properties: N.A.
Special protective equipment and precautions for fire-fighters
Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures
Wear personal protection equipment.
Remove persons to safety.
See protective measures under point 7 and 8.
Methods and materials for containment and cleaning up
Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Do not use on extensive surface areas in premises where there are occupants.
Don't use empty container before they have been cleaned.
Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
Conditions for safe storage, including any incompatibilities
Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
Incompatible materials:

Safety Data Sheet (HazCom 2012) CS-4406 Part A Class B - CS4406AB

None in particular.
 Instructions as regards storage premises:
 Cool and adequately ventilated.
 Storage temperature:
 Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Methyl ethyl ketone - CAS: 78-93-3

- OEL Type: ACGIH - TWA: 200 ppm - STEL: 200 mg/m³ - Notes: ACGIH OEL TWA
- OEL Type: OSHA PEL - TWA: 590 mg/m³, 200 ppm
- OEL Type: EU - TWA(8h): 600 mg/m³, 200 ppm - STEL: 900 mg/m³, 300 ppm

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	Off-white	--	--
Odour:	Polysulfide Odor	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash Point (°F):	200	--	--
Flash point (°C):	93	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	N.A.	--	--
Relative density:	N.A.	--	--

Safety Data Sheet (HazCom 2012)
CS-4406 Part A Class B - CS4406AB

Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

None

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

CS-4406 Part A Class B

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

Skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

Serious eye damage/irritation

Not classified

Based on available data, the classification criteria are not met

Respiratory or skin sensitisation

The product is classified: Skin Sens. 1 H317

Germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

Carcinogenicity

Safety Data Sheet (HazCom 2012)
CS-4406 Part A Class B - CS4406AB

Not classified
 Based on available data, the classification criteria are not met

Reproductive toxicity
 Not classified
 Based on available data, the classification criteria are not met

STOT-single exposure
 Not classified
 Based on available data, the classification criteria are not met

STOT-repeated exposure
 Not classified
 Based on available data, the classification criteria are not met

Aspiration hazard
 Not classified
 Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:
 Aliphatic polysulfide polymer - CAS: 68611-50-7
 Acute toxicity:
 Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Methyl ethyl ketone - CAS: 78-93-3
 Acute toxicity
 ATE - Oral 2737 mg/kg bw
 ATE - Dermal 6480 mg/kg bw
 ATE - Inhalation (Vapours) 34 mg/l
 ATE - Inhalation (Dust/mist) 34 mg/l
 ATE - Inhalation (Gas) 11300 ppmV
 Test: LD50 - Route: Oral - Species: Rat = 2193 mg/kg - Source: OECD 423
 Test: LD50 - Route: Skin - Species: Rabbit > 10 ml/kg - Duration: 24 hours - Source: OECD 402
 Test: LC50 - Route: Inhalation - Species: Rat = 34 mg/kg - Duration: 4h
 Test: LC50 - Route: Inhalation - Species: Rat = 11300 ppm - Duration: 4h
 Test: ATE - Route: Oral = 2737.000 mg/kg bw
 Test: ATE - Route: Skin = 6480.000 mg/kg bw
 Test: ATE - Route: Inhalation Gas = 11300.000 ppmV - Duration: 4h
 Test: ATE - Route: Inhalation Vapour = 34.000 mg/l - Duration: 4h
 Test: ATE - Route: Inhalation (dust, mist) = 34.000 mg/l - Duration: 4h

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1 phenyleneoxymethylene)]bis[oxirane] - CAS: 25036-25-3
 Acute toxicity:
 Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg
 Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

None.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

CS-4406 Part A Class B

The product is classified: Aquatic Chronic 3 - H412

Safety Data Sheet (HazCom 2012)
CS-4406 Part A Class B - CS4406AB

Methyl ethyl ketone - CAS: 78-93-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2993 mg/l - Duration h: 96 - Notes: Pimephalales promelas, OECD 203

Endpoint: EC50 - Species: Daphnia Magna = 308 mg/l - Duration h: 48 - Notes: OECD 202

Endpoint: ErC50 - Species: Algae = 1972 mg/l - Duration h: 72 - Notes: OECD 201

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

No harmful effects expected.

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number

Not classified as dangerous in the meaning of ADR, IATA and IMDG transport regulations.

UN proper shipping name

N.A.

Transport hazard class(es)

N.A.

Packing group

N.A.

Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions

N.A.

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: All the components of this product are listed as active on or are exempt from the TSCA Inventory..

TSCA sections for substances listed in section 3:

Aliphatic polysulfide polymer is listed in TSCA Section 8b

Methyl ethyl ketone is listed in TSCA Section 8, Section 8b

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1 phenyleneoxymethylene)]bis[oxirane] is listed in TSCA Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 Extremely Hazardous Substances: no substances listed.

Safety Data Sheet (HazCom 2012)
CS-4406 Part A Class B - CS4406AB

Section 304 Hazardous substances: Methyl ethyl ketone.
Section 313 Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
Substance(s) listed under CERCLA: Methyl ethyl ketone - Reportable quantity: 5000 pounds.
Reportable quantity for mixture: 326175.8758 pounds.

CAA - Clean Air Act
CAA listed substances:
Methyl ethyl ketone is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act
CWA listed substances:
None.

USA - State specific regulations

California Proposition 65
Substance(s) listed under California Proposition 65:
None.

Massachusetts Right to know
Substance(s) listed under Massachusetts Right to know:
Methyl ethyl ketone.

New Jersey Right to know
Substance(s) listed under New Jersey Right to know:
Methyl ethyl ketone.

Pennsylvania Right to know
Substance(s) listed under Pennsylvania Right to know:
Methyl ethyl ketone.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:
H412 Harmful to aquatic life with long lasting effects.
H315 Causes skin irritation.
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H317 May cause an allergic skin reaction.

According to TSCA section 3(2)(B)(i) : a hydrated form of a chemical substance is considered a mixture of the corresponding anhydrous form and water.

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Safety Data Sheet (HazCom 2012)
CS-4406 Part A Class B - CS4406AB

	Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
TOTAL VOC'S (TVOC) / NONEXEMPT VOC'S (CVOC):	
Using California South Coast Air Quality Management District (SCAQMD) Rule 1143.	
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average

Safety Data Sheet date: 1/15/2025, version 1