

Safety Data Sheet date: 1/20/2025, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: S-885 / S-886 Part B

Other means of identification:

SDS code: S885S886B

Recommended use of the chemical and restrictions on use

Recommended use:

Industrial uses

Sealant

Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party Manufacturers:

--

Flamemaster Corp., 13576 Desmond Street, Pacoima, CA 9 133 1 - USA CAGE Code:

14439

Distributors:

Flamemaster Corp., Tel 818-890-1401, Fax 818-890-6001, www.flamemaster.com

Competent person responsible for the safety data sheet:

Flamemaster Corp., Tel 818-890-1401, Fax 818-890-6001, www.flamemaster.com

Emergency phone number:

CHEMTEL: +1-813-248-0585 (International); 1-800-255-3924 (USA)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

- Danger, Flam. Lig. 2, Highly flammable liquid and vapour.
- Warning, Skin Irrit. 2, Causes skin irritation.
- Warning, Eye Irrit. 2A, Causes serious eye irritation.
- Warning, Skin Sens. 1, May cause an allergic skin reaction.
- Warning, Muta. 2, Suspected of causing genetic defects.
- Danger, Repr. 1B, May damage fertility or the unborn child.
- Danger, STOT SE 1, Causes damage to organs.
- Warning, STOT SE 3, May cause drowsiness or dizziness.
- Danger, STOT RE 1, Causes damage to organs through prolonged or repeated exposure.

Aquatic Acute 2, Toxic to aquatic life.

Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.



Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H360 May damage fertility or the unborn child.

H370 Causes damage to organs.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water/...

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor/...

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER/doctor/... if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use Alcohol foam, carbon dioxide (CO2), dry chemical, water spray/water fog to extinguish.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.



P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 30% - < 40% Toluene

CAS: 108-88-3

B.6/2 Flam. Liq. 2 H225

4.2/2 Skin Irrit. 2 H315

4.3/2A Eye Irrit. 2A H319

♦ A.7/2 Repr. 2 H361d

A.8/3 STOT SE 3 H336

A.9/2 STOT RE 2 H373

A.10/1 Asp. Tox. 1 H304

US-HAE/A2 Aquatic Acute 2 H401 US-HAE/C3 Aquatic Chronic 3 H412

>= 3% - < 5% Dibutyltin dilaurate

CAS: 77-58-7

4.3/2A Eye Irrit. 2A H319

A.4.2/1 Skin Sens. 1 H317

A.5/2 Muta. 2 H341

A.7/1B Repr. 1B H360

♠ A.8/1 STOT SE 1 H370

♦ A.9/1 STOT RE 1 H372





US-HAE/A1 Aquatic Acute 1 H400



US-HAE/C1 Aquatic Chronic 1 H410

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire: Use Alcohol foam, carbon dioxide (CO2), dry chemical, water spray/water fog to extinguish.

Unsuitable extinguishing media

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.A. Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.



7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Toluene - CAS: 108-88-3

- OEL Type: ACGIH - TWA(8h): 20 ppm

- OEL Type: NIOSH REL - TWA: 375 mg/m3, 100 ppm

- OEL Type: ST - TWA: 560 mg/m3, 150 ppm

- OEL Type: TWA - TWA: 200 ppm

- OEL Type: EU - TWA(8h): 192 mg/m3, 50 ppm - STEL: 384 mg/m3, 100 ppm -

Notes: Skin

Dibutyltin dilaurate - CAS: 77-58-7

- OEL Type: ACGIH - TWA: 0.1 mg/m3

- OEL Type: STEL - TWA: 0.2 mg/m3

- OEL Type: OSHA PEL - TWA: 0.1 mg/m3

- OEL Type: NIOSH REL - TWA: 0.1 mg/m3

- OEL Type: TWA - TWA: 0.1 mg/m3

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

Ν̈.Α.

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:



Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value	Method:	Notes
Physical state:	Liquid		
Colour:	White		
Odour:	N.A.		
Odour threshold:	N.A.		
pH:	N.A.		
Melting point / freezing point:	N.A.		
Initial boiling point and boiling range:	182 F		
Flash Point (°F):	40		
Flash point (°C):	4.4		
Evaporation rate:	N.A.		
Solid/gas flammability:	N.A.		
Upper/lower flammability	N.A.		
or explosive limits:			
Vapour pressure:	N.A.		
Vapour density:	3.2		
Relative density:	N.A.		
Solubility in water:	N.A.		
Solubility in oil:	N.A.		
Partition coefficient	N.A.		
(n-octanol/water):			
Auto-ignition temperature:	N.A.		
Decomposition	N.A.		
temperature:			
Viscosity:	N.A.		
Explosive properties:	N.A.		
Oxidizing properties:	N.A.		

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.		
Fat Solubility:	N.A.		
Conductivity:	N.A.		
Substance Groups	N.A.		
relevant properties			

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)



Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

S-885 / S-886 Part B

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

Skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

Serious eye damage/irritation

The product is classified: Eye Irrit. 2A H319

Respiratory or skin sensitisation

The product is classified: Skin Sens. 1 H317

Germ cell mutagenicity

The product is classified: Muta. 2 H341

Carcinogenicity

Not classified

Based on available data, the classification criteria are not met

Reproductive toxicity

The product is classified: Repr. 1B H360

STOT-single exposure

The product is classified: STOT SE 1 H370; STOT SE 3 H336

STOT-repeated exposure

The product is classified: STOT RE 1 H372

Aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

Toluene - CAS: 108-88-3

Acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat (Male, female) 28.1 mg/l - Notes: The

component/mixture is moderately toxic after

short term inhalation.

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Notes: The

component/mixture is moderately toxic after

single contact with skin.

Test: LD50 - Route: Oral - Species: Rat (male) 5580 mg/kg

Dibutyltin dilaurate - CAS: 77-58-7

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:



Toluene - Group 3.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

S-885 / S-886 Part B

The product is classified: Aquatic Acute 2 - H401; Aquatic Chronic 2 - H411

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

No harmful effects expected.

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION





UN number

ADR-UN Number: 1139

DOT number: UN1139

IATA-UN Number: 1139 IMDG-UN Number: 1139

UN proper shipping name

ADR-Shipping Name: COATING SOLUTION

DOT-Shipping Name: Coating solution (includes surface treatments or coatings used for

industrial or other purposes such as vehicle undercoating, drum or barrel lining)

IATA-Shipping Name: COATING SOLUTION IMDG-Shipping Name: COATING SOLUTION

Transport hazard class(es)

ADR-Class: 3

DOT Hazard Class: 3

ADR - Hazard identification number: 33

IATA-Class: 3 IATA-Label: 3 IMDG-Class: 3

Packing group

ADR-Packing Group: II
DOT Packing group: II
IATA-Packing group: II
IMDG-Packing group: II



Environmental hazards

ADR-Enviromental Pollutant: Yes IMDG-Marine pollutant: Yes

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions

DOT Special provisions: 149, IB2, T4, TP1, TP8

ADR-Subsidiary hazards:

ADR-S.P.: 640D

ADR-Transport category (Tunnel restriction code): 2 (D/E)

IATA-Passenger Aircraft: 353
IATA-Subsidiary hazards: IATA-Cargo Aircraft: 364
IATA-S.P.: A3
IATA-ERG: 3L

IMDG-EmS: F-E , <u>S-E</u>

IMDG-Subsidiary hazards: -

IMDG-Stowage and handling: Category B

IMDG-Segregation: -

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: All the components of this product are listed as active on or are exempt from the TSCA Inventory..

TSCA sections for substances listed in section 3:

Toluene is listed in TSCA Section 8a - CAIR, Section 8d HSDR, Section 8b Dibutyltin dilaurate is listed in TSCA Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 Extremely Hazardous Substances: no substances listed.

Section 304 Hazardous substances: Toluene. Section 313 Toxic chemical list: Toluene.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA: Toluene - Reportable quantity: 1000 pounds. Reportable quantity for mixture: 2861.119854 pounds.

CAA - Clean Air Act

CAA listed substances:

Toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

Toluene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

Toluene - Listed as reproductive toxicant.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:



Toluene.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Toluene.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Toluene.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H360 May damage fertility or the unborn child.

H370 Causes damage to organs.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

According to TSCA section 3(2)(B)(i): a hydrated form of a chemical substance is considered a mixture of the corresponding anhydrous form and water.

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.
GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer



IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

TOTAL VOC'S (TVOC) / NONEXEMPT

NONEXEMPT VOC'S (CVOC): Using California South Coast Air Quality Management District (SCAQMD) Rule 1143.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average

Safety Data Sheet date: 1/20/2025, version 1