

**Safety Data Sheet (HazCom 2012)**  
**CS-3201 Part A Class B Tan - CS3201ABT**

**Safety Data Sheet date: 4/24/2025, version 1**

## 1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: CS-3201 Part A Class B Tan

Other means of identification:

SDS code: CS3201ABT

Recommended use of the chemical and restrictions on use

Recommended use:

Industrial uses

Sealant

Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Manufacturers:

Flamemaster Corp., 13576 Desmond Street, Pacoima, CA 91331 - USA CAGE Code: 14439

Distributors:

Flamemaster Corp., Tel 818-890-1401, Fax 818-890-6001, [www.flamemaster.com](http://www.flamemaster.com)

Competent person responsible for the safety data sheet:

Flamemaster Corp., Tel 818-890-1401, Fax 818-890-6001, [www.flamemaster.com](http://www.flamemaster.com)

Emergency phone number:

CHEMTEL: +1-813-248-0585 (International); 1-800-255-3924 (USA)

## 2. HAZARD(S) IDENTIFICATION

Classification of the chemical



Warning, Skin Sens. 1, May cause an allergic skin reaction.



Warning, Repr. 2, Suspected of damaging fertility or the unborn child.

Aquatic Acute 3, Harmful to aquatic life.

Label elements

Hazard pictograms:



Warning

Hazard statements:

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H402 Harmful to aquatic life.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water/...

P308+P313 IF exposed or concerned: Get medical advice/attention.

## Safety Data Sheet (HazCom 2012)

### CS-3201 Part A Class B Tan - CS3201ABT

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

---

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 60% - < 70% Aliphatic polysulfide polymer

CAS: 68611-50-7

US-HAE/A3 Aquatic Acute 3 H402

>= 1% - < 3% Bisphenol A - epoxy resins, number average MW >700-<1100

CAS: 67924-34-9



B.6/2 Flam. Liq. 2 H225



A.3/2A Eye Irrit. 2A H319



A.2/2 Skin Irrit. 2 H315



A.4.2/1 Skin Sens. 1 H317



A.7/2 Repr. 2 H361d

US-HAE/A2 Aquatic Acute 2 H401

US-HAE/C3 Aquatic Chronic 3 H412

>= 0.3% - < 0.5% Toluene

CAS: 108-88-3



B.6/2 Flam. Liq. 2 H225



A.2/2 Skin Irrit. 2 H315



A.3/2A Eye Irrit. 2A H319



A.7/2 Repr. 2 H361d



A.8/3 STOT SE 3 H336



A.9/2 STOT RE 2 H373

## Safety Data Sheet (HazCom 2012) CS-3201 Part A Class B Tan - CS3201ABT



A.10/1 Asp. Tox. 1 H304

US-HAE/A2 Aquatic Acute 2 H401  
US-HAE/C3 Aquatic Chronic 3 H412

---

### 4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

---

### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Water.

Carbon dioxide (CO<sub>2</sub>).

Unsuitable extinguishing media

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.A.

Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

---

### 7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

## Safety Data Sheet (HazCom 2012)

### CS-3201 Part A Class B Tan - CS3201ABT

Exercise the greatest care when handling or opening the container.  
 Do not use on extensive surface areas in premises where there are occupants.  
 Don't use empty container before they have been cleaned.  
 Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.  
 See also section 8 for recommended protective equipment.  
 Advice on general occupational hygiene:  
 Contaminated clothing should be changed before entering eating areas.  
 Do not eat or drink while working.  
 Conditions for safe storage, including any incompatibilities  
 Keep away from food, drink and feed.  
 Incompatible materials:  
 None in particular.  
 Instructions as regards storage premises:  
 Adequately ventilated premises.  
 Storage temperature:  
 Store at ambient temperature.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

Toluene - CAS: 108-88-3

- OEL Type: ACGIH - TWA(8h): 20 ppm
- OEL Type: NIOSH REL - TWA: 375 mg/m<sup>3</sup>, 100 ppm
- OEL Type: ST - TWA: 560 mg/m<sup>3</sup>, 150 ppm
- OEL Type: TWA - TWA: 200 ppm
- OEL Type: EU - TWA(8h): 192 mg/m<sup>3</sup>, 50 ppm - STEL: 384 mg/m<sup>3</sup>, 100 ppm -

Notes: Skin

### DNEL Exposure Limit Values

N.A.

### PNEC Exposure Limit Values

N.A.

### Appropriate engineering controls:

None

### Individual protection measures

#### Eye protection:

Use close fitting safety goggles, don't use eye lens.

#### Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

#### Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

#### Respiratory protection:

Not needed for normal use.

#### Thermal Hazards:

None

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	Black	--	--
Odour:	Polysulfide Odor	--	--
Odour threshold:	N.A.	--	--

## Safety Data Sheet (HazCom 2012)

### CS-3201 Part A Class B Tan - CS3201ABT

pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash Point (°F):	200	--	--
Flash point (°C):	93	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	N.A.	--	--
Relative density:	1.48 g/cm3	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

#### 9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

## 10. STABILITY AND REACTIVITY

#### Reactivity

Stable under normal conditions

#### Chemical stability

Stable under normal conditions

#### Possibility of hazardous reactions

None

#### Conditions to avoid

Stable under normal conditions.

#### Incompatible materials

None in particular.

#### Hazardous decomposition products

None.

## 11. TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

Toxicological information of the product:

CS-3201 Part A Class B Tan

## Safety Data Sheet (HazCom 2012)

### CS-3201 Part A Class B Tan - CS3201ABT

Acute toxicity  
 Not classified  
 Based on available data, the classification criteria are not met

Skin corrosion/irritation  
 Not classified  
 Based on available data, the classification criteria are not met

Serious eye damage/irritation  
 Not classified  
 Based on available data, the classification criteria are not met

Respiratory or skin sensitisation  
 The product is classified: Skin Sens. 1 H317

Germ cell mutagenicity  
 Not classified  
 Based on available data, the classification criteria are not met

Carcinogenicity  
 Not classified  
 Based on available data, the classification criteria are not met

Reproductive toxicity  
 The product is classified: Repr. 2 H361

STOT-single exposure  
 Not classified  
 Based on available data, the classification criteria are not met

STOT-repeated exposure  
 Not classified  
 Based on available data, the classification criteria are not met

Aspiration hazard  
 Not classified  
 Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

Aliphatic polysulfide polymer - CAS: 68611-50-7

Acute toxicity:  
 Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Bisphenol A - epoxy resins, number average MW >700-<1100 - CAS: 67924-34-9

Acute toxicity:  
 Test: LD50 - Route: Skin - Species: Rat (Male, female) > 2000 mg/kg  
 Test: LD50 - Route: Oral - Species: Rat (female) > 2000 mg/kg

Toluene - CAS: 108-88-3

Acute toxicity:  
 Test: LC50 - Route: Inhalation - Species: Rat (Male, female) 28.1 mg/l - Notes: The component/mixture is moderately toxic after short term inhalation.  
 Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Notes: The component/mixture is moderately toxic after single contact with skin.  
 Test: LD50 - Route: Oral - Species: Rat (male) 5580 mg/kg

Substance(s) listed on the NTP report on Carcinogens:  
 None.

Substance(s) listed on the IARC Monographs:  
 Toluene - Group 3.

Substance(s) listed as OSHA Carcinogen(s):  
 None.

Substance(s) listed as NIOSH Carcinogen(s):  
 None.

**Safety Data Sheet (HazCom 2012)**  
**CS-3201 Part A Class B Tan - CS3201ABT**

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

CS-3201 Part A Class B Tan

The product is classified: Aquatic Acute 3 - H402

Aliphatic polysulfide polymer - CAS: 68611-50-7

a) Aquatic acute toxicity:

Endpoint: LL50

- Species: *Oryzias latipes* > 100 mg/l - Duration h: 96

Endpoint: EL50

- Species: *Daphnia Magna* < 100 mg/l - Duration h: 48

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Crustacea > 1 mg/l

e) Plant toxicity:

Endpoint: ErL50 - Species: Algae > 100 mg/l - Duration h: 72

Toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: *Oncorhynchus mykiss* 5.5 mg/l - Duration h: 96

Endpoint: EC50 - Species: Water flea 3.78 mg/l - Duration h: 48

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: *Oncorhynchus mykiss* 1.39 mg/l - Duration h: 960

Endpoint: NOEC - Species: Water flea 0.74 mg/l - Duration h: 168

c) Bacteria toxicity:

Endpoint: EC50 - Species: bacteria 84 mg/l - Duration h: 24

### Persistence and degradability

Toluene - CAS: 108-88-3

Biodegradability: Biodegradability rate - Test: Aerobic - Duration: 20 days - %: 86 -

Notes: Readily biodegradable

### Bioaccumulative potential

Toluene - CAS: 108-88-3

Potentially bioaccumulative. - Test: BCF - Bioconcentration factor 90

### Mobility in soil

N.A.

### Other adverse effects

No harmful effects expected.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

## 14. TRANSPORT INFORMATION

### UN number

Not classified as dangerous in the meaning of ADR, IATA and IMDG transport regulations.

### UN proper shipping name

N.A.

### Transport hazard class(es)

N.A.

### Packing group

N.A.

### Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

**Safety Data Sheet (HazCom 2012)**  
**CS-3201 Part A Class B Tan - CS3201ABT**

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)  
N.A.

Special precautions  
N.A.

---

**15. REGULATORY INFORMATION**

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: All the components of this product are listed as active on or are exempt from the TSCA Inventory..

TSCA sections for substances listed in section 3:

Aliphatic polysulfide polymer is listed in TSCA Section 8b

Bisphenol A - epoxy resins, number average MW >700-<1100 is listed in TSCA Section 8b

Toluene is listed in TSCA Section 8a - CAIR, Section 8d HSDR, Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 Extremely Hazardous Substances: no substances listed.

Section 304 Hazardous substances: Toluene.

Section 313 Toxic chemical list: Toluene.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: Toluene - Reportable quantity: 1000 pounds.

Reportable quantity for mixture: 239005.7361 pounds.

CAA - Clean Air Act

CAA listed substances:

Toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

Toluene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

Toluene - Listed as reproductive toxicant.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Toluene.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Toluene.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Toluene.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:



## Safety Data Sheet (HazCom 2012)

### CS-3201 Part A Class B Tan - CS3201ABT

#### 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

- H402 Harmful to aquatic life.
- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H361d Suspected of damaging the unborn child.
- H401 Toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H304 May be fatal if swallowed and enters airways.

According to TSCA section 3(2)(B)(i) : a hydrated form of a chemical substance is considered a mixture of the corresponding anhydrous form and water.

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

- |           |  |
|-----------|--|
| ADR:      | European Agreement concerning the International Carriage of Dangerous Goods by Road. |
| ATE:      | Acute Toxicity Estimate  |
| ATEmix:   | Acute toxicity Estimate (Mixtures)   |
| CAS:      | Chemical Abstracts Service (division of the American Chemical Society).              |
| CLP:      | Classification, Labeling, Packaging.   |
| DNEL:     | Derived No Effect Level.   |
| EINECS:   | European Inventory of Existing Commercial Chemical Substances.                       |
| GHS:      | Globally Harmonized System of Classification and Labeling of Chemicals.              |
| HMIS:     | Hazardous Materials Identification System  |
| IARC:     | International Agency for Research on Cancer  |
| IATA:     | International Air Transport Association.   |
| IATA-DGR: | Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  |
| ICAO:     | International Civil Aviation Organization.   |
| ICAO-TI:  | Technical Instructions by the "International Civil Aviation Organization" (ICAO).    |
| IMDG:     | International Maritime Code for Dangerous Goods.                                     |
| INCI:     | International Nomenclature of Cosmetic Ingredients.                                  |
| KSt:      | Explosion coefficient.   |
| LC50:     | Lethal concentration, for 50 percent of test population.                             |
| LD50:     | Lethal dose, for 50 percent of test population.                                      |
| NFPA:     | National Fire Protection Association   |
| NIOSH:    | National Institute for Occupational Safety and Health                                |
| NTP:      | National Toxicology Program  |
| OSHA:     | Occupational Safety and Health Administration  |
| PNEC:     | Predicted No Effect Concentration.   |
| RID:      | Regulation Concerning the International Transport of Dangerous Goods by Rail.        |

**Safety Data Sheet (HazCom 2012)**  
**CS-3201 Part A Class B Tan - CS3201ABT**

TOTAL  
VOC'S  
(TVOC) /  
NONEXEMPT  
VOC'S  
(CVOC):  
Using  
California  
South Coast  
Air Quality  
Management  
District  
(SCAQMD)  
Rule 1143.

STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average

Safety Data Sheet date: 4/24/2025, version 1